



ISO 9001



catalogue of products

**PRODUKT  
POLSKI**



# About us

**Z.S.S. OSPEL Joint-Stock Company** is one of the leading manufacturers of electrical wiring accessories in Poland, boasting over 70 years of tradition and industry expertise. Our strength lies in our 100% polish capital and our continuous investment in advanced machinery, human resources, and cutting-edge technologies.

Through our knowledge, dedication and reliable approach, we have become a trusted partner for both individual customers and professional installation companies. We are proud that the OSPEL brand has become synonymous with professionalism.

### Our mission and innovation

Our mission is to provide high-quality accessories that enable the implementation of modern electrical solutions in every home. Our ambitious and creative team of engineers is deeply involved in developing new structural and functional solutions.

In response to evolving market needs and technological advancements, we have expanded our portfolio to include **innovative touch switches**, including **Wi-Fi**-enabled models that seamlessly combine modern design with smart functionality.

### Quality and standards

Our products meet the highest safety and quality standards. All items hold the necessary **certificates of conformity with current regulations**. Furthermore, since 2000, we have maintained an **ISO 9001 quality management system certification**, covering:

- Design and manufacturing
- Distribution
- Plastics processing and metalworking services

### The three pillars

Modernity, safety and aesthetics are the three pillars of our business. Thanks to advanced constructional solutions and meticulous attention to detail, OSPEL products have enjoyed long-standing recognition among customers throughout poland.

### Global reach

While we focus on nationwide wholesale distribution, our products are also successfully exported to international markets, including: **Hungary, Slovakia, Czech Republic, Romania, Bulgaria, Greece, Ukraine, Lithuania, Estonia, Latvia, Germany, Sweden, Finland, Norway, Denmark, United Kingdom and Egypt.**



# Table of contents



<b>Szafir</b>	5
<b>Aria</b>	23
<b>Sonata</b>	47
<b>Sonata Touch</b>	71
<b>Sonata Steel Inox</b>	80
<b>Sonata New Silver</b>	84
<b>Sonata Wireless control</b>	89
<b>Impresja</b>	95
<b>As</b>	115
<b>As Antibacterial</b>	137
<b>Karo</b>	151
Modules <b>Keystone</b>	167
<b>Kier</b>	171
<b>Akcent</b>	183
<b>Ospel 45</b>	191
<b>Madera</b>	195
<b>Fala</b>	199
<b>Bis</b>	205
<b>Delfina</b>	211
Industrial plugs and sockets	213
Accessories	219
Diagrams of switches	223




**Innovative mounting solutions** that streamline and accelerate installation.

# Szafir

Features such as a flexible frame that masks subtle wall irregularities, ample space for cable management, and a plastic mounting bridge with locking clips for precise alignment in multiple frames are just a few of the advantages. The compact design and low profile ensure that the accessories sit flush against the wall for a sleek, aesthetic finish.

## AVAILABLE COLOURS



White – nr 00



Cashmere beige – nr 83



Silver – nr 18




Grey matt – nr 70



Black matt – nr 33



Cashmere beige



## Flush mounting switches

Screwless terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-20



ŁP-1Z/m/00  
Single pole switch 2600



ŁP-2Z/m/00  
All-or-part switch, chandelier 2601



ŁP-9Z/m/00  
Two-way + single pole switch 2608

ŁP-10Z/m/00  
Double two-way switch 2609



ŁP-3Z/m/00  
Two-way switch 2602



ŁP-4Z/m/00  
Intermediate switch 2603




ŁP-5Z/m/00  
Short-circuiting switch „light” 2604



ŁP-6Z/m/00  
Short-circuiting switch „bell” 2604



ŁP-7Z/m/00  
Venetian blind switch 2605



ŁP-7ZB/m/00  
Venetian blind switch with mechanical lock 2605



ŁP-11Z/m/00  
Double pole switch 2606



ŁP-17Z/m/00  
Double short-circuiting switch 2610



ŁP-21Z/m/00  
Short-circuiting switch 2604



ŁP-13Z/m/00  
Triple switch 2611

Screw terminals



ŁP-19Z/m/00  
Short-circuiting triple switch  
/available only in IP-20 version/ 2682

## Flush mounting switches with built-in light

Screwless terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-20



ŁP-1ZS/m/00  
Single pole switch 2600



ŁP-2ZS/m/00  
All-or-part switch, chandelier 2601



ŁP-9ZS/m/00  
Two-way + single pole switch 2608

ŁP-10ZS/m/00  
Double two-way switch 2609



ŁP-3ZS/m/00  
Two-way switch 2602



ŁP-4ZS/m/00  
Intermediate switch 2603



ŁP-5ZS/m/00  
Short-circuiting switch „light” 2604



ŁP-6ZS/m/00  
Short-circuiting switch „bell” 2604



ŁP-7ZS/m/00  
Venetian blind switch 2605



ŁP-7ZBS/m/00  
Venetian blind switch with mechanical lock 2605



ŁP-11ZS/m/00  
Double pole switch 2606



ŁP-12ZS/m/00  
Control switch 2607



ŁP-21ZS/m/00  
Short-circuiting switch 2604



ŁP-17ZS/m/00  
Double short-circuiting switch 2610




ŁP-15ZS/m/00  
Hotel switch 2649

Screw terminals

### Hotel switch

Current supply: 230V~50Hz  
 Protection rating: IP-20  
 Rated current: 16A  
 Time of delay: 3s  
 Switch works with a standard card with dimensions 86 x 54 x 0.8 mm

Equipped with a non-replaceable backlight module.



## Dimmer

Screw terminals  
Current supply: 230V~50Hz  
Protection rating: IP-20



ŁP-8ZL2/m/00  
Universal dimmer,  
load: GLS 10-250W,  
CFL 5-75W, LED 0-100W,  
functions: electronic switch,  
"time to bed"

2612

## Temperature regulators

Screw terminals  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W  
- inductive 750W  
Protection rating: IP-20



RTP-1ZN/m/00  
Temperature regulator  
with aerial sensor

2651

RTP-1Z/m/00  
Temperature regulator  
with underfloor sensor

2651

## Electronic movement detector

Screw terminals  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W,  
- fluorescent 750W  
- inductive 750W  
Protection rating: IP-20  
Way of adjustment the time of transmitter's  
switching on: 3s. – 5min.  
Angle of movement detection's field: 136°  
Field of activity: 7m  
Works with LED light



ŁP-16Z/m/00 2650  
Electronic movement detector

## Triple socket EURO

Screw terminals  
Rated voltage: 250V  
Rated current: 2,5A  
Protection rating: IP-20



GP-3Z/m/00  
Triple socket EURO

2626



GP-3ZP/m/00  
Triple socket EURO  
with shutters

2626

## Single socket with ground with USB A+C charger

Screwless terminals  
Rated voltage:  
- input: 230V~ 50Hz (max 0,3A)  
- output A or C: 5VDC/ 3A; 9VDC/ 2,22A; 12VDC/ 1,67A  
- output A+C: 5VDC/ 3,4A max 20W  
Protection rating IP-20  
Doesn't work with surface mounting wall frames  
Standard fast charger



GP-1ZZPUSBAC/m/00  
Single socket with ground,  
with shutters,  
with USB A+C charger

2687

## USB A+C charger

Screw terminals  
Rated voltage:  
- input: 230V~ 50Hz (max 0,3A)  
- output A or C: 5VDC/ 2,1A; 9VDC/ 1,67A;  
12VDC/ 1A  
- output A+C: 5VDC/ 2,1A max 12W  
Protection rating: IP-20  
Standard fast charger



GPUSB-2Z/m/00 2683  
USB A+C charger

## Flush mounting socket outlets

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-20



GP-1Z/m/00 2614  
Single socket



GP-1ZZP/m/00 2615  
Single socket with ground,  
with shutters



GP-1ZZD/m/00 2616  
Single socket with ground DATA



GPH-1ZZ/m/00/d 2619  
Hermetic socket  
with ground, IP-44



GP-1ZP/m/00 2614  
Single socket with shutters



GP-1ZS/m/00 2618  
Single socket  
with ground schuko



GP-1ZZDP/m/00 2616  
Single socket with ground DATA,  
with shutters



GPH-1ZZP/m/00/d 2619  
Hermetic socket  
with ground, IP-44,  
with shutters



GP-1ZZ/m/00 2615  
Single socket with ground



GP-1ZSP/m/00 2618  
Single socket with ground  
schuko with shutters



GP-1ZZK/m/00 2617  
Single socket with ground DATA,  
with access key



GPH-1ZS/m/00/d 2620  
Hermetic socket with ground schuko,  
IP-44



GPH-1ZSP/m/00/d 2620  
Hermetic socket with ground schuko,  
IP-44, with shutters

Hermetic sockets in silver, grey matt and black matt colours are offered only with transparent lid. Hermetic sockets in white and cashmere beige colours are offered also with lid in product's colour. After right product's code write .../00/w for products in white colour or .../83/w for products in cashmere beige colour.

## Flush mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20  
 Compatible with multi-gang frames



GP-2ZR/m/00  
Twin socket 2623



GP-2ZRZ/m/00  
Twin socket with ground 2624



GP-2ZRZP/m/00  
Twin socket with ground with shutters 2624

## Flush mounting socket outlets (sold entire)

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-2Z/00  
Twin socket 2621



GP-2ZZ/00  
Twin socket with ground 2622



GP-2ZZP/00  
Twin socket with ground, with shutters 2622



GP-2ZC/00  
Twin socket with ground, without changing phase 2627




GP-2ZS/00  
Twin socket with ground schuko 2625



GP-2ZSP/00  
Twin socket with ground schuko with shutters 2625

AVAILABLE COLOURS



## Equipotential socket



GPE-1Z/m/00 \*  
Single equipotential socket 2645



GPE-2Z/m/00 \*  
Twin equipotential socket 2646



WKE\*  
Plug into the equipotential socket 1571

## Antenna subscribers



GPA-1ZF/m/00 2633  
Single, terminal antenna RTV subscriber, type F



GPA-2ZF/m/00 2634  
Twin, terminal antenna RTV subscriber, type F



GPA-10ZP/m/00\* 2628  
Through antenna RTV subscriber attenuation coefficient 10 dB

GPA-14ZP/m/00\* 2628  
Through antenna RTV subscriber attenuation coefficient 14 dB

GPA-16ZP/m/00\* 2628  
Through antenna RTV subscriber attenuation coefficient 16 dB



GPA-10ZPZ/m/00\* 2628  
Terminal antenna RTV subscriber attenuation coefficient 10 dB



GPA-ZK/m/00 2629  
Terminal antenna RTV subscriber attenuation coefficient 2,5-3 dB



GPA-ZS/m/00 2630  
Terminal antenna RTV-SAT subscriber, attenuation coefficient 1,5-2 dB



GPA-ZSP/m/00\* 2630  
Through antenna RTV-SAT subscriber attenuation coefficient 1,2 dB



GPA-Z2S/m/00 2632  
Terminal antenna RTV-SAT subscriber with two outlets SAT attenuation coefficient 1,5 dB



GPA-ZD/m/00\* 2631  
Terminal antenna RTV-DATA subscriber

\* on request

## Telephone sockets

Connection IDC



GPT-1Z/m/00  
Single telephone socket

2635



GPT-2ZN/m/00  
Twin telephone socket, independent

2636

## Loudspeaker sockets



GG-1Z/m/00  
Single loudspeaker socket  
connection of lines ability 0,75mm<sup>2</sup>

2642



GG-2Z/m/00  
Twin loudspeaker socket  
connection of lines ability 0,75mm<sup>2</sup>

2643



GGN-1Z/m/00  
Single loudspeaker socket  
connection of lines ability 6mm<sup>2</sup>

2644

## Computer sockets

Connection IDC



GPK-1Z/K/m/00  
Single computer socket,  
5e class, MMC


2637



GPK-2Z/K/m/00  
Twin computer socket,  
5e class, MMC

2639

## AVAILABLE COLOURS



## Sockets covers Keystone type



GPK-1Z/p/00  
Single computer socket cover,  
flat

2637



GPK-1ZS/p/00  
Single computer socket cover,  
slant

2638



GPK-2Z/p/00  
Twin computer socket cover,  
flat

2639



GPK-2ZS/p/00  
Twin computer socket cover,  
slant

2640

Modules which can be mounted in these socket covers are on page 167.

## Accessories for switches IP-44



ZU-1Z  
Sealing set for switches IP-44

2685

There is a possibility to mount switches with protection rating IP-20 as switches with IP-44, to do that, must be bought sealing set presented above.

## Cable terminal



GPPK-1Z/m/00  
Cable terminal

2647

## Blank cover



Z-1Z/m/00  
Blank cover

2648

## Protective cover



O-1Z  
Protective cover

2686

## Wall frames



PNP-1U/00  
Single wall frame

2161

PNP-2U/00  
Twin wall frame

2162

PNP-3U/00  
Threefold wall frame

2163


PNP-4U/00  
Fourfold wall frame

2164

PNP-5U/00  
Fivefold wall frame

2165





## Surrounds Standard

white		cashmere beige		
R-1Z/00 Single surround	2652	R-1Z/83 Single surround	2652	
R-2Z/00 Twin surround	2653	R-2Z/83 Twin surround	2653	
R-3Z/00 Threefold surround	2654	R-3Z/83 Threefold surround	2654	
R-4Z/00 Fourfold surround	2655	R-4Z/83 Fourfold surround	2655	
R-5Z/00 Fivefold surround	2656	R-5Z/83 Fivefold surround	2656	

## Surrounds Standard for sets IP-44

white		cashmere beige		
RH-1Z/00 Single surround	2652	RH-1Z/83 Single surround	2652	
RH-2Z/00 Twin surround	2653	RH-2Z/83 Twin surround	2653	
RH-3Z/00 Threefold surround	2654	RH-3Z/83 Threefold surround	2654	
RH-4Z/00 Fourfold surround	2655	RH-4Z/83 Fourfold surround	2655	
RH-5Z/00 Fivefold surround	2656	RH-5Z/83 Fivefold surround	2656	

## Surrounds Metallic

silver		grey matt		black matt		
R-1Z/18 Single surround	2652	R-1Z/70 Single surround	2652	R-1Z/33 Single surround	2652	
R-2Z/18 Twin surround	2653	R-2Z/70 Twin surround	2653	R-2Z/33 Twin surround	2653	
R-3Z/18 Threefold surround	2654	R-3Z/70 Threefold surround	2654	R-3Z/33 Threefold surround	2654	
R-4Z/18 Fourfold surround	2655	R-4Z/70 Fourfold surround	2655	R-4Z/33 Fourfold surround	2655	
R-5Z/18 Fivefold surround	2656	R-5Z/70 Fivefold surround	2656	R-5Z/33 Fivefold surround	2656	

## Surrounds Metallic for sets IP-44

silver		grey matt		black matt		
RH-1Z/18 Single surround	2652	RH-1Z/70 Single surround	2652	RH-1Z/33 Single surround	2652	
RH-2Z/18 Twin surround	2653	RH-2Z/70 Twin surround	2653	RH-2Z/33 Twin surround	2653	
RH-3Z/18 Threefold surround	2654	RH-3Z/70 Threefold surround	2654	RH-3Z/33 Threefold surround	2654	
RH-4Z/18 Fourfold surround	2655	RH-4Z/70 Fourfold surround	2655	RH-4Z/33 Fourfold surround	2655	
RH-5Z/18 Fivefold surround	2656	RH-5Z/70 Fivefold surround	2656	RH-5Z/33 Fivefold surround	2656	

Presented surrounds are universal, the products can be mounted in horizontal and vertical position.

Presented surrounds are universal, the products can be mounted in horizontal and vertical position.

## Example order


To order single pole switch in white colour must be ordered:

**ŁP-1Z/m/00**  
**R-1Z/00**




To order single socket with ground in grey matt colour must be ordered:

**GP-1ZZ/m/70**  
**R-1Z/70**



## AVAILABLE COLOURS



## Designations

Products of Szafir series are sold without external surround (\*excluding a few twin sockets). Below are written designations which must be used to place the order. After right product's code use the right number of colour, products in colour:

White – number 00,  
Cashmere beige – number 83,  
Silver – number 18,  
Grey matt – number 70,  
Black matt – number 33.

ŁP-.....Z/m	Switches - in the place marked by dots, write the right number of switch	GPT-1Z/m	Single telephone socket
ŁP-8ZL2/m	Universal dimmer	GPT-2ZN/m	Twin telephone socket, independent
ŁP-15ZS/m	Hotel switch	GPA-1ZF/m	Single, terminal antenna RTV subscriber, type F
RTP-1Z/m	Temperature regulator	GPA-2ZF/m	Twin, terminal antenna RTV subscriber, type F
GP-16Z/m	Electronic movement detector	GPA-ZK/m	Terminal antenna RTV subscriber
GP-1Z/m	Single socket	GPA-10ZPZ/m	Through antenna RTV subscriber (on request)
GP-1ZP/m	Single socket with shutters	GPA-10ZP/m	Through antenna RTV subscriber (on request)
GP-1ZZ/m	Single socket with ground	GPA-14ZP/m	Through antenna RTV subscriber (on request)
GP-1ZZP/m	Single socket with ground, with shutters	GPA-16ZP/m	Through antenna RTV subscriber (on request)
GP-1ZS/m	Single socket with ground schuko	GPA-ZS/m	Terminal antenna RTV-SAT subscriber
GP-1ZSP/m	Single socket with ground schuko, with shutters	GPA-ZSP/m	Through antenna RTV-SAT subscriber (on request)
GP-1ZZD/m	Single socket with ground DATA	GPA-ZZS/m	Terminal antenna RTV-SAT subscriber, with two outlets SAT
GP-1ZZDP/m	Single socket with ground DATA, with shutters	GPA-ZD/m	Terminal antenna RTV-DATA subscriber (on request)
GP-1ZZK/m	Single socket with ground DATA, with shutters	GG-1Z/m	Single loudspeaker socket
GPH-1ZZ/m	Hermetic socket with ground, IP-44	GG-2Z/m	Twin loudspeaker socket
GPH-1ZZP/m	Hermetic socket with ground, IP-44, with shutters	GGN-1Z/m	Single loudspeaker socket
GPH-1ZS/m	Hermetic socket with ground schuko, IP-44	GPK-1Z/K/m	Single computer socket, 5e class, MMC
GPH-1ZSP/m	Hermetic socket with ground schuko, IP-44, with shutters	GPK-2Z/K/m	Twin computer socket, 5e class, MMC
GP-2ZR/m	Twin socket	GPK-1Z/p	Single socket cover, flat
GP-2ZRZ/m	Twin socket with ground	GPK-2Z/p	Twin socket cover, flat
GP-2ZRZP/m	Twin socket with ground, with shutters	GPK-1ZS/p	Single computer socket cover, slant
GP-2Z	Twin socket *	GPK-2ZS/p	Twin computer socket cover, slant
GP-2ZZ	Twin socket with ground *	GPE-1Z/m	Single equipotential socket (on request)
GP-2ZC	Twin socket with ground, without changing phase *	GPE-2Z/m	Twin equipotential socket (on request)
GP-2ZS	Twin socket with ground schuko *	GPPK-1Z/m	Cable terminal
GP-2ZSP	Twin socket with ground schuko with shutters*	Z-1Z/m	Blank cover
GP-2ZZP	Twin socket with ground, with shutters*		
GP-3Z/m	Triple socket EURO		
GP-3ZP/m	Triple socket EURO with shutters		
GP-1ZZPUSBAC/m	Single socket with ground, with shutters, with USB A+C charger		
GPIUSB-2Z/m	USB A+C charger		

Quick and easy installation of wiring accessories.




Efficient assembly in our most popular power sockets and specialized outlets, assembly is carried out using precision „click-in“ clips.



To further streamline the process, terminal screws in the power sockets are supplied pre-unscrewed, making them ready for immediate wire connection. These screws are captive, meaning they are secured against falling out and being lost during installation.



Optimized wire management in double sockets, wire tightening is simplified by uni-directional screw positioning.




Furthermore, the perpendicular wire entry into the terminals eliminates the risk of wires slipping out while the product is being secured to the wall box.




Innovative design the construction of our switches, single power sockets, and specialized outlets allows them to be mounted to wall boxes without removing the outer covers. Additionally, the arched mounting holes allow for slight alignment adjustments, even if the installation box is mounted unevenly.

## SOCKETS



Aesthetics and precision the subtle, low-profile design of the outer covers ensures a sleek, aesthetic finish on the wall.



The flexible frame, equipped with multi-clips, allows for a perfect fit against the wall by compensating for surface curvatures and imperfections. Crucially, the frame can be installed without the need to remove covers or switch rockers.



Ergonomic release buttons ensure the quick and easy removal of wires.

## SWITCHES



The most significant advancement in the Szafir series, compared to previous product lines, is the implementation of the innovative plastic mounting bridge, enhancing both durability and precision.



The high-quality plastic bridge features perimeter locking tabs that ensure perfect alignment of products when installed in multi-gang configurations.



During wall renovations or painting, there is no need to dismantle the entire unit—only the frame needs to be removed. Our modern mounting system allows for the replacement of a single product within a multi-gang set without disturbing the remaining units.



A fusion of modern design and perfect proportions. Distinctive inner frames create a **striking visual accent.**

# Aria

Decorative inner frames add a unique sense of originality to the products. They allow for the introduction of subtle color accents, enabling you to personalize the accessories to suit your individual taste.

In the Aria series, switch illumination is as stylish as it is practical. With a choice of seven different backlight colors, you can select the perfect hue to harmonize with your interior décor.



## AVAILABLE COLOURS



White – nr 00



Ecru – nr 27



Silver – nr 18



Grey matt – nr 70




Black matt – nr 33

## AVAILABLE LIGHTING COLOURS



LED gold




LED red



LTS orange



LED green



LED blue




LTS blue



LED white

## EXAMPLES OF COLOUR COMBINATIONS






## Flush mounting switches

Screwless terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-20




ŁP-1U/m/00 2100  
 Single pole switch




ŁP-2U/m/00 2101  
 All-or-part switch, chandelier



ŁP-9U/m/00 2109  
 Two-way + single pole switch



ŁP-11U/m/00 2107  
 Double pole switch



ŁP-13U/m/00 2112  
 Triple switch



ŁP-21U/m/00 2104  
 Short-circuiting switch




ŁP-17U/m/00 2111  
 Double short-circuiting switch



ŁP-10U/m/00 2110  
 Double two-way switch



ŁP-12US/m/00 2108  
 Control switch



ŁP-24U/m/00 2192  
 Short-circuiting triple switch



ŁP-3U/m/00 2102  
 Two-way switch



ŁP-4U/m/00 2103  
 Intermediate switch



ŁP-5U/m/00 2104  
 Short-circuiting switch „light”

### Screw terminals



ŁP-19U/m/00 2193  
 Double intermediate switch  
 /available only on IP 20 version/



ŁP-19US/m/00 2193  
 Double intermediate switch  
 with built-in light  
 /available only in IP 20 version/



ŁP-6U/m/00 2104  
 Short-circuiting switch „bell”



ŁP-7U/m/00 2105  
 Venetian blind switch



ŁP-7UB/m/00 2106  
 Venetian blind switch  
 with mechanical lock

### Hotel switch

Current supply: 230V-50Hz  
 Protection rating: IP-20  
 Rated current: 16A  
 Time of delay: 3s  
 Switch works with a standard card with  
 dimensions 86 x 54 x 0.8 mm




ŁP-15US/m/00 2153  
 Hotel switch

### Accessories for switches IP-44

There is a possibility to mount switches with  
 protection rating IP-20 as switches with IP-44,  
 to do that, must be bought sealing set  
 presented below.



ZU-1R 1118  
 Sealing set for switches IP-44



## Lighting set for switches



ZP-1UP  
Lighting set LTS  
orange 2100



ZP-1UN  
Lighting set LTS  
blue 2100



ZP-2UB  
Lighting set LED  
white 2100



ZP-2UG  
Lighting set LED  
gold 2100



ZP-2UZ  
Lighting set LED  
green 2100



ZP-2UN  
Lighting set LED  
blue 2100



ZP-2UC  
Lighting set LED  
red 2100

NOTE: Except for switches ŁP-9U, ŁP-10U, ŁP-17U, ŁP-19U i ŁP-24U.

## Lighting set for triple switches



ZP-3UP  
Lighting set LTS  
orange 2112



ZP-3UN  
Lighting set LTS  
blue 2112



ZP-4UB  
Lighting set LED  
white 2112



ZP-4UG  
Lighting set LED  
gold 2112



ZP-4UZ  
Lighting set LED  
green 2112



ZP-4UN  
Lighting set LED  
blue 2112



ZP-4UC  
Lighting set LED  
red 2112

To order switches with built-in light look on page 41.

## Dimmers

Screw terminals  
Current supply: 230V-50Hz  
Protection rating: IP-20



ŁP-8U/m/00 2113  
Push-turn dimmer adapted  
to incandescent and halogen loading,  
load 40-400W



ŁP-8UL2/m/00 2114  
Universal dimmer  
load: GLS - 10-250W,  
CFL - 5-75W, LED - 0-100W  
functions: electronic switch,  
"time to bed"

## Temperature regulators

Screw terminals  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W  
- inductive 750W  
Protection rating: IP-20



RTP-1UN/m/00 2155  
Temperature regulator  
with aerial sensor



RTP-1U/m/00\* 2180  
Temperature regulator  
with underfloor sensor

## Electronic movement detector

Screw terminals  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W,  
- fluorescent 750W  
- inductive 750W  
Protection rating: IP-20  
Way of adjustment the time of transmitter's  
switching on: 3s. - 5min.  
Angle of movement detection's field: 136°  
Field of activity: 7m  
Works with LED light



ŁP-16U/m/00 2154  
Electronic movement detector

## Triple socket EURO

Screw terminals  
Rated voltage: 250V  
Rated current: 2,5A  
Protection rating: IP-20



GP-3U/m/00 2127  
Triple socket EURO



GP-3UP/m/00 2127  
Triple socket EURO  
with shutters

## Single socket with ground, with USB charger

Screwless terminals  
Rated voltage:  
- input: 230V-50Hz  
- output: 5VDC  
Rated current: 2,1A  
Protection rating: IP-20  
Doesn't work with surface  
mounting wall frames



GP-1UZPUSB/m/00 2186  
Single socket with ground,  
with shutters, with USB charger

## Single socket with ground, with USB A+C charger

Screwless terminals  
Rated voltage:  
- input: 230V-50Hz (max 0,3A)  
- output A or C: 5VDC/ 3A; 9VDC/ 2,22A;  
12VDC/ 1,67A  
- output A+C: 5VDC/ 3,4A max 20W  
Protection rating: IP-20  
Doesn't work with surface  
mounting wall frames  
Standard fast charger



GP-1UZPUSBAC/m/00 2194  
Single socket with ground, with shutters,  
with USB A+C charger

## Flush mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-1U/m/00  
Single socket 2115



GP-1UP/m/00  
Single socket with shutters 2115



GP-1UZ/m/00  
Single socket with ground 2116



GP-1UZP/m/00  
Single socket with ground, with shutters 2116



GP-1US/m/00  
Single socket with ground schuko 2119



GP-1USP/m/00  
Single socket with ground schuko, with shutters 2119



GP-1UZD/m/00/22  
Single socket with ground DATA 2117



GP-1UZDP/m/00/22  
Single socket with ground DATA, with shutters 2117



GP-1UZK/m/00/22  
Single socket with ground DATA, with access key 2118



GPH-1UZ/m/00/d  
Hermetic socket with ground, IP-44 2120



GPH-1UZP/m/00/d  
Hermetic socket with ground, IP-44, with shutters 2120




GPH-1US/m/00/d  
Hermetic socket with ground schuko, IP-44 2121



GPH-1USP/m/00/d  
Hermetic socket with ground schuko, IP-44, with shutters 2121

Hermetic sockets in white and ecru colours are also offered with lid in product's colour. After right product's code write: .../00/w for products in white colour or .../27/w for products in ecru colour.

## AVAILABLE COLOURS



## Flush mounting socket outlets for Standard surrounds

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-2UR/m/00  
Twin socket 2124



GP-2URZ/m/00  
Twin socket with ground 2125



GP-2URZP/m/00  
Twin socket with ground, with shutters 2125

## Flush mounting socket outlets for Prestige surrounds



GP-2URAZ/m/00  
Twin socket with ground 2125



GP-2URAZP/m/00  
Twin socket with ground, with shutters 2125

## Flush mounting socket outlets (sold entire)

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-2U/00  
Twin socket 2122



GP-2UZ/00  
Twin socket with ground 2123



GP-2UZP/00  
Twin socket with ground, with shutters 2123




GP-2US/00  
Twin socket with ground schuko 2126



GP-2USP/00  
Twin socket with ground schuko, with shutters 2126



GP-2UC/00  
Twin socket with ground, without changing phase 2128



## Equipotential socket



GPE-1U/m/00\*  
Single equipotential socket

2149



GPE-2U/m/00\*  
Twin equipotential socket

2150



WKE\*  
Plug into  
the equipotential socket

1571

## Antenna subscribers

Screw terminals



GPA-1UF/m/00  
Single, terminal antenna RTV subscriber,  
type F

2135



GPA-2UF/m/00  
Twin, terminal antenna RTV subscriber,  
type F

2136



GPA-US/m/00  
Terminal antenna RTV-SAT subscriber,  
attenuation coefficient 1,5-2 dB

2131

GPA-USP/m/00\*  
Through antenna RTV-SAT subscriber,  
attenuation coefficient 1,2 dB

2132



GPA-U2S/m/00  
Terminal antenna RTV-SAT subscriber  
with two outlets SAT

2134



GPA-UD/m/00\*  
Terminal antenna  
RTV-DATA subscriber

2133



GPA-UK/m/00  
Terminal antenna RTV subscriber,  
attenuation coefficient 2,5-3 dB

2130

GPA-10UP/m/00\*  
Through antenna RTV subscriber,  
attenuation coefficient 10 dB

2129

GPA-14UP/m/00\*  
Through antenna RTV subscriber,  
attenuation coefficient 14 dB

2129

GPA-16UP/m/00\*  
Through antenna RTV subscriber,  
attenuation coefficient 16 dB

2129

GPA-10UPZ/m/00\*  
Through antenna RTV subscriber  
attenuation coefficient 10 dB

2129

## Telephone sockets

Screw terminals



GPT-1U/m/00  
Single telephone socket

2137



GPT-2UN/m/00  
Twin telephone socket,  
independent

2138

GPT-2UR/m/00  
Twin telephone socket,  
parallel

2138

## Loudspeaker sockets



GG-1U/m/00  
Single loudspeaker socket  
connection of lines ability 0,75 mm<sup>2</sup>

2146



GG-2U/m/00  
Twin loudspeaker socket  
connection of lines ability 0,75 mm<sup>2</sup>

2147



GGN-1U/m/00  
Single loudspeaker socket  
connection of lines ability 6 mm<sup>2</sup>

2148

## Computer sockets

Connection IDC



GPK-1U/K/m/00  
Single computer socket,  
5e class, MMC

2139



GPK-2U/K/m/00  
Twin computer socket,  
5e class, MMC

2142

## Sockets covers Keystone type



GPK-1U/p/00  
Single computer socket cover,  
flat 2140



GPK-1US/p/00  
Single computer socket cover,  
slant 2141



GPK-1UP/p/00  
Single computer socket cover,  
with shutter, flat 2178



GPK-2U/p/00  
Twin computer socket cover,  
flat 2143



GPK-2US/p/00  
Twin computer socket cover,  
slant 2144



GPK-2UP/p/00  
Twin computer socket cover,  
with shutter, flat 2179

Modules which can be mounted in these socket covers are on page 167.

## Cable terminal

Screw terminals, 5x4mm<sup>2</sup>  
Protection rating: IP-20  
Flush-mounted into ø60 boxes



GPPK-1U/m/00  
Cable terminal 2151

## Blank cover



Z-1U/m/00  
Blank cover 2152


## Adapter

It allows to use of Ospel 45 system products  
in the Aria series.



AP45-1U/m/00  
Adapter 2187

## AVAILABLE COLOURS



## Wall frames




PNP-1U/00  
Single wall frame 2161

PNP-2U/00  
Twin wall frame 2162

PNP-3U/00  
Threefold wall frame 2163

PNP-4U/00  
Fourfold wall frame 2164

PNP-5U/00  
Fivefold wall frame 2165



## Decorative surrounds




RO-1U/00  
Decorative surround for switches 2100



RO-13U/00  
Decorative surround  
for triple switches 2112



RO-5U/00  
Decorative surround for  
double intermediate switch 2193



RO-2U/00  
Decorative surround for  
single sockets outlets and dimmers 2115



RO-3U/00  
Decorative surround  
for twin sockets 2122




RO-4U/00  
Decorative surround for twin sockets  
mounted into multiple surrounds 2124

Decorative frames in a wide range of colours are available for products from the Aria series. To order chosen surround in the place of dots must be written the number of wanted colour according to the presentation. Presented colours can differ from original.

- RO-1U/...
- RO-13U/...
- RO-2U/...
- RO-3U/...
- RO-4U/...
- RO-5U/...





## Surrounds Standard

white		ecru		
R-1U/00 Single surround	2156	R-1U/27 Single surround	2156	
R-2U/00 Twin surround	2157	R-2U/27 Twin surround	2157	
R-3U/00 Threefold surround	2158	R-3U/27 Threefold surround	2158	
R-4U/00 Fourfold surround	2159	R-4U/27 Fourfold surround	2159	
R-5U/00 Fivefold surround	2160	R-5U/27 Fivefold surround	2160	

## Surrounds Standard for sets IP-44

white		ecru		
RH-1U/00 Single surround	2156	RH-1U/27 Single surround	2156	
RH-2U/00 Twin surround	2157	RH-2U/27 Twin surround	2157	
RH-3U/00 Threefold surround	2158	RH-3U/27 Threefold surround	2158	
RH-4U/00 Fourfold surround	2159	RH-4U/27 Fourfold surround	2159	
RH-5U/00 Fivefold surround	2160	RH-5U/27 Fivefold surround	2160	

## Surrounds Metallic

silver		grey matt		black matt		
R-1U/18 Single surround	2156	R-1U/70 Single surround	2156	R-1U/33 Single surround	2156	
R-2U/18 Twin surround	2157	R-2U/70 Twin surround	2157	R-2U/33 Twin surround	2157	
R-3U/18 Threefold surround	2158	R-3U/70 Threefold surround	2158	R-3U/33 Threefold surround	2158	
R-4U/18 Fourfold surround	2159	R-4U/70 Fourfold surround	2159	R-4U/33 Fourfold surround	2159	
R-5U/18 Fivefold surround	2160	R-5U/70 Fivefold surround	2160	R-5U/33 Fivefold surround	2160	

## Surrounds Metallic for sets IP-44


silver		grey matt		black matt		
RH-1U/18 Single surround	2156	RH-1U/70 Single surround	2156	RH-1U/33 Single surround	2156	
RH-2U/18 Twin surround	2157	RH-2U/70 Twin surround	2157	RH-2U/33 Twin surround	2157	
RH-3U/18 Threefold surround	2158	RH-3U/70 Threefold surround	2158	RH-3U/33 Threefold surround	2158	
RH-4U/18 Fourfold surround	2159	RH-4U/70 Fourfold surround	2159	RH-4U/33 Fourfold surround	2159	
RH-5U/18 Fivefold surround	2160	RH-5U/70 Fivefold surround	2160	RH-5U/33 Fivefold surround	2160	

Presented surrounds are universal, the products can be mounted in horizontal and vertical position.

Presented surrounds are universal, the products can be mounted in horizontal and vertical position.


## Surrounds Prestige – sold only in IP-20 version

brushed aluminium



R-1UAC/62/25 2156  
Single surround  
R-2UAC/62/25 2157  
Twin surround  
R-3UAC/62/25 2158  
Threefold surround  
R-4UAC/62/25 2159  
Fourfold surround

brushed anthracite



R-1UAC/64/25 2156  
Single surround  
R-2UAC/64/25 2157  
Twin surround  
R-3UAC/64/25 2158  
Threefold surround  
R-4UAC/64/25 2159  
Fourfold surround




white glass




R-1UGC/31/00 2156  
Single surround  
R-2UGC/31/00 2157  
Twin surround  
R-3UGC/31/00 2158  
Threefold surround  
R-4UGC/31/00 2159  
Fourfold surround

black glass




R-1UGC/32/25 2156  
Single surround  
R-2UGC/32/25 2157  
Twin surround  
R-3UGC/32/25 2158  
Threefold surround  
R-4UGC/32/25 2159  
Fourfold surround


grey glass



R-1UGC/41/25 2156  
Single surround  
R-2UGC/41/25 2157  
Twin surround  
R-3UGC/41/25 2158  
Threefold surround  
R-4UGC/41/25 2159  
Fourfold surround



white frosted glass, oval



RP-1UGC/78/00 2156  
Single surround  
RP-2UGC/78/00 2157  
Twin surround  
RP-3UGC/78/00 2158  
Threefold surround  
RP-4UGC/78/00 2159  
Fourfold surround

black frosted glass, oval




RP-1UGC/79/25 2156  
Single surround  
RP-2UGC/79/25 2157  
Twin surround  
RP-3UGC/79/25 2158  
Threefold surround  
RP-4UGC/79/25 2159  
Fourfold surround



Presented surrounds are universal, the products can be mounted in horizontal and vertical position.

## AVAILABLE COLOURS



## Example order


To order single pole switch in white colour with surround in black matt colour must be ordered:

ŁP-1U/m/00  
R-1U/33




To order USB charger in white colour must be ordered:

GK-2USB/00  
AP45-1U/m/00  
R-1U/00



To order single pole switch in grey matt colour with lighting set LED in green colour must be ordered:

ŁP-1U/m/70  
ZP-2UZ  
R-1U/70



## Designations

Products of Aria series are sold without external surround (\*excluding a few twin sockets). Below are written designations which must be used to place the order. After right product's code use the right number of colour, products in colour:

White – number 00  
 Ecu – number 27  
 Silver – number 18  
 Grey matt – number 70  
 Black matt – number 33

ŁP-.....U/m	Switches - in the place marked by dots, write the right number of switch	GPT-1U/m	Single telephone socket
ŁP-8U/m	Push-turn dimmer, adapted to incandescent loading and halogen loading	GPT-2UN/m	Twin telephone socket, independent
ŁP-8UL2/m	Universal dimmer	GPT-2UR/m	Twin telephone socket, parallel
ŁP-15US/m	Hotel switch	GPA-1UF/m	Single, terminal antenna RTV subscriber, type F
ŁP-16U/m	Electronic movement detector	GPA-2UF/m	Twin, terminal antenna RTV subscriber, type F
GP-1U/m	Single socket	GPA-UK/m	Terminal antenna RTV subscriber (on request)
GP-1UP/m	Single socket with shutters	GPA-10UPZ/m	Through antenna RTV subscriber (on request)
GP-1UZ/m	Single socket with ground	GPA-10UP/m	Through antenna RTV subscriberZAP-10 (on request)
GP-1UZP/m	Single socket with ground, with shutters	GPA-14UP/m	Through antenna RTV subscriberZAP-14 (on request)
GP-1US/m	Single socket with ground schuko	GPA-16UP/m	Through antenna RTV subscriberZAP-16 (on request)
GP-1USP/m	Single socket with ground schuko, with shutters	GPA-US/m	Terminal antenna RTV-SAT subscriber
GP-1UZD/m	Single socket with ground DATA	GPA-USP/m	Through antenna RTV-SAT subscriber (on request)
GP-1UZDP/m	Single socket with ground DATA, with shutters	GPA-U2S/m	Terminal antenna RTV-SAT subscriber, with two outlets SAT
GP-1UZK/m	Single socket with ground DATA, with access key	GPA-UD/m	Terminal antenna RTV-DATA subscriber (on request)
GPH-1UZ/m	Hermetic socket IP-44	GG-1U/m	Single loudspeaker socket
GPH-1UZP/m	Hermetic socket IP-44, with shutters	GG-2U/m	Twin loudspeaker socket
GPH-1US/m	Hermetic socket with ground schuko, IP-44	GGN-1U/m	Single loudspeaker socket
GPH-1USP/m	Hermetic socket with ground schuko, IP-44, with shutters	GPK-1U/K/m	Single computer socket, 5e class, MMC
GP-2UR/m	Twin socket	GPK-2U/K/m	Twin computer socket, 5e class, MMC
GP-2URZ/m	Twin socket with ground	GPK-1U/p	Single socket cover, flat
GP-2URZP/m	Twin socket with ground, with shutters	GPK-2U/p	Twin socket cover, flat
GP-2URAZ/m	Twin socket with ground	GPK-1UP/p	Single computer socket cover with shutter, flat
GP-2URAZP/m	Twin socket with ground with shutters	GPK-2UP/p	Twin computer socket cover with shutter, flat
GP-2U	Twin socket *	GPK-1US/p	Single computer socket cover, slant
GP-2UZ	Twin socket with ground *	GPK-2US/p	Twin computer socket cover, slant
GP-2UC	Twin socket with ground, without changing phase *	GPE-1U/m	Single equipotential socket (on request)
GP-2UZP	Twin socket with ground, with shutters*	GPE-2U/m	Twin equipotential socket (on request)
GP-2US	Twin socket with ground schuko *	RTP-1U/m	Temperature regulator with underfloor sensor (on request)
GP-2USP	Twin socket with ground schuko, with shutters*	RTP-1UN/m	Temperature regulator with aerial sensor
GP-3U/m	Triple socket EURO	Z-1U/m	Blank cover
GP-3UP/m	Triple socket EURO with shutters	GPPK-1U/m	Cable terminal
GP-1UZPUSB/m	Single socket with ground, with USB charger, with shutters	AP45-1U/m	Adapter
GP-1UZPUSBAC/m	Single socket with ground, with USB A+C charger, with shutters		



# Aria

FLUSH-MOUNTED SERIES

## Quick and easy installation of wiring accessories




Safety shutters protect children from electric shock by preventing the insertion of metal objects into the socket apertures.



The enclosed design of the self-returning mounting claws protects the installer's fingers from accidental injury.




Side wire entry allows for a visual quality check of the terminal connections even after the socket module has been fully installed in the wall box.



Alignment spacers located on the bridges ensure perfect spacing and precise positioning of modules in multi-gang boxes.

### SOCKETS



A universal multi-gang frame system that allows for both vertical and horizontal layouts.



Quick assembly and disassembly of the frame on the switch module, thanks to the use of a quick-release mounting cover.


### SWITCHES



Side wire entry allows for a visual quality check of the terminal connections even after the switch module has been fully installed in the wall box. Ergonomic release buttons ensure easy removal of the wires from the terminals. Furthermore, the red button allows for quick and easy identification of the live (line) wire terminal.



The replaceable illumination module allows you to choose the color of the emitted light (Its and led), ensuring a perfect match with your interior design.



Self-returning mounting claws, equipped with stainless steel spring elements, significantly facilitate the installation of the switch module in the wall box.



**Designed to meet the expectations** of trendsetters, it will captivate you with its refined shape and timeless elegance.



# Sonata

With its sophisticated design, the Sonata series blends perfectly with modern interiors. A sleek, flat form, elegance, superior craftsmanship, and functionality are the key features that set this series apart.



## AVAILABLE COLOURS



White – nr 00



White matt – nr 75



Ecru – nr 27




Cashmere – nr 82



Silver – nr 38



Gold – nr 39



Brown metallic – nr 40



Graphite grey – nr 73



Black matt – nr 33

## EXAMPLES OF COLOUR COMBINATIONS



White glass – nr 31



Black glass – nr 32



Aluminium – nr 35



White glass – nr 31/00



Black glass – nr 32/25



Grey glass – nr 41/25



White frosted glass – nr 78/00



Black frosted glass – nr 79/33



Blue frosted glass – nr 80/33



Champagne frosted glass – nr 81/33



Grey frosted glass – nr 85/33



Brushed aluminium – nr 62/25



Brushed satin – nr 63/25



Brushed anthracite – nr 64/25



White frosted glass, bevelled  
– nr 78/00



Black frosted glass, bevelled  
– nr 79/33



## Flush mounting switches

Screwless terminals  
 Rated voltage: 250V  
 Rated current: 16AX  
 Protection rating: IP-20



ŁP-1R/m/00  
Single pole switch 1068



ŁP-3R/m/00  
Two-way switch 1070



ŁP-2R/m/00  
All-or-part switch, chandelier 1069

ŁP-9R/m/00  
Two-way switch  
+ single pole switch 1075

ŁP-10R/m/00  
Double two-way switch 1076



ŁP-4R/m/00  
Intermediate switch 1071



ŁP-11R/m/00  
Double pole switch 1074

## Flush mounting switches with built-in light

Screwless terminals  
 Rated voltage: 250V  
 Rated current: 16AX  
 Protection rating: IP-20



ŁP-1RS/m/00  
Single pole switch 1068



ŁP-2RS/m/00  
All-or-part switch, chandelier 1069



ŁP-3RS/m/00  
Two-way switch 1070



ŁP-4RS/m/00  
Intermediate switch 1071



ŁP-11RS/m/00  
Double pole switch 1074



ŁP-12RS/m/00  
Control switch 1131

Rated current: 10AX



ŁP-5R/m/00  
Short-circuiting switch „light” 1072



ŁP-6R/m/00  
Short-circuiting switch „bell” 1072

Screw terminals



ŁP-19R/m/00  
Double intermediate switch  
/available only on IP 20 version/ 1146

Rated current: 10AX



ŁP-5RS/m/00  
Short-circuiting switch „light” 1072



ŁP-6RS/m/00  
Short-circuiting switch „bell” 1072

Screw terminals



ŁP-19RS/m/00  
Double intermediate switch  
/available only on IP 20 version/ 1146



ŁP-7R/m/00  
Venetian blind switch 1073



ŁP-13R/m/00  
Triple switch 1117

## Accessories for switches IP-44

There is a possibility to mount switches with protection rating IP-20 as switches with IP-44, to do that, must be bought sealing set presented below.



ZU-1R  
Sealing set for switches IP-44 1118

Rated current: 10AX



ŁP-7RS/m/00  
Venetian blind switch 1073



ŁP-7RBS/m/00  
Venetian blind switch with mechanical lock 2009

## Hotel switch

Screw terminals  
 Current supply: 230~ 50Hz  
 Protection rating: IP-20  
 Rated current: 16A  
 Time of delay: 3s

Switch works with a standard card with dimensions 86 x 54 x 0.8 mm



ŁP-13RS/m/00  
Triple switch 1117



ŁP-21RS/m/00  
Short-circuiting switch 1072




ŁP-15RS/m/00  
Hotel switch 1107



ŁP-17R/m/00  
Double short-circuiting switch 1132



ŁP-21R/m/00  
Short-circuiting switch 1072



## Dimmers

Screw terminals  
Current supply: 230V ~50Hz  
Protection rating: IP-20



ŁP-8R/m/00 1077  
Push-turn dimmer adapted to incandescent and halogen loading, load 40-400W



ŁP-8RL2/m/00 2006  
Universal dimmer  
load: GLS - 10-250W, CFL - 5-75W  
LED - 0-100W  
functions: electronic switch, "time to bed"

## Temperature regulators

Screw terminals,  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W  
- inductive 750W  
Protection rating: IP-20



RTP-1RN/m/00 1110  
Temperature regulator with aerial sensor



RTP-1R/m/00\* 1109  
Temperature regulator with underfloor sensor

## Wi-Fi electronic temperature regulator

Screw terminals,  
Rated voltage: 230V~ 50/60Hz  
Rated current: 16A  
Functions: Heating / Cooling  
Temperature probe: Included  
Protection rating: IP-20



RTE-1R/m/00 1111  
Wi-Fi electronic temperature regulator

## Equipotential socket



GPE-1R/m/00\* 1398  
Single equipotential socket



GPE-2R/m/00\* 1399  
Twin equipotential socket



WKE\* 1571  
Plug into the equipotential socket

## Electronic movement detector

Screw terminals  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W  
- fluorescent 750W  
- inductive 750W  
Protection rating: IP-20  
Way of adjustment the time of transmitter's switching on: 3s. - 5min.  
Angle of movement detection's field: 136°  
Field of activity: 7m  
Works with LED light



ŁP-16R/m/00 1108  
Electronic movement detector

## British sockets

Screw terminals  
Rated voltage: 250V  
Rated current: 13A  
Protection rating: IP-20



GP/442097TSS1/1P/33 2020  
Single socket with ground and shutters, with switch, British standard



GP/442097TSS2/1P/33 2021  
Twin socket with ground and shutters, with switch, British standard

Sockets work only with British standard installation boxes.

## Surrounds

Only for UK sockets

White



R-1RBS/00 2020  
Single surround - British standard

White



R-2RBS/00 2021  
Double surround - British standard

Black matt



R-1RBS/33 2020  
Single surround - British standard

Black matt



R-2RBS/33 2021  
Double surround - British standard

# Sonata

FLUSH-MOUNTED SERIES

## Triple socket EURO

Screw terminals  
 Rated voltage: 250V  
 Rated current: 2,5A  
 Protection rating: IP-20



GP-3R/m/00  
 Triple socket EURO

1090



GP-3RP/m/00  
 Triple socket EURO  
 with shutters

1090

## Single sockets with ground with USB charger

Screwless terminals  
 Rated voltage: input: 230V~50Hz, output: 5VDC  
 Rated current: 2,1A  
 Protection rating: IP-20  
 Doesn't work with surface mounting wall frames



GP-1RZPUSB/m/00  
 Single socket with ground, with shutters,  
 with USB charger

2059



GP-1RSPUSB/m/00  
 Single socket with ground schuko,  
 with shutters, with USB charger

2060

## Single sockets with ground with USB A+C charger

Screwless terminals  
 Rated voltage:  
 – input: 230V~50Hz (max 0,3A)  
 – output A or C: 5VDC/ 3A; 9VDC/ 2,22A; 12VDC/ 1,67A  
 – output A+C: 5VDC/ 3,4A max 20W  
 Protection rating: IP-20  
 Doesn't work with surface mounting wall frames  
 Standard fast charger



GP-1RZPUSBAC/m/00  
 Single socket with ground, with shutters,  
 with USB A+C charger


2096



GP-1RSPUSBAC/m/00  
 Single socket with ground schuko,  
 with shutters, with USB A+C charger

2097

AVAILABLE COLOURS



## Flush mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A,  
 Protection rating: IP-20



GP-1R/m/00  
 Single socket

1079



GP-1RP/m/00  
 Single socket with shutters

1079



GP-1RZ/m/00  
 Single socket with ground

1080



GP-1RZP/m/00  
 Single socket with ground,  
 with shutters

1080



GP-1RS/m/00  
 Single socket with ground  
 schuko

1082



GP-1RSP/m/00  
 Single socket with ground  
 schuko, with shutters

1082



GP-1RZD/m/00  
 Single socket with ground DATA

1081



GP-1RZDP/m/00  
 Single socket with ground DATA,  
 with shutters

1081



GP-1RZK/m/00  
 Single socket with ground DATA,  
 with access key

1128



GPH-1RZ/m/00/d  
 Hermetic socket  
 with ground, IP-44

1083



GPH-1RZP/m/00/d  
 Hermetic socket  
 with ground, IP-44,  
 with shutters

1083



GPH-1RS/m/00/d  
 Hermetic socket  
 with ground schuko, IP-44


1084



GPH-1RSP/m/00/d  
 Hermetic socket  
 with ground schuko, IP-44,  
 with shutters

1084

Hermetic sockets in white and ecru colours are also offered with lid in product's colour. After right product's code write: .../00/w for products in white colour or .../27/w for products in ecru colour.



## Flush mounting socket outlets for Standard surrounds

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-2RR/m/00  
Twin socket 1087



GP-2RRP/m/00  
Twin socket with shutters 1087



GP-2RRZ/m/00  
Twin socket with ground 1088



GP-2RRZP/m/00  
Twin socket with ground,  
with shutters 1088

## Flush mounting socket outlets for Prestige surrounds

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-2RRAZ/m/00  
Twin socket with ground 2095



GP-2RRAZP/m/00  
Twin socket with ground,  
with shutters 2095

## Flush mounting socket outlets (sold entire)

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-2R/00  
Twin socket 1085



GP-2RP/00  
Twin socket with shutters 1085



GP-2RC/00  
Twin socket with ground,  
without changing phase 1091



GP-2RZ/00  
Twin socket  
with ground 1086



GP-2RZP/00  
Twin socket with ground,  
with shutters 1086



GP-2RS/00  
Twin socket  
with ground schuko 1089



GP-2RSP/00  
Twin socket with ground  
schuko, with shutters 1089



## Antenna subscribers

Screw terminals



GPA-1RF/m/00 1097  
Terminal antenna RTV subscriber,  
type F, single



GPA-2RF/m/00 1377  
Terminal antenna RTV subscriber,  
type F, twin



GPA-10RP/m/00\* 1092  
Through antenna RTV subscriber 10 dB

GPA-14RP/m/00\* 1092  
Through antenna RTV subscriber 14 dB

GPA-16RP/m/00\* 1092  
Through antenna RTV subscriber 16 dB



GPA-10RPZ/m/00\* 1092  
Through antenna RTV subscriber



GPA-RK/m/00 1093  
Terminal antenna RTV subscriber



GPA-RS/m/00 1094  
Terminal antenna RTV-SAT subscriber,



GPA-RSP/m/00\* 1095  
Through antenna RTV-SAT subscriber



GPA-R2S/m/00 1096  
Terminal antenna RTV-SAT subscriber  
with two outlets SAT



GPA-RD/m/00\* 1386  
Terminal antenna  
RTV-DATA subscriber

## Telephone sockets

Screw terminals



GPT-1R/m/00 1098  
Single telephone socket



GPT-2RN/m/00 1099  
Twin telephone socket,  
independent

GPT-2RR/m/00 1099  
Twin telephone socket,  
parallel

## Blank cover



Z-1R/m/00 1127  
Blank cover

## Loudspeaker sockets



GG-1R/m/00 1105  
Single loudspeaker socket  
Connection of lines ability 0,75 mm<sup>2</sup>



GG-2R/m/00 1106  
Twin loudspeaker socket  
Connection of lines ability 0,75 mm<sup>2</sup>



GGN-1R/m/00 1144  
Single loudspeaker socket  
Connection of lines ability 6 mm<sup>2</sup>

## Computer sockets

Connection IDC



GPK-1R/K/m/00 1100  
Single computer socket,  
5e class, MMC

GPK-1R/K6/m/00 1102  
Single computer socket,  
6 class, MMC




GPK-2R/K/m/00 1101  
Twin computer socket,  
5e class, MMC

GPK-2R/K6/m/00 1103  
Twin computer socket,  
6 class, MMC

## Adapter

It allows to use of Ospel 45 system products  
in the Sonata series.



AP45-1R/m/00 1147  
Adapter

## Sockets covers Keystone type



GPK-1RS/p/00 1366  
Single computer socket cover,  
slant



GPK-2RS/p/00 1367  
Twin computer socket cover,  
slant



GPK-1R/p/00 1392  
Single computer socket cover,  
flat



GPK-2R/p/00 1393  
Twin computer socket cover,  
flat

## Cable terminal

Screw terminals, 5x4mm<sup>2</sup>  
Protection rating: IP-20  
Flush-mounted into ø60 boxes




GPPK-1R/m/00 1140  
Cable terminal

# Sonata

FLUSH-MOUNTED SERIES

AVAILABLE COLOURS



## Surrounds Standard

## Surrounds Metallic

white



R-1R/00 Single surround	1112
R-2R/00 Twin surround	1113
R-3R/00 Threefold surround	1114
R-4R/00 Fourfold surround	1115
R-5R/00 Fivefold surround	1116

cashmere



R-1R/82 Single surround	1112
R-2R/82 Twin surround	1113
R-3R/82 Threefold surround	1114
R-4R/82 Fourfold surround	1115
R-5R/82 Fivefold surround	1116

brown metallic



R-1R/40 Single surround	1112	
R-2R/40 Twin surround	1113	
R-3R/40 Threefold surround	1114	
R-4R/40 Fourfold surround	1115	
R-5R/40 Fivefold surround	1116	

white matt



R-1R/75 Single surround	1112
R-2R/75 Twin surround	1113
R-3R/75 Threefold surround	1114
R-4R/75 Fourfold surround	1115
R-5R/75 Fivefold surround	1116

silver



R-1R/38 Single surround	1112
R-2R/38 Twin surround	1113
R-3R/38 Threefold surround	1114
R-4R/38 Fourfold surround	1115
R-5R/38 Fivefold surround	1116

graphite grey



R-1R/73 Single surround	1112	
R-2R/73 Twin surround	1113	
R-3R/73 Threefold surround	1114	
R-4R/73 Fourfold surround	1115	
R-5R/73 Fivefold surround	1116	

ecru



R-1R/27 Single surround	1112
R-2R/27 Twin surround	1113
R-3R/27 Threefold surround	1114
R-4R/27 Fourfold surround	1115
R-5R/27 Fivefold surround	1116

gold



R-1R/39 Single surround	1112
R-2R/39 Twin surround	1113
R-3R/39 Threefold surround	1114
R-4R/39 Fourfold surround	1115
R-5R/39 Fivefold surround	1116

black matt



R-1R/33 Single surround	1112	
R-2R/33 Twin surround	1113	
R-3R/33 Threefold surround	1114	
R-4R/33 Fourfold surround	1115	
R-5R/33 Fivefold surround	1116	

Presented surrounds are universal, the products can be mounted in horizontal and vertical position.

## Surrounds Standard for sets IP-44

## Surrounds Metallic for sets IP-44

white



RH-1R/00 Single surround	1112
RH-2R/00 Twin surround	1113
RH-3R/00 Threefold surround	1114
RH-4R/00 Fourfold surround	1115
RH-5R/00 Fivefold surround	1116

cashmere



RH-1R/82 Single surround	1112
RH-2R/82 Twin surround	1113
RH-3R/82 Threefold surround	1114
RH-4R/82 Fourfold surround	1115
RH-5R/82 Fivefold surround	1116

brown metallic



RH-1R/40 Single surround	1112	
RH-2R/40 Twin surround	1113	
RH-3R/40 Threefold surround	1114	
RH-4R/40 Fourfold surround	1115	
RH-5R/40 Fivefold surround	1116	

white matt



RH-1R/75 Single surround	1112
RH-2R/75 Twin surround	1113
RH-3R/75 Threefold surround	1114
RH-4R/75 Fourfold surround	1115
RH-5R/75 Fivefold surround	1116

silver



RH-1R/38 Single surround	1112
RH-2R/38 Twin surround	1113
RH-3R/38 Threefold surround	1114
RH-4R/38 Fourfold surround	1115
RH-5R/38 Fivefold surround	1116

graphite grey



RH-1R/73 Single surround	1112	
RH-2R/73 Twin surround	1113	
RH-3R/73 Threefold surround	1114	
RH-4R/73 Fourfold surround	1115	
RH-5R/73 Fivefold surround	1116	

ecru



RH-1R/27 Single surround	1112
RH-2R/27 Twin surround	1113
RH-3R/27 Threefold surround	1114
RH-4R/27 Fourfold surround	1115
RH-5R/27 Fivefold surround	1116

gold



RH-1R/39 Single surround	1112
RH-2R/39 Twin surround	1113
RH-3R/39 Threefold surround	1114
RH-4R/39 Fourfold surround	1115
RH-5R/39 Fivefold surround	1116

black matt



RH-1R/33 Single surround	1112	
RH-2R/33 Twin surround	1113	
RH-3R/33 Threefold surround	1114	
RH-4R/33 Fourfold surround	1115	
RH-5R/33 Fivefold surround	1116	

Presented surrounds are universal, the products can be mounted in horizontal and vertical position.

# Sonata

FLUSH-MOUNTED SERIES

## Ramki Prestige – sold only in IP-20 version


size – 6 mm

white glass



R-1RG/31 Single surround	1112
R-2RG/31 Twin surround	1113
R-3RG/31 Threefold surround	1114
R-4RG/31 Fourfold surround	1115


black glass



R-1RG/32 Single surround	1112
R-2RG/32 Twin surround	1113
R-3RG/32 Threefold surround	1114
R-4RG/32 Fourfold surround	1115




aluminium



R-1RA/35 Single surround	1112
R-2RA/35 Twin surround	1113
R-3RA/35 Threefold surround	1114
R-4RA/35 Fourfold surround	1115




AVAILABLE COLOURS



## Ramki Prestige – sold only in IP-20 version


size – 4 mm

brushed aluminium + black surround




R-1RAC/62/25 Single surround	1112
R-2RAC/62/25 Twin surround	1113
R-3RAC/62/25 Threefold surround	1114
R-4RAC/62/25 Fourfold surround	1115
R-5RAC/62/25 Fivefold surround	1116

brushed satin + black surround



R-1RAC/63/25 Single surround	1112
R-2RAC/63/25 Twin surround	1113
R-3RAC/63/25 Threefold surround	1114
R-4RAC/63/25 Fourfold surround	1115
R-5RAC/63/25 Fivefold surround	1116

brushed anthracite + black surround



R-1RAC/64/25 Single surround	1112
R-2RAC/64/25 Twin surround	1113
R-3RAC/64/25 Threefold surround	1114
R-4RAC/64/25 Fourfold surround	1115
R-5RAC/64/25 Fivefold surround	1116



white glass + white surround




R-1RGC/31/00 Single surround	1112
R-2RGC/31/00 Twin surround	1113
R-3RGC/31/00 Threefold surround	1114
R-4RGC/31/00 Fourfold surround	1115
R-5RGC/31/00 Fivefold surround	1116

grey glass + black surround



R-1RGC/41/25 Single surround	1112
R-2RGC/41/25 Twin surround	1113
R-3RGC/41/25 Threefold surround	1114
R-4RGC/41/25 Fourfold surround	1115
R-5RGC/41/25 Fivefold surround	1116

black glass + black surround



R-1RGC/32/25 Single surround	1112
R-2RGC/32/25 Twin surround	1113
R-3RGC/32/25 Threefold surround	1114
R-4RGC/32/25 Fourfold surround	1115
R-5RGC/32/25 Fivefold surround	1116



# Sonata

FLUSH-MOUNTED SERIES

## Ramki Prestige – sold only in IP-20 version

size – 4 mm

white frosted glass + white surround



R-1RGC/78/00 Single surround	1112
R-2RGC/78/00 Twin surround	1113
R-3RGC/78/00 Threefold surround	1114
R-4RGC/78/00 Fourfold surround	1115
R-5RGC/78/00 Fivefold surround	1116

black frosted glass + black surround



R-1RGC/79/33 Single surround	1112
R-2RGC/79/33 Twin surround	1113
R-3RGC/79/33 Threefold surround	1114
R-4RGC/79/33 Fourfold surround	1115
R-5RGC/79/33 Fivefold surround	1116




blue frosted glass + black surround



R-1RGC/80/33 Single surround	1112
R-2RGC/80/33 Twin surround	1113
R-3RGC/80/33 Threefold surround	1114
R-4RGC/80/33 Fourfold surround	1115
R-5RGC/80/33 Fivefold surround	1116

champagne frosted glass + black surround



R-1RGC/81/33 Single surround	1112
R-2RGC/81/33 Twin surround	1113
R-3RGC/81/33 Threefold surround	1114
R-4RGC/81/33 Fourfold surround	1115
R-5RGC/81/33 Fivefold surround	1116


grey frosted glass + black surround



R-1RGC/85/33 Single surround	1112
R-2RGC/85/33 Twin surround	1113
R-3RGC/85/33 Threefold surround	1114
R-4RGC/85/33 Fourfold surround	1115
R-5RGC/85/33 Fivefold surround	1116

**SONATA series frames are compatible with selected intercom and video intercom systems by Wekta, as well as the Appartme home automation system, ensuring a consistent and harmonious finish for the entire installation.**

AVAILABLE COLOURS



## Ramki Prestige – sold only in IP-20 version

size – 4 mm

white frosted glass, bevelled + white surround




RS-1RGC/78/00 Single surround	1112
RS-2RGC/78/00 Twin surround	1113
RS-3RGC/78/00 Threefold surround	1114
RS-4RGC/78/00 Fourfold surround	1115
RS-5RGC/78/00 Fivefold surround	1116

black frosted glass, bevelled + black surround




RS-1RGC/79/33 Single surround	1112
RS-2RGC/79/33 Twin surround	1113
RS-3RGC/79/33 Threefold surround	1114
RS-4RGC/79/33 Fourfold surround	1115
RS-5RGC/79/33 Fivefold surround	1116



## Wall frames



PNP-1R/00 Single wall frame	1133
PNP-2R/00 Twin wall frame	1134
PNP-3R/00 Threefold wall frame	1135




PNP-2RN/00 Twin corner wall frame	1148
--------------------------------------	------



# Sonata

FLUSH-MOUNTED SERIES

AVAILABLE COLOURS



## Example order

To order single pole switch in white colour must be ordered:

ŁP-1R/m/00  
R-1R/00




To order black single pole switch with built-in light with aluminium surround must be ordered:

ŁP-1RS/m/33  
R-1RA/35



To order USB charger in white colour must be ordered:

GK-2USB/00  
AP45-1R/m/00  
R-1R/00



## Designations

Products of SONATA series (\*excluding a few twin sockets) in all colours are sold without external surround. Below are written designations which must be used to place the order.

After right product's code write the right number of colour:

white – number 00,  
white mat – number 75,  
ecru – number 27,  
cashmere – number 82,  
silver – number 38,

gold – number 39,  
brown metallic – number 40,  
graphite grey – number 73,  
black matt – number 33.

ŁP-.....R/m	Switches – in the place marked by dots, write the right number of switch	GP-2RS	Twin socket with ground schuko*
ŁP-.....RS/m	Switches with built-in light – in the place marked by dots, write the right number of switch	GP-2RSP	Twin socket with ground schuko, with shutters*
ŁP-8R/m	Push-turn dimmer adapted to incandescent and halogen loading	GP-2RC	Twin socket without changing phase*
ŁP-8RL2/m	Universal dimmer	GP-3R/m	Triple socket EURO
ŁP-15RS/m	Hotel switch	GP-3RP/m	Triple socket EURO with shutters
ŁP-16R/m	Electronic movement detector	GPT-1R/m	Single telephone socket
GP-1R/m	Single socket	GPT-2RN/m	Twin telephone socket, independent
GP-1RP/m	Single socket with shutters	GPT-2RR/m	Twin telephone socket, parallel
GP-1RZ/m	Single socket with ground	GPA-1RF/m	Single antenna RTV subscriber type F
GP-1RZP/m	Single socket with ground, with shutters	GPA-2RF/m	Twin antenna RTV subscriber type F
GP-1RS/m	Single socket with ground schuko	GPA-RK/m	Terminal antenna RTV subscriber
GP-1RSP/m	Single socket with ground schuko, with shutters	GPA-10RPZ/m	Through antenna RTV subscriber (on request)
GP-1RZD/m	Single socket with ground DATA	GPA-10RP/m	Through antenna RTV subscriber, 10 dB (on request)
GP-1RZDP/m	Single socket with ground DATA, with shutters	GPA-14RP/m	Through antenna RTV subscriber, 14 dB (on request)
GP-1RZK/m	Single socket with ground DATA, with access key	GPA-16RP/m	Through antenna RTV subscriber, 16 dB (on request)
GPH-1RZ/m	Hermetic socket IP-44	GPA-RS/m	Terminal antenna RTV-SAT subscriber
GPH-1RZP/m	Hermetic socket IP-44, with shutters	GPA-RSP/m	Through antenna RTV-SAT subscriber (on request)
GPH-1RS/m	Hermetic socket with ground schuko, IP-44	GPA-R2S/m	Terminal antenna RTV-SAT subscriber, with two outlets SAT
GPH-1RSP/m	Hermetic socket with ground schuko, IP-44, with shutters	GPA-RD/m	Terminal antenna RTV-DATA subscriber (on request)
GP-1RZPUSB/m	Single socket with ground, with USB charger, with shutters	GG-1R/m	Single loudspeaker socket
GP-1RSPUSB/m	Single socket with ground schuko with USB charger, with shutters	GG-2R/m	Twin loudspeaker socket
GP-1RZPUSBAC/m	Single socket with ground, with USB A+C charger, with shutters	GGN-1R/m	Single loudspeaker socket
GP-1RSPUSBAC/m	Single socket with ground schuko, with USB A+C charger, with shutters	GPK-1R/K/m	Single computer socket, 5e class, MMC
GP/442097TSS1/1P/25	Single socket with ground and shutters, with switch, British standard	GPK-2R/K/m	Twin computer socket, 5e class, MMC
GP/442097TSS2/1P/25	Twin socket with ground and shutters, with switch, British standard	GPK-1R/K6/m	Single computer socket, 6 class, MMC
GP-2RR/m	Twin socket	GPK-2R/K6/m	Twin computer socket, 6 class, MMC
GP-2RRP/m	Twin socket with shutters	GPE-1R/m	Single equipotential socket (on request)
GP-2RRZ/m	Twin socket with ground	GPE-2R/m	Twin equipotential socket (on request)
GP-2RRZP/m	Twin socket with ground, with shutters	GPK-1RS/p	Single computer socket cover, slant
GP-2RRAZ/m	Twin socket with ground	GPK-2RS/p	Twin computer socket cover, slant
GP-2RRAZP/m	Twin socket with ground with shutters	GPK-1R/p	Single computer socket cover, flat
GP-2R	Twin socket*	GPK-2R/p	Twin computer socket cover, flat
GP-2RP	Twin socket with shutters*	RTP-1R/m	Temperature regulator with underfloor sensor (on request)
GP-2RZ	Twin socket with ground*	RTP-1RN/m	Temperature regulator with aerial sensor
GP-2RZP	Twin socket with ground, with shutters*	RTE-1R/m	Wi-Fi electronic temperature regulator
		Z-1R/m	Blank cover
		GPPK-1R/m	Cable terminal
		AP45-1R/m	Adapter


# Sonata

FLUSH-MOUNTED SERIES

## Quick and easy installation of wiring accessories




Safety shutters protect children from electric shock by preventing the insertion of metal objects into the socket apertures.



The enclosed design of the self-returning mounting claws protects the installer's fingers from accidental injury.



Side wire entry allows for a visual quality check of the terminal connections even after the socket module has been fully installed in the wall box.



Alignment spacers located on the bridges ensure perfect spacing and precise positioning of modules in multi-gang boxes.

### SOCKETS



### SWITCHES



Side wire entry allows for a visual quality check of the terminal connections even after the switch module has been fully installed in the wall box. Ergonomic release buttons ensure easy removal of the wires from the terminals. Furthermore, the red button allows for quick and easy identification of the live (line) wire terminal.



The replaceable illumination module allows you to choose the color of the emitted light, ensuring a perfect match with your interior design.



Quick assembly and disassembly of the frame on the switch module, thanks to the use of a quick-release mounting cover.



Self-returning mounting claws, equipped with stainless steel spring elements, significantly facilitate the installation of the switch module in the wall box.



**Smart touch panels**  
with Wi-Fi control.



# Sonata TOUCH

Modern electronic switches for lighting control.

Sonata TOUCH switches are fully compatible with other Sonata products, allowing you to equip any room with functional solutions while giving it a modern character.


# Sonata TOUCH

FLUSH-MOUNTED SERIES

## AVAILABLE COLOURS



White – nr 31



Black – nr 32




White frosted glass – nr 78



Black frosted glass – nr 79

## LOOK OF SWITCHED ON PANELS





Switch connected to the power supply



Connected state with the light source switched on

## EXAMPLES OF COLOUR COMBINATIONS



# Sonata TOUCH

FLUSH-MOUNTED SERIES

AVAILABLE COLOURS

31 white

32 black

78 white frosted glass

79 black frosted glass

## Flush mounting switches

Screw terminals  
 Rated voltage: 230V  
 Load: LED 100W, GLS 750W  
 Rated current: 10AX  
 Protection rating: IP-20



ŁPD-1RS/m/31 4001  
 Single pole touch switch



ŁPD-2RS/m/31 4002  
 All-or-part touch switch



ŁPD-25RS/m/31 4003  
 Two-way touch switch with intermediate switch function



ŁPD-21RS/m/31 4005  
 Short-circuiting single pole touch switch



ŁPD-26RS/m/31 4004  
 Double two-way touch switch with intermediate switch function



ŁPD-18RS/m/31 4005  
 Short-circuiting all-or-part touch switch




ŁPD-13RS/m/31 4007  
 Triple touch switch




ŁPD-7RS/m/31 4006  
 Venetian blind touch switch, Load: 1000W

## Flush mounting switches

Screw terminals  
 Rated voltage: 230V  
 Load: LED 100W, GLS 750W  
 Rated current: 10AX  
 Protection rating: IP-20



ŁPD-1RS/m/32 4001  
 Single pole touch switch




ŁPD-2RS/m/32 4002  
 All-or-part touch switch



ŁPD-25RS/m/32 4003  
 Two-way touch switch with intermediate switch function




ŁPD-21RS/m/32 4005  
 Short-circuiting single pole touch switch



ŁPD-26RS/m/32 4004  
 Double two-way touch switch with intermediate switch function



ŁPD-18RS/m/32 4005  
 Short-circuiting all-or-part touch switch



ŁPD-13RS/m/32 4007  
 Triple touch switch



ŁPD-7RS/m/32 4006  
 Venetian blind touch switch, Load: 1000W

Short-circuiting single pole and all-or-part touch switches are compatible with the ŁP-8RL2/m universal dimmer, enabling touch-controlled light intensity adjustment.

# Sonata TOUCH Wi-Fi

SERIA MODUŁOWA | PODTYNKOWA

## Flush mounting switches Wi-Fi

Screw terminals  
Rated voltage: 230V  
Load: LED 100W, GLS 750W  
Rated current: 10AX  
Protection rating: IP-20



ŁPDT-1RS/m/31  
Single pole touch switch

4011



ŁPDT-2RS/m/31  
All-or-part touch switch

4012



ŁPDT-7RS/m/31  
Venetian blind touch switch,  
Load: 1000W

4013

## Flush mounting switches Wi-Fi

Screw terminals  
Rated voltage: 230V  
Load: LED 100W, GLS 750W  
Rated current: 10AX  
Protection rating: IP-20



ŁPDT-1RS/m/32  
Single pole touch switch

4011



ŁPDT-2RS/m/32  
All-or-part touch switch

4012



ŁPDT-7RS/m/32  
Venetian blind touch switch,  
Load: 1000W

4013

The ŁPDT-1RS and ŁPDT-2RS replace standard two-way and intermediate switches. A Wi-Fi network and app configuration are required for proper operation. These switches communicate with each other exclusively via the wireless Wi-Fi network.

AVAILABLE COLOURS



A modern alternative to traditional solutions.

MANAGE LIGHTING AND SHUTTERS ACCORDING TO YOUR NEEDS.



**TOUCH CONTROL**  
a classic feel with a modern accent



**REMOTE CONTROL**  
via the free Tuya Smart Life app (Android / iOS)



**VOICE CONTROL**  
compatibility with Google Home and Amazon Alexa

## FUNCTIONALITY



**CONNECTIVITY WHEREVER YOU ARE**



**SCHEDULING**



**TIMERS**



**DEVICE SHARING**



**EASY SETUP**



**UPDATES**

### Compatibility and Installation

The Sonata Touch Wi-Fi is an integral part of the Sonata series and works seamlessly with all products in the range, including frames, sockets, USB charger outlets, and more.

Full Modularity – flexible configurations in multi-gang frames, from single to fivefold.

Easy Installation in any mounting box using either screws or claws.

### Technical Requirements:

- Power Supply: Phase (L) and Neutral (N) wires required
- Connectivity: Wi-Fi network (2.4 GHz)
- Software: Tuya Smart Life app



**IMPORTANT: CONFIGURATION AND DEVICE PAIRING VIA THE TUYA APP ARE REQUIRED.**

# Sonata TOUCH

FLUSH-MOUNTED SERIES



## Example order

To order a triple touch switch in white colour with a white glass surround must be ordered:

ŁPD-13RS/m/31

R-1RG/31



To order a single pole touch switch in black colour with a black glass surround must be ordered:

ŁPD-1RS/m/79

R-1RGC/79/33



## Designations

Products of Sonata Touch series are sold without external surround. Below are written designations which must be used to place the order. After right product's code use the right number of colour, products in colour:

white – number 31,  
black – number 32,  
white frosted glass – number 78,  
black frosted glass – number 79.

ŁPD-1RS/m/	Single pole touch switch	ŁPDT-1RS/m/	Single pole switch Wi-Fi
ŁPD-2RS/m/	All-or-part touch switch	ŁPDT-2RS/m/	All-or-part touch switch Wi-Fi
ŁPD-25RS/m/	Two-way touch switch with intermediate switch function	ŁPDT-7RS/m/	Venetian blind switch Wi-Fi
ŁPD-21RS/m/	Short-circuiting single pole touch switch		
ŁPD-26RS/m/	Double two-way touch switch with intermediate switch function		
ŁPD-18RS/m/	Short-circuiting all-or-part touch switch		
ŁPD-13RS/m/	Triple touch switch		
ŁPD-7RS/m/	Venetian blind touch switch, Load: 1000W		



Steel  
**INOX**

## Flush mounting switches with built-in light

Screwless terminals  
 Rated voltage: 250V  
 Rated current: 16AX  
 Protection rating: IP-20



ŁP-1RMS/m/37  
 Single pole switch 1150



ŁP-2RMS/m/37  
 All-or-part switch, chandelier 1151



ŁP-3RMS/m/37  
 Two-way switch 1152



ŁP-4RMS/m/37  
 Intermediate switch 1153



ŁP-11RMS/m/37  
 Double pole switch 1156



ŁP-12RMS/m/37  
 Control switch 1157

Rated current: 10AX



ŁP-5RMS/m/37  
 Short-circuiting switch „light” 1154



ŁP-6RMS/m/37  
 Short-circuiting switch „bell” 1154



ŁP-7RMS/m/37  
 Venetian blind switch 1155



ŁP-7RMS/m/37  
 Venetian blind switch with mechanical lock 1180

Accessories for switches with built-in light are on page 220.

## Dimmers

Screw terminals  
 Current supply: 230V-50 Hz  
 Protection rating: IP-20



ŁP-8RM/m/37  
 Push-turn dimmer 1159  
 load: 40-400W



ŁP-8RML2/m/37  
 Universal dimmer 1179  
 load: GLS - 10-250W,  
 CFL - 5-75W, LED - 0-100W  
 functions: electronic switch,  
 “time to bed”

## Flush mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-1RM/m/37  
 Single socket 1160



GP-1RMP/m/37  
 Single socket with shutters 1160



GP-1RMZ/m/37  
 Single socket with ground 1161



GP-1RMZP/m/37  
 Single socket with ground, with shutters 1161



GP-1RMZD/m/37  
 Single socket with ground DATA 1162



GP-1RMZDP/m/37  
 Single socket with ground DATA, with shutters 1162



GP-1RMZK/m/37  
 Single socket with ground DATA, with access key 1163

## Antenna subscribers

Screw terminals



GPA-2RMF/m/37  
 Twin, terminal antenna RTV subscriber, type F 1175



GPA-10RMPZ/m/37\*  
 Through antenna RTV subscriber 1165



GPA-10RMP/m/37\*  
 Through antenna RTV subscriber 10 dB 1165



GPA-RMK/m/37  
 Terminal antenna RTV subscriber 1166

GPA-14RMP/m/37\*  
 Through antenna RTV subscriber 14 dB 1165

GPA-16RMP/m/37\*  
 Through antenna RTV subscriber 16 dB 1165



GPA-RMS/m/37  
 Terminal antenna RTV-SAT subscriber 1171

\* on request

## Computer socket

Connection IDC



GPK-2RM/K/m/37  
Twin computer socket,  
5e class, MMC

1169

## Telephone socket

Connection IDC



GPT-2RMN/m/37  
Twin telephone socket,  
independent

1167

## Socket covers Keystone type



GPK-2RM/p/37  
Twin computer socket cover,  
flat

1176

## Surrounds – sold only in IP-20 version



R-1RM/37  
Single surround

1112



R-2RM/37  
Twin surround

1113



R-3RM/37  
Threefold surround

1114



R-4RM/37  
Fourfold surround

1115



Modules which can be mounted in these  
socket covers are on page 167.

## Example order

To order all-or-part switch with built-in light must be ordered:

**ŁP-2RMS/m/37**  
**R-1RM/37**



ŁP-2RMS/m/37

+



R-1RM/37

=



## Designations

Products of SONATA STEEL INOX series are sold without external surround.  
Below are written designations which must be used to place the order.  
After right product's code write number 37.

ŁP-...RMS/m/37	Switches with built-in light - in the place marked by dots, write the right number of switch	GPA-10RMP/m/37	Through antenna RTV subscriber, 10 dB (on request)
ŁP-8RM/m/37	Push-turn dimmer adapted to incandescent and halogen loading	GPA-14RMP/m/37	Through antenna RTV subscriber, 14 dB (on request)
ŁP-8RML2/m/37	Universal dimmer	GPA-16RMP/m/37	Through antenna RTV subscriber, 16 dB (on request)
GP-1RM/m/37	Single socket	GPA-10RMP-Z/m/37	Through antenna RTV subscriber (on request)
GP-1RMP/m/37	Single socket with shutters	GPA-RMK/m/37	Terminal antenna RTV subscriber
GP-1RMZ/m/37	Single socket with ground	GPA-2RMF/m/37	Twin antenna RTV subscriber type F
GP-1RMZP/m/37	Single socket with ground, with shutters	GPA-RMS/m/37	Terminal antenna RTV-SAT subscriber
GP-1RMZD/m/37	Single socket with ground DATA	GPT-2RMN/m/37	Twin telephone socket, independent
GP-1RMZDP/m/37	Single socket with ground DATA, with shutters	GPK-2RM/K/m/37	Twin computer socket 5e class, MMC
GP-1RMZK/m/37	Single socket with ground DATA, with access key	GPK-2RM/p/37	Twin computer socket cover, flat

# Sonata New Silver

FLUSH-MOUNTED SERIES

## Flush mounting switches with built-in light

Screwless terminals  
 Rated voltage: 250V  
 Rated current: 16AX  
 Protection rating: IP-20



ŁP-1RMS/m/44  
 Single pole switch 1150



ŁP-2RMS/m/44  
 All-or-part switch, chandelier 1151



ŁP-3RMS/m/44  
 Two-way switch 1152



ŁP-4RMS/m/44  
 Intermediate switch 1153



ŁP-11RMS/m/44  
 Double pole switch 1156



ŁP-12RMS/m/44  
 Control switch 1157

Rated current: 10AX



ŁP-5RMS/m/44  
 Short-circuiting switch „light” 1154



ŁP-6RMS/m/44  
 Short-circuiting switch „bell” 1154



ŁP-7RMS/m/44  
 Venetian blind switch 1155

## Dimmers

Screw terminals  
 Current supply: 230V-50 Hz  
 Protection rating: IP-20



ŁP-8RM/m/44  
 Push-turn dimmer 1159  
 load: 40-400W



ŁP-8RML2/m/44  
 Universal dimmer 1179  
 load: GLS - 10-250W,  
 CFL - 5-75W, LED - 0-100W  
 functions: electronic switch,  
 “time to bed”



ŁP-7RMBS/m/44  
 Venetian blind switch  
 with mechanical lock 1180

Accessories for switches with built-in light are on page 220.

\* on request

## Flush mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-1RM/m/44  
 Single socket 1160



GP-1RMP/m/44  
 Single socket  
 with shutters 1160



GP-1RMZ/m/44  
 Single socket with ground 1161



GP-1RMZP/m/44  
 Single socket with ground,  
 with shutters 1161



GP-1RMZD/m/44  
 Single socket with ground DATA 1162



GP-1RMZDP/m/44  
 Single socket with ground DATA,  
 with shutters 1162



GP-1RMZK/m/44  
 Single socket with ground DATA,  
 with access key 1163

## Antenna subscribers

Screw terminals



GPA-2RMF/m/44  
 Twin, terminal antenna RTV subscriber,  
 type F 1175



GPA-10RMPZ/m/44  
 Through antenna RTV subscriber 1165



GPA-10RMP/m/44  
 Through antenna RTV subscriber 10 dB 1165



GPA-RMK/m/44  
 Terminal antenna RTV subscriber 1166

GPA-14RMP/m/44  
 Through antenna RTV subscriber 14 dB 1165

GPA-16RMP/m/44  
 Through antenna RTV subscriber 16 dB 1165



GPA-RMS/m/44  
 Terminal antenna RTV-SAT subscriber 1171

\* on request

# Sonata New Silver

FLUSH-MOUNTED SERIES

## Computer socket

Connection IDC



GPK-2RM/K/m/44  
Twin computer socket,  
5e class, MMC

1169

## Telephone socket

Connection IDC



GPT-2RMN/m/44  
Twin telephone socket,  
independent

1167


## Socket covers Keystone type



GPK-2RM/p/44  
Twin computer socket cover,  
flat

1176

## Surrounds – sold only in IP-20 version



R-1RM/44  
Single surround

1112



R-2RM/44  
Twin surround

1113



R-3RM/44  
Threefold surround

1114



R-4RM/44  
Fourfold surround

1115



Modules which can be mounted in these  
socket covers are on page 167.

## Example order

To order all-or-part switch with built-in light must be ordered:


**ŁP-1RMS/m/44**

**R-1RM/44**



ŁP-1RMS/m/44

+



R-1RM/44

=



## Designations

Products of SONATA NEW SILVER series are sold without external surround.

Below are written designations which must be used to place the order.

After right product's code write number 44.

ŁP-...RMS/m/44	Switches with built-in light - in the place marked by dots, write the right number of switch	GPA-14RMP/m/44	Through antenna RTV subscriber, 14 dB (on request)
ŁP-8RM/m/44	Push-turn dimmer adapted to incandescent and halogen loading	GPA-16RMP/m/44	Through antenna RTV subscriber, 16 dB (on request)
ŁP-8RML2/m/44	Universal dimmer	GPA-10RMPZ/m/44	Through antenna RTV subscriber (on request)
GP-1RM/m/44	Single socket	GPA-RMK/m/44	Terminal antenna RTV subscriber
GP-1RMP/m/44	Single socket with shutters	GPA-2RMF/m/44	Twin antenna RTV subscriber type F
GP-1RMZ/m/44	Single socket with ground	GPA-RMS/m/44	Terminal antenna RTV-SAT subscriber
GP-1RMZP/m/44	Single socket with ground, with shutters	GPT-2RMN/m/44	Twin telephone socket, independent
GP-1RMZD/m/44	Single socket with ground DATA	GPK-2RM/K/m/44	Twin computer socket 5e class, MMC
GP-1RMZDP/m/44	Single socket with ground DATA, with shutters	GPK-2RM/p/44	Twin computer socket cover, flat
GP-1RMZK/m/44	Single socket with ground DATA, with access key		
GPA-10RMP/m/44	Through antenna RTV subscriber, 10 dB (on request)		




**Wireless control** switches are an evolution of the Sonata series.

# Sonata

## Wireless control

This wireless management system simplifies daily life by controlling lighting, roller blinds, and gates.

The system is based on radio transmission technology. Installation requires no wall channeling or cutting out new mounting boxes, making it easy to upgrade an existing electrical system with new functionalities.



# Sonata Wireless control

SURFACE MOUNTED SERIES

## Wireless connectors

Mounting type: surface-mounted - dowels spaced 60 mm / direct gluing to the wall  
 Current supply: 3V CR2032 battery  
 Frequency: 868 MHz  
 Battery life: up to 3 years  
 Installation: for frames of the Sonata series  
 Cooperation: with F & Wave or Exta Free modules  
 Field of activity: up to 100 m  
 Protection rating: IP20



£N-1RRZ/m/00 1141  
 Two-channel wireless switch  
 Compatible with Exta Free system



£N-1RRF/m/00 1141  
 Two-channel wireless switch  
 Compatible with F&Wave system



£N-2RRZ/m/00 1142  
 Four-channel wireless switch  
 Compatible with Exta Free system



£N-2RRF/m/00 1142  
 Four-channel wireless switch  
 Compatible with F&Wave system

Wireless switches are sold without an external frame.  
 The Sonata series external frame must be purchased separately.

## Two-channel wireless switch keys



K-1RB/75 1141  
 Two-channel wireless switch key\*




K-1RB/27 1141  
 Two-channel wireless switch key



K-1RB/82 1141  
 Two-channel wireless switch key

## AVAILABLE COLOURS



K-1RB/38 1141  
 Two-channel wireless switch key



K-1RB/39 1141  
 Two-channel wireless switch key



K-1RB/40 1141  
 Two-channel wireless switch key



K-1RB/33 1141  
 Two-channel wireless switch key

## Four-channel wireless switch keys



K-2RB/75 1142  
 Four-channel wireless switch keys\*



K-2RB/27 1142  
 Four-channel wireless switch keys



K-2RB/82 1142  
 Four-channel wireless switch keys



K-2RB/38 1142  
 Four-channel wireless switch keys



K-2RB/39 1142  
 Four-channel wireless switch keys



K-2RB/40 1142  
 Four-channel wireless switch keys



K-2RB/33 1142  
 Four-channel wireless switch keys

\*on request

\*on request

# Sonata Wireless control

SURFACE MOUNTED SERIES

nr 00 white

## The wireless connector set for lighting control

### ZłN-1RSF/m/00

Actuator: single multi-functional relay  
 Programmable relay functions: bistable, monostable, time, on-off  
 Coil supply: 250V~  
 Possible number of transmitters: 32 units  
 Local input to the mechanical button  
 Contact type: separated input contact NO, 8 A (AC-1)  
 Terminals: screw-type (max 2,5mm<sup>2</sup>)  
 Transmitter signal re-transmission  
 Built-in electronic thermal protection  
 Installation: flush-mount / at the receiver  
 Frequency: 868 MHz  
 Standby/operation power consumption: 0,25 W / 0,6 W  
 Operating temperature: -25 ÷ 65°C  
 Dimensions: 43 mm x 48 mm x 20 mm  
 Ingress protection: IP20  
 Compatibility with other elements of F&Wave system



łN-1RRF/m/00  
 Two-channel wireless switch  
 Compatible with F&Wave system

+



FW-R1P-P  
 Executive module

## The wireless connector set for lighting control

### ZłN-2RSF/m/00

Actuator: single multi-functional relay  
 Programmable relay functions: bistable, monostable, time, on-off  
 Coil supply: 250V~  
 Possible number of transmitters: 32 units  
 Local input to the mechanical button  
 Contact type: two separated input contacts NO, 4 A (AC-1)  
 Terminals: screw-type (max 2,5mm<sup>2</sup>)  
 Transmitter signal re-transmission  
 Built-in electronic thermal protection  
 Installation: flush-mount / at the receiver  
 Frequency: 868 MHz  
 Standby/operation power consumption: 0,25 W / 0,6 W  
 Operating temperature: -25 ÷ 65°C  
 Dimensions: 43 mm x 48 mm x 20 mm  
 Ingress protection: IP20  
 Compatibility with other elements of F&Wave system



łN-2RRF/m/00  
 Four-channel wireless switch  
 Compatible with F&Wave system

+



FW-R2P-P  
 Executive module

## The wireless connector set for blinds control

### ZłN-1RZF/m/00

Actuator: double multi-functional relay  
 Interlock function, preventing supply power connection to both motor windings.  
 Coil supply: 250V~  
 Possible number of transmitters: 32 szt.  
 Local input to the mechanical button  
 Contact type: two separated contacts 3 A (AC-1), 0,6 A (AC-3)  
 Screw-type terminals (max 2,5mm<sup>2</sup>)  
 Transmitter signal re-transmission  
 Built-in electronic thermal protection  
 Installation: flush-mount / at the receiver  
 Frequency: 868 MHz  
 Standby/operation power consumption: 0,25 W / 0,6 W  
 Operating temperature: -25 ÷ 65°C  
 Dimensions: 43 mm x 48 mm x 20 mm  
 Ingress protection: IP20  
 Compatibility with other elements of F&Wave system



łN-1RRF/m/00  
 Two-channel wireless switch  
 Compatible with F&Wave system

+



FW-STR1P-P  
 Executive module

## Roller blind control module

### FW-STR1P-P

Actuator: double multi-functional relay  
 Interlock function, preventing supply power connection to both motor windings.  
 Coil supply: 250V~  
 Possible number of transmitters: 32 szt.  
 Local input to the mechanical button  
 Contact type: two separated contacts 3 A (AC-1), 0,6 A (AC-3)  
 Screw-type terminals (max 2,5mm<sup>2</sup>)  
 Transmitter signal re-transmission  
 Built-in electronic thermal protection  
 Installation: flush-mount / at the receiver  
 Frequency: 868 MHz  
 Standby/operation power consumption: 0,25 W / 0,6 W  
 Operating temperature: -25 ÷ 65°C  
 Dimensions: 43 mm x 48 mm x 20 mm  
 Ingress protection: IP20  
 Compatibility with other elements of F&Wave system



FW-STR1P-P  
 Executive module

## Example order



łN-1RRZ/m/00

+



R-1RGC/41/25

=



To obtain a two-channel wireless switch in white, with a grey glass frame of the Sonata Prestige series, must be ordered:


łN-1RRZ/m/00  
 R-1RGC/41/25

## Example order



łN-2RRZ/m/00

+



R-1RGC/32/25

=



To obtain a four-channel wireless switch in white, with a black glass frame of the Sonata Prestige series, must be ordered:

łN-2RRZ/m/00  
 R-1RGC/32/25



Offers **endless design possibilities** for any interior, thanks to a wide range of available colors.




# Impresja

The Impresja series is characterized by discreet elegance, subtle shapes, and sophisticated design.


## AVAILABLE COLOURS



White – nr 00



Ecru – nr 27



Silver – nr 18



Gold metallic – nr 28



Titanium – nr 23



Anthracite – nr 50



Black matt – nr 33

## EXAMPLES OF COLOUR COMBINATIONS



Brushed aluminium – nr 62/25



Brushed satin – nr 63/25



Brushed anthracite – nr 64/25



White glass – nr 31/00




Grey glass – nr 41/25



Black glass – nr 32/25



Surrounds  
**Brushed metals**



## Flush mounting switches

Screwless terminals  
 Rated voltage: 250V  
 Rated current: 16AX  
 Protection rating: IP-20



ŁP-1Y/m/00  
Single pole switch 1001



ŁP-3Y/m/00  
Two-way switch 1003



ŁP-2Y/m/00  
All-or-part switch, chandelier 1002

ŁP-9Y/m/00  
Two-way switch + single pole switch 1009

ŁP-10Y/m/00  
Double two-way switch 1010



ŁP-4Y/m/00  
Intermediate switch 1004



ŁP-11Y/m/00  
Double pole switch 1007

Rated current: 10AX



ŁP-5Y/m/00  
Short-circuiting switch „light” 1005



ŁP-6Y/m/00  
Short-circuiting switch „bell” 1005



ŁP-7Y/m/00  
Venetian blind switch 1006

ŁP-7YB/m/00  
Venetian blind switch with mechanical lock 2008



ŁP-13Y/m/00  
Triple switch 1129

ŁP-24Y/m/00  
Short-circuiting triple switch 2084



ŁP-17Y/m/00  
Double short-circuiting switch 1260



ŁP-21Y/m/00  
Short-circuiting switch 1005


Screw terminals



ŁP-19Y/m/00  
Double intermediate switch  
/available only on IP 20 version/ 2094

## Accessories for switches IP-44

There is a possibility to mount switches with protection rating IP-20 as switches with IP-44, to do that, must be bought sealing set presented below.



ZU-1Y  
Sealing set for switches IP-44 1056

## Flush mounting switches with built-in light

Screwless terminals  
 Rated voltage: 250V  
 Rated current: 16AX  
 Protection rating: IP-20



ŁP-1YS/m/00  
Single pole switch 1001



ŁP-2YS/m/00  
All-or-part switch, chandelier 1002



ŁP-3YS/m/00  
Two-way switch 1003



ŁP-4YS/m/00  
Intermediate switch 1004



ŁP-11YS/m/00  
Double pole switch 1007



ŁP-12YS/m/00  
Control switch 1008

Rated current: 10AX



ŁP-5YS/m/00  
Short-circuiting switch „light” 1005



ŁP-6YS/m/00  
Short-circuiting switch „bell” 1005



ŁP-7YS/m/00  
Venetian blind switch 1006



ŁP-7YBS/m/00  
Venetian blind switch with mechanical lock 2008



ŁP-21YS/m/00  
Short-circuiting switch 1005



ŁP-19YS/m/00  
Double intermediate switch  
/available only on IP 20 version/ 2094

## Hotel switch


Screw terminals  
 Current supply: 230~ 50Hz  
 Protection rating: IP-20  
 Rated current: 16A  
 Time of delay: 3s

Switch works with a standard card with dimensions 86 x 54 x 0.8 mm



ŁP-15YS/m/00  
Hotel switch 1041

Accessories for switches with built-in light are on page 220.



## Dimmers

Screw terminals  
Current supply: 230V ~50Hz  
Protection rating: IP-20



ŁP-8Y/m/00 1011  
Push-turn dimmer adapted to incandescent and halogen loading, load 40-400W



ŁP-8YL2/m/00 2005  
Universal dimmer, load: GLS 10-250W, CFL 5-75W, LED 0-100W, functions: electronic switch, "time to bed"

## Temperature regulators

Screw terminals,  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W  
- inductive 750W  
Protection rating: IP-20



RTP-1YN/m/00 1044  
Temperature regulator with aerial sensor



RTP-1Y/m/00\* 1043  
Temperature regulator with underfloor sensor

## Equipotential socket



GPE-1Y/m/00\* 1396  
Single equipotential socket



GPE-2Y/m/00\* 1397  
Twin equipotential socket



WKE\* 1571  
Plug into the equipotential socket

## Flush mounting socket outlets

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-20



GP-1Y/m/00 1013  
Single socket



GP-1YZP/m/00 1014  
Single socket with ground, with shutters



GP-1YZD/m/00 1015  
Single socket with ground DATA



GPH-1YZ/m/00/d 1018  
Hermetic socket with ground, IP-44



GPH-1YSP/m/00/d 1019  
Hermetic socket with ground schuko, IP-44, with shutters



GP-1YP/m/00 1013  
Single socket with shutters



GP-1YS/m/00 1017  
Single socket with ground schuko



GP-1YZDP/m/00 1015  
Single socket with ground DATA, with shutters



GPH-1YZP/m/00/d 1018  
Hermetic socket with ground, IP-44, with shutters



GP-1YZ/m/00 1014  
Single socket with ground



GP-1YSP/m/00 1017  
Single socket with ground schuko, with shutters



GP-1YZK/m/00 1016  
Single socket with ground DATA, with access key



GPH-1YS/m/00/d 1019  
Hermetic socket with ground schuko, IP-44

## Electronic movement detector

Screw terminals  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W,  
- fluorescent 750W  
- inductive 750W  
Protection rating: IP-20  
Way of adjustment the time of transmitter's switching on: 3s. – 5min.  
Angle of movement detection's field: 136°  
Field of activity: 7m  
Works with LED light



ŁP-16Y/m/00 1042  
Electronic movement detector

## Triple socket EURO

Screw terminals  
Rated voltage: 250V  
Rated current: 2,5A  
Protection rating: IP-20



GP-3Y/m/00 1025  
Triple socket EURO

Hermetic sockets in white and ecru colours are also offered with lid in product's colour. After right product's code write: .../00/w for products in white colour or .../27/w for products in ecru colour.

## Single socket with ground, with USB charger

Screwless terminals  
 Rated voltage:  
 – input: 230V~50Hz  
 – output: 5VDC  
 Rated current: 2,1A  
 Protection rating: IP-20  
 Doesn't work with surface mounting wall frames



GP-1YZPUSB/m/00 2066  
 Single socket with ground, with shutters, with USB charger

## Single socket with ground, with USB A+C charger

Screwless terminals  
 Rated voltage:  
 – input: 230V~50Hz (max 0,3A)  
 – output A or C: 5VDC/ 3A; 9VDC/ 2,22A; 12VDC/ 1,67A  
 – output A+C: 5VDC/ 3,4A max 20W  
 Protection rating IP-20  
 Doesn't work with surface mounting wall frames  
 Standard fast charger



GP-1YZPUSBAC/m/00 2069  
 Single socket with ground, with shutters, with USB A+C charger

## Flush mounting socket outlets for Standard surrounds

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-2YR/m/00 1022  
 Twin socket



GP-2YRP/m/00 1022  
 Twin socket with shutters



GP-2YRZ/m/00 1023  
 Twin socket with ground



GP-2YRZP/m/00 1023  
 Twin socket with ground, with shutters

## Flush mounting socket outlets for Prestige surrounds

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20




GP-2YRAZ/m/00 1023  
 Twin socket with ground



GP-2YRAZP/m/00 1023  
 Twin socket with ground, with shutters

## AVAILABLE COLOURS



## Flush mounting socket outlets (sold entire)

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-2Y/00 1020  
 Twin socket



GP-2YP/00 1020  
 Twin socket with shutters



GP-2YZ/00 1021  
 Twin socket with ground



GP-2YZP/00 1021  
 Twin socket with ground, with shutters



GP-2YS/00 1024  
 Twin socket with ground schuko



GP-2YSP/00 1024  
 Twin socket with ground schuko, with shutters



GP-2YC/00 1026  
 Twin socket with ground, without changing phase

## Blank cover



Z-1Y/m/00 1066  
 Blank cover

## Cable terminal

Screw terminals, 5x4mm<sup>2</sup>  
 Protection rating: IP-20  
 Flush-mounted into ø60 boxes



GPPK-1Y/m/00 1139  
 Cable terminal



## Antenna subscribers

Screw terminals



GPA-1YF/m/00 1031  
Single, terminal antenna RTV subscriber, type F




GPA-2YF/m/00 1376  
Twin, terminal antenna RTV subscriber, type F



GPA-10YPZ/m/00\* 1027  
Through antenna RTV subscriber, ZAK-10, attenuation coefficient 10 dB



GPA-10YP/m/00\* 1027  
Through antenna RTV subscriber, attenuation coefficient 10 dB



GPA-14YP/m/00\* 1027  
Through antenna RTV subscriber, attenuation coefficient 14 dB



GPA-16YP/m/00\* 1027  
Through antenna RTV subscriber, attenuation coefficient 16 dB



GPA-YK/m/00 1028  
Terminal antenna RTV subscriber, ZAR-1



GPA-YS/m/00 1029  
Terminal antenna RTV-SAT subscriber



GPA-YSP/m/00\* 1030  
Through antenna RTV-SAT subscriber



GPA-Y2S/m/00 1067  
Terminal antenna RTV-SAT subscriber, with two outlets SAT



GPA-YD/m/00\* 1385  
Terminal antenna RTV-DATA subscriber

## Telephone sockets

Screw terminals



GPT-1Y/m/00 1032  
Single telephone socket



GPT-2YN/m/00 1033  
Twin telephone socket, independent



GPT-2YR/m/00 1033  
Twin telephone socket, parallel

## Computer sockets

Connection IDC



GPK-1Y/K/m/00 1034  
Single computer socket, 5e class, MMC



GPK-2Y/K/m/00\* 1035  
Twin computer socket, 5e class, MMC

## Loudspeaker sockets



GG-1Y/m/00 1039  
Single loudspeaker socket  
Connection of lines ability 0,75 mm<sup>2</sup>



GG-2Y/m/00 1040  
Twin loudspeaker socket  
Connection of lines ability 0,75 mm<sup>2</sup>



GGN-1Y/m/00 1145  
Single loudspeaker socket  
connection of lines ability 6 mm<sup>2</sup>

## Adapter

It allows to use of OspeL 45 system products in the Impresja series.



AP45-1Y/m/00 2057  
Adapter

## Sockets covers Keystone type



GPK-1YS/p/00 1368  
Single computer socket cover, slant



GPK-2YS/p/00 1369  
Twin computer socket cover, slant



GPK-1Y/p/00 1390  
Single computer socket cover, flat




GPK-2Y/p/00 1391  
Twin computer socket cover, flat

Modules which can be mounted in these socket covers are on page 167.


## Wall frames




PNP-1Y/00 1051  
Single wall frame



PNP-2Y/00 1052  
Twin wall frame




PNP-3Y/00 1053  
Threefold wall frame



PNP-4Y/00 1054  
Fourfold wall frame




PNP-5Y/00 1055  
Fivefold wall frame



## Surrounds Standard

white



R-1Y/00	1046
Single surround	
R-2Y/00	1047
Twin surround	
R-3Y/00	1048
Threefold surround	
R-4Y/00	1049
Fourfold surround	
R-5Y/00	1050
Fivefold surround	

ecru



R-1Y/27	1046
Single surround	
R-2Y/27	1047
Twin surround	
R-3Y/27	1048
Threefold surround	
R-4Y/27	1049
Fourfold surround	
R-5Y/27	1050
Fivefold surround	

## Surrounds Metallic

silver



R-1Y/18	1046
Single surround	
R-2Y/18	1047
Twin surround	
R-3Y/18	1048
Threefold surround	
R-4Y/18	1049
Fourfold surround	
R-5Y/18	1050
Fivefold surround	

titanium



R-1Y/23	1046
Single surround	
R-2Y/23	1047
Twin surround	
R-3Y/23	1048
Threefold surround	
R-4Y/23	1049
Fourfold surround	
R-5Y/23	1050
Fivefold surround	

gold metallic



R-1Y/28	1046	
Single surround		
R-2Y/28	1047	
Twin surround		
R-3Y/28	1048	
Threefold surround		
R-4Y/28	1049	
Fourfold surround		
R-5Y/28	1050	
Fivefold surround		

anthracite



R-1Y/50	1046	
Single surround		
R-2Y/50	1047	
Twin surround		
R-3Y/50	1048	
Threefold surround		
R-4Y/50	1049	
Fourfold surround		
R-5Y/50	1050	
Fivefold surround		

black matt



R-1Y/33	1046	
Single surround		
R-2Y/33	1047	
Twin surround		
R-3Y/33	1048	
Threefold surround		
R-4Y/33	1049	
Fourfold surround		
R-5Y/33	1050	
Fivefold surround		

Presented surrounds are universal, the products can be mounted in horizontal and vertical position.

## Surrounds Standard for sets IP-44

white



RH-1Y/00	1046
Single surround	
RH-2Y/00	1047
Twin surround	
RH-3Y/00	1048
Threefold surround	
RH-4Y/00	1049
Fourfold surround	
RH-5Y/00	1050
Fivefold surround	

ecru



RH-1Y/27	1046
Single surround	
RH-2Y/27	1047
Twin surround	
RH-3Y/27	1048
Threefold surround	
RH-4Y/27	1049
Fourfold surround	
RH-5Y/27	1050
Fivefold surround	

## Surrounds Metallic for sets IP-44

silver



RH-1Y/18	1046
Single surround	
RH-2Y/18	1047
Twin surround	
RH-3Y/18	1048
Threefold surround	
RH-4Y/18	1049
Fourfold surround	
RH-5Y/18	1050
Fivefold surround	

titanium



RH-1Y/23	1046
Single surround	
RH-2Y/23	1047
Twin surround	
RH-3Y/23	1048
Threefold surround	
RH-4Y/23	1049
Fourfold surround	
RH-5Y/23	1050
Fivefold surround	

gold metallic



RH-1Y/28	1046	
Single surround		
RH-2Y/28	1047	
Twin surround		
RH-3Y/28	1048	
Threefold surround		
RH-4Y/28	1049	
Fourfold surround		
RH-5Y/28	1050	
Fivefold surround		

anthracite




RH-1Y/50	1046	
Single surround		
RH-2Y/50	1047	
Twin surround		
RH-3Y/50	1048	
Threefold surround		
RH-4Y/50	1049	
Fourfold surround		
RH-5Y/50	1050	
Fivefold surround		

black matt




RH-1Y/33	1046	
Single surround		
RH-2Y/33	1047	
Twin surround		
RH-3Y/33	1048	
Threefold surround		
RH-4Y/33	1049	
Fourfold surround		
RH-5Y/33	1050	
Fivefold surround		



## Surrounds Prestige – sold only in IP-20 version

brushed aluminium + black surround



R-1YAC/62/25 Single surround	1046
R-2YAC/62/25 Twin surround	1047
R-3YAC/62/25 Threefold surround	1048
R-4YAC/62/25 Fourfold surround	1049
R-5YAC/62/25 Fivefold surround	1050

brushed satin + black surround



R-1YAC/63/25 Single surround	1046
R-2YAC/63/25 Twin surround	1047
R-3YAC/63/25 Threefold surround	1048
R-4YAC/63/25 Fourfold surround	1049
R-5YAC/63/25 Fivefold surround	1050

brushed anthracite + black surround



R-1YAC/64/25 Single surround	1046	
R-2YAC/64/25 Twin surround	1047	
R-3YAC/64/25 Threefold surround	1048	
R-4YAC/64/25 Fourfold surround	1049	
R-5YAC/64/25 Fivefold surround	1050	

white glass + white surround




R-1YGC/31/00 Single surround	1046
R-2YGC/31/00 Twin surround	1047
R-3YGC/31/00 Threefold surround	1048
R-4YGC/31/00 Fourfold surround	1049
R-5YGC/31/00 Fivefold surround	1050

grey glass + black surround



R-1YGC/41/25 Single surround	1046
R-2YGC/41/25 Twin surround	1047
R-3YGC/41/25 Threefold surround	1048
R-4YGC/41/25 Fourfold surround	1049
R-5YGC/41/25 Fivefold surround	1050

black glass + black surround



R-1YGC/32/25 Single surround	1046	
R-2YGC/32/25 Twin surround	1047	
R-3YGC/32/25 Threefold surround	1048	
R-4YGC/32/25 Fourfold surround	1049	
R-5YGC/32/25 Fivefold surround	1050	

## Ramki Prestige – sold only in IP-20 version


size – 4 mm

white frosted glass, bevelled + white surround





RS-1YGC/78/00 Single surround	1112
RS-2YGC/78/00 Twin surround	1113
RS-3YGC/78/00 Threefold surround	1114
RS-4YGC/78/00 Fourfold surround	1115
RS-5YGC/78/00 Fivefold surround	1116

black frosted glass, bevelled + black surround



RS-1YGC/79/33 Single surround	1112
RS-2YGC/79/33 Twin surround	1113
RS-3YGC/79/33 Threefold surround	1114
RS-4YGC/79/33 Fourfold surround	1115
RS-5YGC/79/33 Fivefold surround	1116





## Example order

To order single pole switch in white colour must be ordered:  
**ŁP-1Y/m/00**  
**R-1Y/00**



To order single pole switch in ecru colour must be ordered:  
**ŁP-1Y/m/27**  
**R-1Y/27**



To order two-way switch in silver colour must be ordered:  
**ŁP-3Y/m/18**  
**R-1Y/18**



## Designations

Products of IMPRESJA series (\*excluding a few twin sockets) in all colours are sold without external surround. Below are written designations which must be used to place the order.

After right product's code write the right number of colour  
 white – number 00,  
 ecru – number 27,  
 silver – number 18,  
 gold metallic – number 28,  
 titanium – number 23,  
 anthracite – number 50,  
 black matt – number 33.

ŁP-.....Y/m	Switches – in the place marked by dots, write the right number of switch	GP-2YS	Twin socket with ground schuko*
ŁP-.....YS/m	Switches with built-in light - in the place marked by dots, write the right number of switch	GP-2YSP	Twin socket with ground schuko, with shutters*
ŁP-8Y/m	Push-turn dimmer adapted to incandescent and halogen loading	GP-2YC	Twin socket without changing phase*
ŁP-8YL2/m	Universal dimmer	GP-3Y/m	Triple socket EURO
ŁP-15YS/m	Hotel switch	GPT-1Y/m	Single telephone socket
ŁP-16Y/m	Electronic movement detector	GPT-2YN/m	Twin telephone socket, independent
GP-1Y/m	Single socket	GPT-2YR/m	Twin telephone socket, parallel
GP-1YP/m	Single socket with shutters	GPA-10YP/m	Through antenna RTV subscriberZAP-10 (on request)
GP-1YZ/m	Single socket with ground	GPA-14YP/m	Through antenna RTV subscriberZAP-14 (on request)
GP-1YZP/m	Single socket with ground, with shutters	GPA-16YP/m	Through antenna RTV subscriberZAP-16 (on request)
GP-1YS/m	Single socket with ground schuko	GPA-10YPZ/m	Through antenna RTV subscriber
GP-1YSP/m	Single socket with ground schuko, with shutters	GPA-YK/m	Terminal antenna RTV subscriber ZAR-1
GP-1YZD/m	Single socket with ground DATA	GPA-YS/m	Terminal antenna RTV-SAT subscriber
GP-1YZDP/m	Single socket with ground DATA, with shutters	GPA-YSP/m	Through antenna RTV-SAT subscriber (on request)
GP-1YZK/m	Single socket with ground DATA, with access key	GPA-Y2S/m	Terminal antenna RTV-SAT subscriber, with two outlets SAT
GPH-1YZ/m	Hermetic socket IP-44	GPA-YD/m	Terminal antenna RTV-DATA subscriber (on request)
GPH-1YZP/m	Hermetic socket IP-44, with shutters	GPA-1YF/m	Single, terminal antenna RTV subscriber, type F
GPH-1YS/m	Hermetic socket with ground schuko, IP-44	GPA-2YF/m	Twin, terminal antenna RTV subscriber, type F
GPH-1YSP/m	Hermetic socket with ground schuko, IP-44, with shutters	GG-1Y/m	Single loudspeaker socket
GP-1YZPUSB/m	Single socket with ground, with USB charger, with shutters	GG-2Y/m	Twin loudspeaker socket
GP-1YZPUSBAC/m	Single socket with ground, with USB A+C charger, with shutters	GGN-1Y/m	Single loudspeaker socket
GP-2YR/m	Twin socket	AP45-1Y/m	Adapter
GP-2YRP/m	Twin socket with shutters	GPK-1Y/K/m	Single computer socket, 5e class, MMC
GP-2YRZ/m	Twin socket with ground	GPK-2Y/K/m	Twin computer socket, 5e class, MMC
GP-2YRZP/m	Twin socket with ground, with shutters	GPE-1Y/m	Single equipotential socket (on request)
GP-2YRAZ/m	Twin socket with ground	GPE-2Y/m	Twin equipotential socket (on request)
GP-2YRAZP/m	Twin socket with ground,with shutters	GPK-1YS/p	Single computer socket cover, slant
GP-2Y	Twin socket*	GPK-2YS/p	Twin computer socket cover, slant
GP-2YP	Twin socket with shutters*	GPK-1Y/p	Single computer socket cover, flat
GP-2YZ	Twin socket with ground*	GPK-2Y/p	Twin computer socket cover, flat
GP-2YZP	Twin socket with ground, with shutters*	RTP-1Y/m	Temperature regulator with underfloor sensor (on request)
		RTP-1YN/m	Temperature regulator with aerial sensor
		Z-1Y/m	Blank cover
		GPPK-1Y/m	Cable terminal


# Impresja

FLUSH-MOUNTED SERIES

Quick and easy installation of wiring accessories



Safety shutters protect children from electric shock by preventing the insertion of metal objects into the socket apertures.



The enclosed design of the self-returning mounting claws protects the installer's fingers from accidental injury.



Side wire entry allows for a visual quality check of the terminal connections even after the socket module has been fully installed in the wall box.

## SOCKETS




A universal multi-gang frame system that allows for both vertical and horizontal layouts.




Quick assembly and disassembly of the frame on the switch module, thanks to the use of a quick-release mounting cover.

## SWITCHES



Side wire entry allows for a visual quality check of the terminal connections even after the switch module has been fully installed in the wall box. Ergonomic release buttons ensure easy removal of the wires from the terminals. Furthermore, the red button allows for quick and easy identification of the live (line) wire terminal.




The replaceable illumination module allows you to choose the color of the emitted light, ensuring a perfect match with your interior design.



Self-returning mounting claws, equipped with stainless steel spring elements, significantly facilitate the installation of the switch module in the wall box.



**Top-quality materials**  
and timeless design  
–a stylish addition to  
your interior for years.



# AS

The As series features a geometric form softened by the delicate curves of its frames. It is a perfect blend of dynamic design and neutral colors that will suit any interior.

## AVAILABLE COLOURS



White – nr 00



Ecrú – nr 27



Cashmere – nr 82



Green matt – nr 84




Silver – nr 18



Black matt – nr 33



# Cashmere



## Flush mounting switches

Screw terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-20



ŁP-1G/m/00  
Single pole switch 1300



ŁP-2G/m/00  
All-or-part switch, chandelier 1301



ŁP-9G/m/00  
Two-way + single pole switch 1308

ŁP-17G/m/00  
Double short-circuiting switch 1363

ŁP-10G/m/00  
Double two-way switch 1309

ŁP-19G/m/00  
Double intermediate switch  
/available only on IP 20 version/ 2093



ŁP-3G/m/00  
Two-way switch 1302



ŁP-4G/m/00  
Intermediate switch 1303



ŁP-5G/m/00  
Short-circuiting switch „light” 1304



ŁP-6G/m/00  
Short-circuiting switch „bell” 1304



ŁP-7G/m/00  
Venetian blind switch 1305



ŁP-7GB/m/00  
Venetian blind switch  
with mechanical lock 2010



ŁP-11G/m/00  
Double pole switch 1306



ŁP-21G/m/00  
Short-circuiting switch 1304

## Accessories for switches IP-44

There is a possibility to mount switches with protection rating IP-20 as switches with IP-44, to do that, must be bought sealing set presented below.



ZU-1G  
Sealing set for switches IP-44 1352



ŁP-13G/m/00  
Triple switch 1310



ŁP-24G/m/00  
Short-circuiting triple switch 2086

## Flush mounting switches with built-in light

Screw terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-20



ŁP-1GS/m/00  
Single pole switch 1300



ŁP-2GS/m/00  
All-or-part switch, chandelier 1301



ŁP-3GS/m/00  
Two-way switch 1302



ŁP-4GS/m/00  
Intermediate switch 1303



ŁP-5GS/m/00  
Short-circuiting switch „light” 1304



ŁP-6GS/m/00  
Short-circuiting switch „bell” 1304



ŁP-7GS/m/00  
Venetian blind switch 1305



ŁP-7GBS/m/00  
Venetian blind switch  
with mechanical lock 2010



ŁP-11GS/m/00  
Double pole switch 1306



ŁP-12GS/m/00  
Control switch 1307



ŁP-21GS/m/00  
Short-circuiting switch 1304

## Hotel switch

Screw terminals  
 Current supply: 230~ 50Hz  
 Protection rating: IP-20  
 Rated current: 16A  
 Time of delay: 3s

Switch works with a standard card with dimensions 86 x 54 x 0.8 mm




ŁP-15GS/m/00  
Hotel switch 1342

## Screwless terminals



ŁP-13GS/m/00  
Triple switch 1310

Accessories for switches with built-in light are on page 220.



## Dimmers

Screw terminals  
Current supply: 230V~50Hz  
Protection rating: IP-20



ŁP-8G/m/00 1311  
Push-turn dimmer adapted to incandescent and halogen loading, load 40-400W



ŁP-8GL2/m/00 2007  
Universal dimmer load: GLS - 10-250W, CFL - 5-75W LED - 0-100W functions: electronic switch, "time to bed"

## Temperature regulators

Screw terminals  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W  
- inductive 750W  
Protection rating: IP-20



RTP-1GN/m/00 1388  
Temperature regulator with aerial sensor



RTP-1G/m/00\* 1344  
Temperature regulator with underfloor sensor

## Electronic movement detector

Screw terminals  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W,  
- fluorescent 750W  
- inductive 750W  
Protection rating: IP-20  
Way of adjustment the time of transmitter's switching on: 3s. - 5min.  
Angle of movement detection's field: 136°  
Field of activity: 7m  
Works with LED light



ŁP-16G/m/00 1343  
Electronic movement detector

## Equipotential socket



GPE-1G/m/00\* 1382  
Single equipotential socket



GPE-2G/m/00\* 1383  
Twin equipotential socket



WKE\* 1571  
Plug into the equipotential socket

## Triple socket EURO

Screw terminals  
Rated voltage: 250V  
Rated current: 2,5A  
Protection rating: IP-20



GP-3G/m/00 1325  
Triple socket EURO

## Single socket with ground with USB charger

Screwless terminals  
Rated voltage:  
- input: 230V~50Hz  
- output: 5VDC  
Rated current: 2,1A  
Protection rating: IP-20  
Doesn't work with surface mounting wall frames



GP-1GZPUSB/m/00 2067  
Single socket with ground, with shutters, with USB charger

## Single socket with ground, with USB A+C charger

Screwless terminals  
Rated voltage: +  
- input: 230V~ 50Hz (max 0,3A)  
- output A or C: 5VDC/ 3A; 9VDC/ 2,22A; 12VDC/ 1,67A  
- output A+C: 5VDC/ 3,4A max 20W  
Protection rating IP-20  
Doesn't work with surface mounting wall frames  
Standard fast charger



GP-1GZPUSBAC/m/00 2065  
Single socket with ground, with shutters, with USB A+C charger

## Flush mounting socket outlets

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-20



GP-1G/m/00 1313  
Single socket



GP-1GZP/m/00 1314  
Single socket with ground, with shutters



GP-1GZD/m/00 1315  
Single socket with ground DATA



GP-1GZD/m/12\* 1315  
Single socket with ground DATA



GP-1GP/m/00 1313  
Single socket with shutters



GP-1GS/m/00 1317  
Single socket with ground schuko



GP-1GZDP/m/00 1315  
Single socket with ground DATA, with shutters



GP-1GZDP/m/12\* 1315  
Single socket with ground DATA, with shutters



GP-1GZ/m/00 1314  
Single socket with ground




GP-1GSP/m/00 1317  
Single socket with ground schuko, with shutters



GP-1GZK/m/00 1316  
Single socket with ground DATA, with access key



GP-1GZK/m/12\* 1316  
Single socket with ground DATA, with access key



## Flush mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-44



GPH-1GZ/m/00/d  
 Hermetic socket  
 with ground, IP-44

1318



GPH-1GZD/m/00/d\*  
 Hermetic socket  
 with ground DATA, IP-44

1318



GPH-1GZK/m/00/d\*  
 Hermetic socket  
 with ground DATA, IP-44,  
 with access key

2025



GPH-1GZP/m/00/d  
 Hermetic socket  
 with ground, IP-44,  
 with shutters

1318



GPH-1GZD/m/00/w\*  
 Hermetic socket  
 with ground DATA, IP-44

1318



GPH-1GZK/m/00/w\*  
 Hermetic socket  
 with ground DATA, IP-44,  
 with access key

2025



GPH-1GS/m/00/d  
 Hermetic socket  
 with ground schuko, IP-44

1319



GPH-1GZD/m/12/d\*  
 Hermetic socket  
 with ground DATA, IP-44

1318



GPH-1GZK/m/12/d\*  
 Hermetic socket  
 with ground DATA, IP-44,  
 with access key

2025



GPH-1GSP/m/00/d  
 Hermetic socket with ground  
 schuko, IP-44, with shutters

1319



GPH-1GZD/m/12/w\*  
 Hermetic socket  
 with ground DATA, IP-44

1318



GPH-1GZK/m/12/w\*  
 Hermetic socket  
 with ground DATA, IP-44,  
 with access key

2025

Hermetic sockets in white and ecru colours are also offered with lid in product's colour.  
 After right product's code write: .../00/w for products in white colour or .../27/w for products  
 in ecru colour.

\* on request

## Flush mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-2GR/m/00  
 Twin socket

1322



GP-2GRP/m/00  
 Twin socket with shutters

1322



GP-2GRZ/m/00  
 Twin socket with ground

1323



GP-2GRZP/m/00  
 Twin socket with ground,  
 with shutters

1323

## Flush mounting socket outlets (sold entire)

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-2G/00  
 Twin socket

1320



GP-2GZ/00  
 Twin socket with ground

1321



GP-2GS/00  
 Twin socket with ground  
 schuko

1324



GP-2GC/00  
 Twin socket with ground,  
 without changing phase

1326



GP-2GP/00  
 Twin socket with shutters

1320




GP-2GZP/00  
 Twin socket with ground,  
 with shutters

1321



GP-2GSP/00  
 Twin socket with ground  
 schuko, with shutters

1324



## Antenna subscribers

Screw terminals



GPA-1GF/m/00 1332  
Single, terminal antenna RTV subscriber, type F



GPA-2GF/m/00 1375  
Twin, terminal antenna RTV subscriber, type F



GPA-GK/m/00 1328  
Terminal antenna RTV subscriber, attenuation coefficient 2,5-3 dB

GPA-10GPZ/m/00\* 1327  
Through antenna RTV subscriber, attenuation coefficient 10 dB



GPA-10GP/m/00\* 1327  
Through antenna RTV subscriber, attenuation coefficient 10 dB

GPA-14GP/m/00\* 1327  
Through antenna RTV subscriber, attenuation coefficient 14 dB

GPA-16GP/m/00\* 1327  
Through antenna RTV subscriber, attenuation coefficient 16 dB



GPA-GS/m/00 1329  
Terminal antenna RTV-SAT subscriber, attenuation coefficient 1,5-2 dB

GPA-GSP/m/00\* 1330  
Through antenna RTV-SAT subscriber, attenuation coefficient 1,2 dB



GPA-G2S/m/00 1331  
Terminal antenna RTV-SAT subscriber with two outlets SAT



GPA-GD/m/00\* 1384  
Terminal antenna RTV-DATA subscriber

## Telephone sockets

Screw terminals



GPT-1G/m/00 1333  
Single telephone socket



GPT-2GN/m/00 1334  
Twin telephone socket, independent

GPT-2GR/m/00 1334  
Twin telephone socket, parallel

## Adapter

It allows to use of Ospel 45 system products in the As series.



AP45-1G/m/00 2058  
Adapter

## Loudspeaker sockets

Connection of lines ability 0,75 mm<sup>2</sup>



GG-1G/m/00 1340  
Single loudspeaker socket connection of lines ability 0,75 mm<sup>2</sup>



GG-2G/m/00 1341  
Twin loudspeaker socket connection of lines ability 0,75 mm<sup>2</sup>



GGN-1G/m/00 1387  
Single loudspeaker socket connection of lines ability 6 mm<sup>2</sup>

## Computer sockets

Connection IDC



GPK-1G/K/m/00 1335  
Single computer socket, 5e class, MMC



GPK-2G/K/m/00 1336  
Single computer socket, 5e class, MMC

## Sockets covers Keystone type



GPK-1GS/p/00 1366  
Single computer socket cover, slant



GPK-2GS/p/00 1367  
Twin computer socket cover, slant



GPK-1G/p/00 1394  
Single computer socket cover, flat



GPK-2G/p/00 1395  
Twin computer socket cover, flat



GPK-1GP/p/00 2012  
Single computer socket cover, with shutter, flat



GPK-2GP/p/00 2013  
Twin computer socket cover, with shutter, flat

Modules which can be mounted in these socket covers are on page 167.

## Blank cover



Z-1G/m/00  
Blank cover

1362

## Cable terminal

Screw terminals, 5x4mm<sup>2</sup>  
Protection rating: IP-20  
Flush-mounted into ø60 boxes



GPPK-1G/m/00  
Cable terminal

1140

## Wall frames



PNP-1G/00  
Single wall frame

2161



PNP-2G/00  
Twin wall frame

2162



PNP-3G/00  
Threefold wall frame

2163



PNP-4G/00  
Fourfold wall frame

2164




PNP-5G/00  
Fivefold wall frame

2165



## AVAILABLE COLOURS



## Surrounds Standard

white



R-1G/00  
Single surround

1347

R-2G/00  
Twin surround

1348

R-3G/00  
Threefold surround

1349

R-4G/00  
Fourfold surround

1350

R-5G/00  
Fivefold surround

1351

ecru



R-1G/27  
Single surround

1347

R-2G/27  
Twin surround

1348

R-3G/27  
Threefold surround

1349

R-4G/27  
Fourfold surround

1350

R-5G/27  
Fivefold surround

1351



## Surrounds Standard for sets IP-44

white



RH-1G/00  
Single surround

1347

RH-2G/00  
Twin surround

1348

RH-3G/00  
Threefold surround

1349

RH-4G/00  
Fourfold surround

1350

RH-5G/00  
Fivefold surround

1351

ecru



RH-1G/27  
Single surround

1347

RH-2G/27  
Twin surround

1348

RH-3G/27  
Threefold surround

1349


RH-4G/27  
Fourfold surround

1350

RH-5G/27  
Fivefold surround

1351





## Surrounds Metallic

cashmere




- R-1G/82 1347  
Single surround
- R-2G/82 1348  
Twin surround
- R-3G/82 1349  
Threefold surround
- R-4G/82 1350  
Fourfold surround
- R-5G/82 1351  
Fivefold surround

silver



- R-1G/18 1347  
Single surround
- R-2G/18 1348  
Twin surround
- R-3G/18 1349  
Threefold surround
- R-4G/18 1350  
Fourfold surround
- R-5G/18 1351  
Fivefold surround

green matt




- R-1G/84 1347  
Single surround
- R-2G/84 1348  
Twin surround
- R-3G/84 1349  
Threefold surround
- R-4G/84 1350  
Fourfold surround
- R-5G/84 1351  
Fivefold surround

black matt



- R-1G/33 1347  
Single surround
- R-2G/33 1348  
Twin surround
- R-3G/33 1349  
Threefold surround
- R-4G/33 1350  
Fourfold surround
- R-5G/33 1351  
Fivefold surround



## Surrounds Metallic for sets IP-44

cashmere




- RH-1G/82 1347  
Single surround
- RH-2G/82 1348  
Twin surround
- RH-3G/82 1349  
Threefold surround
- RH-4G/82 1350  
Fourfold surround
- RH-5G/82 1351  
Fivefold surround

silver



- RH-1G/18 1347  
Single surround
- RH-2G/18 1348  
Twin surround
- RH-3G/18 1349  
Threefold surround
- RH-4G/18 1350  
Fourfold surround
- RH-5G/18 1351  
Fivefold surround

green matt




- RH-1G/84 1347  
Single surround
- RH-2G/84 1348  
Twin surround
- RH-3G/84 1349  
Threefold surround
- RH-4G/84 1350  
Fourfold surround
- RH-5G/84 1351  
Fivefold surround

black matt



- RH-1G/33 1347  
Single surround
- RH-2G/33 1348  
Twin surround
- RH-3G/33 1349  
Threefold surround
- RH-4G/33 1350  
Fourfold surround
- RH-5G/33 1351  
Fivefold surround



## Example order

To order single pole switch in white colour must be ordered:

ŁP-1G/m/00

R-1G/00



To order single pole switch with built-in light in ecru colour must be ordered:

ŁP-1GS/m/27

R-1G/27




To order USB charger in white colour must be ordered:

GK-2USB/00

AP45-1G/m/00

R-1G/00



## Green matt

## Designations

Products of AS series (\*excluding a few twin sockets) in all colours are sold without external surround. Below are written designations which must be used to place the order.

After the product's code write the right number of colour:

white – number 00,  
 ecru – number 27,  
 cashmere – number 82,  
 green matt – number 84,  
 silver – number 18,  
 black matt – number 33.

ŁP-.....G/m	Switches - in the place marked by dots, write the right number of switch	GPH-1GSP/m	Hermetic socket with ground schuko, IP-44, with shutters	GPT-2GN/m	Twin telephone socket, independent	GPK-1GS/p	Single computer socket cover, slant
ŁP-.....GS/m	Switches with built-in light - in the place marked by dots, write the right number of switch	GPH-1GZD/m	Hermetic socket with ground DATA, IP-44	GPT-2GR/m	Twin telephone socket, parallel	GPK-2GS/p	Twin computer socket cover, slant
ŁP-8G/m	Push-turn dimmer adapted to incandescent and halogen loading	GPH-1GZK/m	Hermetic socket with ground DATA, IP-44, with access key	GPA-10GP/m	Through antenna RTV subscriber ZAP-10 (on request)	GPK-1G/p	Single computer socket cover, flat
ŁP-8GL2/m/	Universal dimmer	GP-1GZPUSB/m	Single socket with ground, with USB charger, with shutters	GPA-14GP/m	Through antenna RTV subscriber ZAP-14 (on request)	GPK-2G/p	Twin computer socket cover, flat
ŁP-15GS/m	Hotel switch	GP-1GZPUSBAC/m	Single socket with ground, with USB A+C charger, with shutters	GPA-16GP/m	Through antenna RTV subscriber ZAP-16 (on request)	GPK-1GP/p	Single computer socket cover, with shutter, flat
ŁP-16G/m	Electronic movement detector	GP-2GR/m	Twin socket	GPA-10GPZ/m	Through antenna RTV subscriber, (on request)	GPK-2GP/p	Twin computer socket cover, with shutter, flat
GP-1G/m	Single socket	GP-2GRP/m	Twin socket with shutters	GPA-GK/m	Terminal antenna RTV subscriber ZAR-1	RTP-1G/m	Temperature regulator with underfloor sensor (on request)
GP-1GP/m	Single socket with shutters	GP-2GRZ/m	Twin socket with ground	GPA-GS/m	Terminal antenna RTV-SAT subscriber,	RTP-1GN/m	Temperature regulator with aerial sensor
GP-1GZ/m	Single socket with ground	GP-2GRZP/m	Twin socket with ground, with shutters	GPA-GSP/m	Through antenna RTV-SAT subscriber (on request)	Z-1G/m	Blank cover
GP-1GZP/m	Single socket with ground, with shutters	GP-2G	Twin socket*	GPA-G2S/m	Terminal antenna RTV-SAT subscriber, with two outlets SAT	GPPK-1G/m	Cable terminal
GP-1GS/m	Single socket with ground schuko	GP-2GP	Twin socket with shutters*	GPA-GD/m	Terminal antenna RTV-DATA subscriber (on request)	AP45-1G/m	Adapter
GP-1GSP/m	Single socket with ground schuko, with shutters	GP-2GZ	Twin socket with ground*	GPA-1GF/m	Single, terminal antenna RTV subscriber, type F		
GP-1GZD/m	Single socket with ground DATA	GP-2GZP	Twin socket with ground, with shutters*	GPA-2GF/m	Twin, terminal antenna RTV subscriber, type F		
GP-1GZDP/m	Single socket with ground DATA, with shutters	GP-2GS	Twin socket with ground schuko*	GG-1G/m	Single loudspeaker socket		
GP-1GZK/m	Single socket with ground DATA, with access key	GP-2GSP	Twin socket with ground schuko, with shutters*	GG-2G/m	Twin loudspeaker socket		
GPH-1GZ/m	Hermetic socket IP-44	GP-2GSC	Twin socket without changing phase*	GGN-1G/m/	Single loudspeaker socket		
GPH-1GZP/m	Hermetic socket IP-44, with shutters	GP-3G/m	Triple socket EURO	GPK-1G/K/m	Single computer socket, 5e class, MMC		
GPH-1GS/m	Hermetic socket with ground schuko, IP-44	GPT-1G/m	Single telephone socket	GPK-2G/K/m	Twin computer socket, 5e class, MMC		
				GPE-1G/m	Single equipotential socket (on request)		
				GPE-2G/m	Twin equipotential socket (on request)		

## Quick and easy installation of wiring accessories



Safety shutters protect children from electric shock by preventing the insertion of metal objects into the socket apertures.



The enclosed design of the self-returning mounting claws protects the installer's fingers from accidental injury.

### SOCKETS




Side wire entry allows for a visual quality check of the terminal connections even after the socket module has been fully installed in the wall box.




Alignment spacers located on the bridges ensure perfect spacing and precise positioning of modules in multi-gang boxes.



### SWITCHES



Alignment spacers located on the bridges ensure perfect spacing and precise positioning of modules in multi-gang boxes.



Side wire entry allows for quality control of the terminal connections even after the switch module has been fully installed in the mounting box.


A two-color (silver and gold) screw designation system makes it easy to identify the power supply terminal.



The replaceable illumination module allows you to choose the color of the emitted light, ensuring a perfect match with your interior design.



Quick assembly and disassembly of the frame on the switch module, thanks to the use of a quick-release mounting cover.



The As Antibacterial series offers products with **antimicrobial protection**, essential for both public utility spaces and residential use.

# AS

antibacterial

The enclosures of As Antibacterial products are manufactured using biocidal polymer additives containing silver nanoparticles. This technology ensures effective bactericidal protection in accordance with the ISO 22196 standard. Its efficacy has been confirmed by independent laboratory testing.

# AS Antibacterial

FLUSH-MOUNTED SERIES | \* series available on request

00 white

## Flush mounting switches

Screw terminals  
Rated voltage: 250V  
Rated current: 10AX  
Protection rating: IP-20



ŁP-1GA/m/00  
Single pole switch 1300



ŁP-2GA/m/00  
All-or-part switch, chandelier 1301  
ŁP-17GA/m/00  
Double short-circuiting switch 1363



ŁP-9GA/m/00  
Two-way switch + single pole switch 1308  
ŁP-10GA/m/00  
Double two-way switch 1309  
ŁP-19GA/m/00  
Double intermediate switch  
/available only on IP 20 version/ 2093



ŁP-3GA/m/00  
Two-way switch 1302



ŁP-4GA/m/00  
Intermediate switch 1303



ŁP-5GA/m/00  
Short-circuiting switch „light” 1304



ŁP-6GA/m/00  
Short-circuiting switch „bell” 1304



ŁP-7GA/m/00  
Venetian blind switch 1305



ŁP-7GAB/m/00  
Venetian blind switch  
with mechanical lock 2010



ŁP-11GA/m/00  
Double pole switch 1306



ŁP-21GA/m/00  
Short-circuiting switch 1304

## Accessories for switches IP-44

There is a possibility to mount switches with protection rating IP-20 as switches with IP-44, to do that, must be bought sealing set presented below.



ZU-1G  
Sealing set for switches IP-44 1352

Screwless terminals



ŁP-13GA/m/00  
Triple switch 1310



ŁP-24GA/m/00  
Short-circuiting triple switch 2086

\* on request

AVAILABLE COLOURS

## Flush mounting switches with built-in light

Screw terminals  
Rated voltage: 250V  
Rated current: 10AX  
Protection rating: IP-20



ŁP-1GAS/m/00  
Single pole switch 1300



ŁP-2GAS/m/00  
All-or-part switch, chandelier 1301  
ŁP-19GAS/m/00  
Double intermediate switch  
/available only on IP 20 version/ 2093



ŁP-3GAS/m/00  
Two-way switch 1302



ŁP-4GAS/m/00  
Intermediate switch 1303



ŁP-5GAS/m/00  
Short-circuiting switch „light” 1304



ŁP-6GAS/m/00  
Short-circuiting switch „bell” 1304



ŁP-7GAS/m/00  
Venetian blind switch 1305



ŁP-7GABS/m/00  
Venetian blind switch  
with mechanical lock 2010



ŁP-11GAS/m/00  
Double pole switch 1306



ŁP-12GAS/m/00  
Control switch 1307



ŁP-21GAS/m/00  
Short-circuiting switch 1304

## Hotel switch

Screw terminals  
Current supply: 230~ 50Hz  
Protection rating: IP-20  
Rated current: 16A  
Time of delay: 3s

Switch works with a standard card with dimensions 86 x 54 x 0.8 mm

Screwless terminals



ŁP-13GAS/m/00  
Triple switch 1310



ŁP-15GAS/m/00  
Hotel switch 1342

Accessories for switches with built-in light are on page 220.

\* on request

# AS Antibacterial

FLUSH-MOUNTED SERIES | \*series available on request

00 white

## Dimmers

Screw terminals  
Current supply: 230V~50Hz  
Protection rating: IP-20



LP-8GA/m/00 1311  
Push-turn dimmer adapted to incandescent and halogen loading, load 40-400W



LP-8GAL2/m/00 2007  
Universal dimmer load: GLS - 10-250W, CFL - 5-75W LED - 0-100W functions: electronic switch, "time to bed"

## Temperature regulators

Screw terminals  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W  
- inductive 750W  
Protection rating: IP-20



RTP-1GAN/m/00 1388  
Temperature regulator with aerial sensor



RTP-1GA/m/00 1344  
Temperature regulator with underfloor sensor

## Electronic movement detector

Screw terminals  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W,  
- fluorescent 750W  
- inductive 750W  
Protection rating: IP-20  
Way of adjustment the time of transmitter's switching on: 3s. - 5min.  
Angle of movement detection's field: 136°  
Field of activity: 7m  
Works with LED light



LP-16GA/m/00 1343  
Electronic movement detector

AVAILABLE COLOURS

## Equipotential socket



GPE-1GA/m/00 1382  
Single equipotential socket



GPE-2GA/m/00 1383  
Twin equipotential socket



WKE 1571  
Plug into the equipotential socket

## Triple socket EURO

Screw terminals  
Rated voltage: 250V  
Rated current: 2,5A  
Protection rating: IP-20



GP-3GA/m/00 1325  
Triple socket EURO

## Single socket with ground with USB charger

Screwless terminals  
Rated voltage:  
- input: 230V~50Hz  
- output: 5VDC  
Rated current: 2,1A  
Protection rating: IP-20  
Doesn't work with surface mounting wall frames



GP-1GAZPUSB/m/00 2067  
Single socket with ground, with shutters, with USB charger

## Single socket with ground, with USB A+C charger

Screwless terminals  
Rated voltage  
- input: 230V~ 50Hz (max 0,3A)  
- output A or C: 5VDC/ 3A; 9VDC/ 2,22A; 12VDC/ 1,67A  
- output A+C: 5VDC/ 3,4A max 20W  
Protection rating IP-20  
Doesn't work with surface mounting wall frames



GP-1GAZPUSBAC/m/00 2065  
Single socket with ground, with shutters, with USB A+C charger

## Flush mounting socket outlets

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-20



GP-1GA/m/00 1313  
Single socket



GP-1GAP/m/00 1313  
Single socket with shutters



GP-1GAZ/m/00 1314  
Single socket with ground



GP-1GAZP/m/00 1314  
Single socket with ground, with shutters



GP-1GAS/m/00 1317  
Single socket with ground schuko



GP-1GASP/m/00 1317  
Single socket with ground schuko, with shutters



GP-1GAZD/m/00 1315  
Single socket with ground DATA



GP-1GAZDP/m/00 1315  
Single socket with ground DATA, with shutters



GP-1GAZK/m/00 1316  
Single socket with ground DATA, with access key



GP-1GAZD/m/12 1315  
Single socket with ground DATA



GP-1GAZDP/m/12 1315  
Single socket with ground DATA, with shutters



GP-1GAZK/m/12 1316  
Single socket with ground DATA, with access key

\* on request

\* on request

# AS Antibacterial

FLUSH-MOUNTED SERIES | \*series available on request

00 white

## Flush mounting socket outlets

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-44



GPH-1GAZ/m/00/w  
Hermetic socket  
with ground 1318



GPH-1GAZP/m/00/w  
Hermetic socket with ground,  
with shutters 1318



GPH-1GAS/m/00/w  
Hermetic socket  
with ground schuko 1319



GPH-1GASP/m/00/w  
Hermetic socket with ground schuko,  
with shutters 1319



GPH-1GAZD/m/00/w  
Hermetic socket  
with ground DATA 1318



GPH-1GAZDP/m/00/w  
Hermetic socket with ground DATA  
with shutters 1318



GPH-1GAZK/m/00/w  
Hermetic socket with ground DATA,  
with access key 2025

Antibacterial hermetic sockets are offered only in white colour, with white lids.

\* on request

AVAILABLE COLOURS

## Flush mounting socket outlets

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-20



GP-2GAR/m/00  
Twin socket 1322



GP-2GARP/m/00  
Twin socket with shutters 1322



GP-2GARZ/m/00  
Twin socket with ground 1323



GP-2GARZP/m/00  
Twin socket with ground,  
with shutters 1323



GP-2GA/00  
Twin socket 1320



GP-2GAZ/00  
Twin socket with ground 1321



GP-2GAS/00  
Twin socket with ground schuko 1324



GP-2GAC/00  
Twin socket with ground,  
without changing phase 1326

## Flush mounting socket outlets (sold entire)

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-20



GP-2GAP/00  
Twin socket with shutters 1320



GP-2GAZP/00  
Twin socket with ground,  
with shutters 1321



GP-2GASP/00  
Twin socket with ground schuko,  
with shutters 1324

\* on request

## Antenna subscribers

Screw terminals



GPA-1GAF/m/00 1332  
Single, terminal antenna RTV subscriber, type F



GPA-2GAF/m/00 1375  
Twin, terminal antenna RTV subscriber, type F



GPA-GAK/m/00 1328  
Terminal antenna RTV subscriber, attenuation coefficient 2,5-3 dB

GPA-10GAPZ/m/00 1327  
Through antenna RTV subscriber, attenuation coefficient 10 dB



GPA-10GAP/m/00 1327  
Through antenna RTV subscriber, attenuation coefficient 10 dB

GPA-14GAP/m/00 1327  
Through antenna RTV subscriber, attenuation coefficient 14 dB

GPA-16GAP/m/00 1327  
Through antenna RTV subscriber, attenuation coefficient 16 dB



GPA-GAS/m/00 1329  
Terminal antenna RTV-SAT subscriber, attenuation coefficient 1,5-2 dB

GPA-GASP/m/00 1330  
Through antenna RTV-SAT subscriber, attenuation coefficient 1,2 dB



GPA-GA2S/m/00 1331  
Terminal antenna RTV-SAT subscriber with two outlets SAT



GPA-GAD/m/00 1384  
Terminal antenna RTV-DATA subscriber

## Telephone sockets

Screw terminals



GPT-1GA/m/00 1333  
Single telephone socket



GPT-2GAN/m/00 1334  
Twin telephone socket, independent

GPT-2GAR/m/00 1334  
Twin telephone socket, parallel

## Adapter

It allows to use of Ospel 45 system products in the As Antibacterial series.



AP45-1GA/m/00 2058  
Adapter

AVAILABLE COLOURS

## Loudspeaker sockets

Connection of lines ability 0,75 mm<sup>2</sup>



GG-1GA/m/00 1340  
Single loudspeaker socket connection of lines ability 0,75 mm<sup>2</sup>



GG-2GA/m/00 1341  
Twin loudspeaker socket connection of lines ability 0,75 mm<sup>2</sup>



GGN-1GA/m/00 1387  
Single loudspeaker socket connection of lines ability 6 mm<sup>2</sup>

## Computer sockets

Connection IDC



GPK-1GA/K/m/00 1335  
Single computer socket, 5e class, MMC



GPK-2GA/K/m/00 1336  
Twin computer socket, 5e class, MMC

## Sockets covers Keystone type



GPK-1GAS/p/00 1366  
Single computer socket cover, slant



GPK-2GAS/p/00 1367  
Twin computer socket cover, slant



GPK-1GA/p/00 1394  
Single computer socket cover, flat



GPK-2GA/p/00 1395  
Twin computer socket cover, flat



GPK-1GAP/p/00 2012  
Single computer socket cover, with shutter, flat



GPK-2GAP/p/00 2013  
Twin computer socket cover, with shutter, flat

Modules which can be mounted in these socket covers are on page 167.

# AS Antibacterial

FLUSH-MOUNTED SERIES | \* series available on request

00 white

## Blank cover



Z-1GA/m/00  
Blank cover 1362

## Cable terminal

Screw terminals, 5x4mm<sup>2</sup>  
Protection rating: IP-20  
Flush-mounted into ø60 boxes



GPPK-1GA/m/00  
Cable terminal 1140

## Wall frames



PNP-1GA/00  
Single wall frame 2161

PNP-2GA/00  
Twin wall frame 2162

PNP-3GA/00  
Threefold wall frame 2163

PNP-4GA/00  
Fourfold wall frame 2164

PNP-5GA/00  
Fivefold wall frame 2165



## AVAILABLE COLOURS

## Surrounds Standard



R-1GA/00  
Single surround 1347

R-2GA/00  
Twin surround 1348

R-3GA/00  
Threefold surround 1349

R-4GA/00  
Fourfold surround 1350

R-5GA/00  
Fivefold surround 1351



## Surrounds Standard for sets IP-44



RH-1GA/00  
Single surround 1347

RH-2GA/00  
Twin surround 1348

RH-3GA/00  
Threefold surround 1349

RH-4GA/00  
Fourfold surround 1350

RH-5GA/00  
Fivefold surround 1351



# AS Antibacterial

FLUSH-MOUNTED SERIES | \*series available on request

00 white

## Available colours



White - nr 00

## Example order



To order single pole switch with built-in light must be ordered

**ŁP-1GAS/m/00**

**R-1GA/00**



To order hermetic socket with ground DATA, with access key must be ordered:

**GPH-1GAZK/m/00/w**

**RH-1GA/00**

\* on request

## AVAILABLE COLOURS

## Designations

Products of AS Antibacterial series (\*excluding a few twin sockets) in all colours are sold without external surround. Below are written designations which must be used to place the order. The designations are valid for white products only.

ŁP-...GA/m	Switches - in the place marked by dots, write the right number of switch	GP-2GAC	Twin socket without changing phase*
ŁP-...GAS/m	Switches with built-in light - in the place marked by dots, write the right number of switch	GP-3GA/m	Triple socket EURO
ŁP-8GA/m	Push-turn dimmer adapted to incandescent and halogen loading	GPA-1GAF/m	Single, terminal antenna RTV subscriber, type F
ŁP-8GAL2/m	Universal dimmer	GPA-2GAF/m	Twin terminal antenna RTV subscriber, type F
ŁP-15GAS/m	Hotel switch	GPA-10GAP/m	Through antenna RTV subscriber ZAP-10
ŁP-16GA/m	Electronic movement detector	GPA-14GAP/m	Through antenna RTV subscriber ZAP-14
GP-1GA/m	Single socket	GPA-16GAP/m	Through antenna RTV subscriber ZAP-16
GP-1GAP/m	Single socket with shutters	GPA-10GAPZ/m	Through antenna RTV subscriber
GP-1GAZ/m	Single socket with ground	GPA-GAK/m	Terminal antenna RTV subscriber ZAR-1
GP-1GAZP/m	Single socket with ground, with shutters	GPA-GAS/m	Terminal antenna RTV-SAT subscriber
GP-1GAS/m	Single socket with ground schuko	GPA-GASP/m	Through antenna RTV-SAT subscriber
GP-1GASP/m	Single socket with ground schuko, with shutters	GPA-GA2S/m	Terminal antenna RTV-SAT subscriber, with two outlets SAT
GP-1GAZD/m	Single socket with ground DATA	GPA-GAD/m	Terminal antenna RTV-DATA subscriber
GP-1GAZDP/m	Single socket with ground DATA, with shutters	GG-1GA/m	Single loudspeaker socket
GP-1GAZK/m	Single socket with ground DATA, with access key	GG-2GA/m	Twin loudspeaker socket
GPH-1GAZ/m	Hermetic socket with ground IP-44	GGN-1GA/m	Single loudspeaker socket
GPH-1GAZP/m	Hermetic socket with ground, IP-44, with shutters	GPT-1GA/m	Single telephone socket
GPH-1GAS/m	Hermetic socket with ground schuko, IP-44	GPT-2GAN/m	Twin telephone socket, independent
GPH-1GASP/m	Hermetic socket with ground schuko, IP-44, with shutters	GPT-2GAR/m	Twin telephone socket, parallel
GPH-1GAZD/m	Hermetic socket with ground DATA, IP-44	GPK-1GA/K/m	Single computer socket, 5e class, MMC
GPH-1GAZDP/m	Hermetic socket with ground DATA with shutters	GPK-2GA/K/m	Twin computer socket 5e class, MMC
GPH-1GAZK/m	Hermetic socket with ground DATA, IP-44, with access key	GPK-1GA/p	Single computer socket cover, flat
GP-1GAZPUS-B/m	Single socket with ground with USB charger	GPK-2GA/p	Twin computer socket cover, flat
GP-2GAR/m	Twin socket	GPK-1GAS/p	Single socket cover, slant
GP-2GARP/m	Twin socket with shutters	GPK-2GAS/p	Twin socket cover, slant
GP-2GARZ/m	Twin socket with ground	GPK-1GAP/p	Single computer socket cover, with shutter, flat
GP-2GARZP/m	Twin socket with ground, with shutters	GPK-2GAP/p	Twin computer socket cover, with shutter, flat
GP-2GA	Twin socket *	GPE-1GA/m	Single equipotential socket
GP-2GAP	Twin socket with shutters*	GPE-2GA/m	Twin equipotential socket
GP-2GAZ	Twin socket with ground *	RTP-1GA/m	Temperature regulator with underfloor sensor
GP-2GAZP	Twin socket with ground, with shutters*	RTP-1GAN/m	Temperature regulator with aerial sensor
GP-2GAS	Twin socket with ground schuko *	Z-1GA/m	Blank cover
GP-2GASP	Twin socket with ground schuko, with shutters*	GPPK-1GA/m	Cable terminal
		AP45-1GA/m	Adapter

**A universal choice**  
for those who value  
classic solutions.



# Karo

Products where the bold shapes of the mechanisms contrast with the subtle lines of the frames. A balanced choice for those who want their wiring accessories to serve as a discreet wall ornament.



## AVAILABLE COLOURS



White – nr 00



## Flush mounting switches

Screw terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-20



ŁP-1S/m/00  
Single pole switch 1500



ŁP-2S/m/00  
All-or-part switch, chandelier 1501

ŁP-17S/m/00  
Double short-circuiting switch 1510



ŁP-9S/m/00  
Two-way switch + single pole switch 1508

ŁP-10S/m/00  
Double two-way switch 1509



ŁP-3S/m/00  
Two-way switch 1502



ŁP-4S/m/00  
Intermediate switch 1503



ŁP-5S/m/00  
Short-circuiting switch „light” 1504



ŁP-6S/m/00  
Short-circuiting switch „bell” 1504



ŁP-7S/m/00  
Venetian blind switch 1505



ŁP-7SB/m/00  
Venetian blind switch with mechanical lock 1575



ŁP-11S/m/00  
Double pole switch 1506



ŁP-13S/m/00  
Triple switch 1511

## Accessories for switches IP-44

There is a possibility to mount switches with protection rating IP-20 as switches with IP-44, to do that, must be bought sealing set presented below.



ZU-1R  
Sealing set for switches IP-44 1118

## Flush mounting switches with built-in light

Screw terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-20



ŁP-1SS/m/00  
Single pole switch 1500



ŁP-2SS/m/00  
All-or-part switch, chandelier 1501



ŁP-3SS/m/00  
Two-way switch 1502



ŁP-4SS/m/00  
Intermediate switch 1503



ŁP-5SS/m/00  
Short-circuiting switch „light” 1504



ŁP-6SS/m/00  
Short-circuiting switch „bell” 1504



ŁP-7SS/m/00  
Venetian blind switch 1505



ŁP-7SBS/m/00  
Venetian blind switch with mechanical lock 1575



ŁP-11SS/m/00  
Double pole switch 1506



ŁP-12SS/m/00  
Control switch 1507



ŁP-13SS/m/00  
Triple switch 1511

## Hotel switch

Screw terminals  
 Current supply: 230~ 50Hz  
 Protection rating: IP-20  
 Rated current: 16A  
 Time of delay: 3s

Switch works with a standard card with dimensions 86 x 54 x 0.8 mm



ŁP-15SS/m/00  
Hotel switch 1546

Accessories for switches with built-in light are on page 220.

## Dimmers

Screw terminals  
Current supply: 230V~50Hz  
Protection rating: IP-20



ŁP-8S/m/00 1512  
Push-turn dimmer adapted to incandescent and halogen loading, load 40-400W



ŁP-8SL2/m/00 1574  
Universal dimmer load: GLS - 10-250W, CFL - 5-75W, LED - 0-100W functions: electronic switch, "time to bed"

## Temperature regulators

Screw terminals  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W  
- inductive 750W  
Protection rating: IP-20



RTP-1SN/m/00 1548  
Temperature regulator with aerial sensor



RTP-1S/m/00\* 1548  
Temperature regulator with underfloor sensor

## Equipotential socket



GPE-1S/m/00\* 1567  
Single equipotential socket



GPE-2S/m/00\* 1568  
Twin equipotential socket



WKE\* 1571  
Plug into the equipotential socket

## Flush mounting socket outlets

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-20



GP-1S/m/00 1514  
Single socket



GP-1SZ/m/00 1515  
Single socket with ground



GP-1SS/m/00 1518  
Single socket with ground schuko



GPH-1SZ/m/00/d 1519  
Hermetic socket with ground, IP-44



GPH-1SS/m/00/d 1520  
Hermetic socket with ground schuko, IP-44



GP-1SP/m/00 1514  
Single socket with shutters



GP-1SZP/m/00 1515  
Single socket with ground, with shutters



GP-1SSP/m/00 1518  
Single socket with ground schuko, with shutters



GPH-1SZP/m/00/d 1519  
Hermetic socket with ground, with shutters



GPH-1SSP/m/00/d 1520  
Hermetic socket with ground schuko, IP-44, with shutters



GP-1SZD/m/00 1516  
Single socket with ground DATA



GP-1SZDP/m/00 1516  
Single socket with ground DATA, with shutters



GP-1SZK/m/00 1517  
Single socket with ground DATA, with access key

## Electronic movement detector

Screw terminals  
Rated voltage: 230V  
Rated current:  
- incandescent 3200W,  
- fluorescent 750W  
- inductive 750W  
Protection rating: IP-20  
Way of adjustment the time of transmitter's switching on: 3s. - 5min.  
Angle of movement detection's field: 136°  
Field of activity: 7m  
Works with LED light



ŁP-16S/m/00 1547  
Electronic movement detector

## Triple socket EURO

Screw terminals  
Rated voltage: 250V  
Rated current: 2,5A  
Protection rating: IP-20



GP-3S/m/00 1526  
Triple socket EURO

## Single socket with ground with USB charger

Screwless terminals  
Rated voltage:  
- input: 230V~50Hz  
- output: 5VDC  
Rated current: 2,1A  
Protection rating: IP-20  
Doesn't work with surface mounting wall frames



GP-1SZPUSB/m/00 2068  
Single socket with ground, with shutters, with USB charger

\* on request

Hermetic sockets in white colour are also offered with lid in white colour. After right product's code write: .../00/w.

## Flush mounting socket outlets

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-20



GP-2SR/m/00 1523  
Twin socket



GP-2SRP/m/00 1523  
Twin socket with shutters



GP-2SRZ/m/00 1524  
Twin socket with ground



GP-2SRZP/m/00 1524  
Twin socket with ground, with shutters

## Flush mounting socket outlets (sold entire)

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-20



GP-2S/00 1521  
Twin socket



GP-2SZ/00 1522  
Twin socket with ground



GP-2SS/00 1525  
Twin socket with ground schuko



GP-2SC/00 1527  
Twin socket with ground, without changing phase



GP-2SP/00 1521  
Twin socket with shutters



GP-2SZP/00 1522  
Twin socket with ground, with shutters



GP-2SSP/00 1525  
Twin socket with ground schuko, with shutters

## AVAILABLE COLOURS

## Antenna subscribers

Screw terminals



GPA-1SF/m/00 1533  
Single, terminal antenna RTV subscriber, type F



GPA-S2S/m/00 1532  
Terminal antenna RTV-SAT subscriber with two outlets SAT



GPA-2SF/m/00 1534  
Twin, terminal antenna RTV subscriber, type F



GPA-SD/m/00\* 1569  
Terminal antenna RTV-DATA subscriber



GPA-SS/m/00 1530  
Terminal antenna RTV-SAT subscriber, attenuation coefficient 1,5-2 dB

GPA-SSP/m/00\* 1531  
Through antenna RTV-SAT subscriber, attenuation coefficient 1,2 dB



GPA-SK/m/00 1529  
Terminal antenna RTV subscriber, attenuation coefficient 2,5-3 dB

GPA-10SP/m/00\* 1528  
Through antenna RTV subscriber, attenuation coefficient 10 dB

GPA-14SP/m/00\* 1528  
Through antenna RTV subscriber, attenuation coefficient 14 dB

GPA-16SP/m/00\* 1528  
Through antenna RTV subscriber, attenuation coefficient 16 dB

GPA-10SPZ/m/00\* 1528  
Through antenna RTV subscriber

## Telephone sockets

Screw terminals



GPT-1S/m/00 1535  
Single telephone socket



GPT-2SN/m/00 1536  
Twin telephone socket, independent



GPT-2SR/m/00 1536  
Twin telephone socket, parallel

## Adapter

It allows to use of Ospel 45 system products in the Karo series.



AP45-1S/m/00 1577  
Adapter

\* on request

## Loudspeaker sockets



GG-1S/m/00 1544  
Single loudspeaker socket  
connection of lines ability 0,75 mm<sup>2</sup>



GG-2S/m/00 1545  
Twin loudspeaker socket  
connection of lines ability 0,75 mm<sup>2</sup>



GGN-1S/m/00 1573  
Single loudspeaker socket  
connection of lines ability 6 mm<sup>2</sup>

## Computer sockets

Connection IDC



GPK-1S/K/m/00 1537  
Single computer socket,  
5e class, MMC



GPK-2S/K/m/00 1538  
Twin computer socket,  
5e class, MMC



GPKA-S/K/m/00 1570  
Computer socket, 5e class, MMC  
+ terminal antenna RTV subscriber,  
type F

## Sockets covers Keystone type



GPK-1S/p/00 1537  
Single computer socket cover,  
flat



GPK-2S/p/00 1538  
Twin computer socket cover,  
flat

## Cable terminal

Screw terminals, 5x4mm<sup>2</sup>  
Protection rating: IP-20  
Flush-mounted into ø60 boxes



GPPK-1S/m/00 1572  
Cable terminal

## Blank cover



Z-1S/m/00 1565  
Blank cover

Modules which can be mounted in these  
socket covers are on page 167.

## AVAILABLE COLOURS

### Surrounds Standard



R-1S/00 Single surround	1549	
R-2S/00 Twin surround	1550	
R-3S/00 Threefold surround	1551	
R-4S/00 Fourfold surround	1552	
R-5S/00 Fivefold surround	1553	

### Surrounds Standard for sets IP-44



RH-1S/00 Single surround	1549	
RH-2S/00 Twin surround	1550	
RH-3S/00 Threefold surround	1551	
RH-4S/00 Fourfold surround	1552	
RH-5S/00 Fivefold surround	1553	

## Example order


To order single pole switch in white colour must be ordered:

ŁP-1S/m/00  
R-1S/00



To order USB charger in white colour must be ordered:

GK-2USB/00  
AP45-1S/m/00  
R-1S/00



## AVAILABLE COLOURS

## Designations

Products of KARO series (\*excluding a few twin sockets) in all colours are sold without external surround. Below are written designations which must be used to place the order.


After right product's code write the right number of colour: white – number 00.

ŁP-.....S/m	Switches - in the place marked by dots, write the right number of switch	GP-3S/m	Triple socket EURO
ŁP-.....SS/m	Switches with built-in light - in the place marked by dots, write the right number of switch	GPT-1S/m	Single telephone socket
ŁP-8S/m	Push-turn dimmer adapted to incandescent and halogen loading	GPT-2SN/m	Twin telephone socket, independent
ŁP-8SL2/m	Universal dimmer	GPT-2SR/m	Twin telephone socket, parallel
ŁP-15SS/m	Hotel switch	GPA-1SF/m	Single, terminal antenna RTV subscriber, type F
ŁP-16S/m	Electronic movement detector	GPA-2SF/m	Twin, terminal antenna RTV subscriber, type F
GP-1S/m	Single socket	GPA-SK/m	Terminal antenna RTV subscriber ZAR-1
GP-1SP/m	Single socket with shutters	GPA-10SPZ/m	Through antenna RTV subscriber (on request)
GP-1SZ/m	Single socket with ground	GPA-10SP/m	Through antenna RTV subscriber ZAP-10 (on request)
GP-1SZP/m	Single socket with ground, with shutters	GPA-14SP/m	Through antenna RTV subscriber ZAP-14 (on request)
GP-1SS/m	Single socket with ground schuko	GPA-16SP/m	Through antenna RTV subscriber ZAP-16 (on request)
GP-1SSP/m	Single socket with ground schuko, with shutters	GPA-SS/m	Terminal antenna RTV-SAT subscriber
GP-1SZD/m	Single socket with ground DATA	GPA-SSP/m	Through antenna RTV-SAT subscriber (on request)
GP-1SZDP/m	Single socket with ground DATA, with shutters	GPA-S2S/m	Terminal antenna RTV-SAT subscriber, with two outlets SAT
GP-1SZK/m	Single socket with ground DATA, with access key	GPA-SD/m	Terminal antenna RTV-DATA subscriber (on request)
GPH-1SZ/m	Hermetic socket with ground IP-44	GG-1S/m	Single loudspeaker socket
GPH-1SZP/m	Hermetic socket with ground IP-44, with shutters	GG-2S/m	Twin loudspeaker socket
GPH-1SS/m	Hermetic socket with ground schuko, IP-44	GGN-1S/m	Single loudspeaker socket
GPH-1SSP/m	Hermetic socket with ground schuko IP-44, with shutters	GPK-1S/K/m	Single computer socket, 5e class, MMC
GP-1SZPUSB/m	Single socket with ground, with USB charger, with shutters	GPK-2S/K/m	Twin computer socket, 5e class, MMC
GP-2SR/m	Twin socket	GPK-1S/p	Single computer socket cover, flat
GP-2SRP/m	Twin socket with shutters	GPK-2S/p	Twin computer socket cover, flat
GP-2SRZ/m	Twin socket with ground	GPKA-S/K/m	Computer socket + terminal antenna RTV subscriber, type F
GP-2SRZP/m	Twin socket with ground, with shutters	GPE-1S/m	Single equipotential socket (on request)
GP-2S	Twin socket*	GPE-2S/m	Twin equipotential socket (on request)
GP-2SP	Twin socket with shutters*	RTP-1S/m	Temperature regulator with underfloor sensor (on request)
GP-2SZ	Twin socket with ground*	RTP-1SN/m	Temperature regulator with aerial sensor
GP-2SZP	Twin socket with ground, with shutters*	Z-1S/m	Blank cover
GP-2SS	Twin socket with ground schuko*	GPPK-1S/m	Cable terminal
GP-2SSP	Twin socket with ground schuko, with shutters*	AP45-1S/m	Adapter

## Quick and easy installation of wiring accessories



Safety shutters protect children from electric shock by preventing the insertion of metal objects into the socket apertures.



The enclosed design of the self-returning mounting claws protects the installer's fingers from accidental injury.



Side wire entry allows for a visual quality check of the terminal connections even after the socket module has been fully installed in the wall box.



Alignment spacers located on the bridges ensure perfect spacing and precise positioning of modules in multi-gang boxes.

### SOCKETS



A universal multi-gang frame system that allows for both vertical and horizontal layouts.



### SWITCHES



Quick assembly and disassembly of the frame on the switch module, thanks to the use of a quick-release mounting cover.



Side wire entry allows for quality control of the terminal connections even after the switch module has been fully installed in the mounting box.

A two-color (silver and gold) screw designation system makes it easy to identify the power supply terminal.



The replaceable illumination module allows you to choose the color of the emitted light, ensuring a perfect match with your interior design.



Self-returning mounting claws, equipped with stainless steel spring elements, significantly facilitate the installation of the switch module in the wall box.



**Socket covers** dedicated to these modules are available in the series: Szafir, Aria, Sonata, Impresja, As, Karo and Ospel 45.

# Keystone

The universal solution for OSPEL equipment, so that there is a possibility to create sets of data communications adapted to your needs.

# Modules OSPEL

KEYSTONE TYPE

## Computer socket modules

### 5e class, unshielded – UTP



MGK-K5  
Module RJ45, MMC



MGK-M5  
Module RJ45, MOLEX



MGK-F5  
Module RJ45, FOREX



MGK-K5E\*  
Module RJ45, MMC

### 6 class, unshielded – UTP



MGK-K6  
Module RJ45, MMC



MGK-T6\*  
Module RJ45, FMT



MGK-F6  
Module RJ45, FOREX



MGK-M6  
Module RJ45, MOLEX

### 6 class, shielded – STP



MGK-K6E\*  
Module RJ45, MMC



MGK-K6AE\*  
Module RJ45, MMC



MGK-T6AE\*  
Module RJ45, FMT



MGK-M6AE\*  
Module RJ45, MOLEX

### 6a class, shielded – STP

## HDMI module



MG-HDMI\*\*  
Module HDMI angular  
  
MG-HDMIP  
Module HDMI straight

## USB module



MG-USB  
Module USB

## Antenna subscriber module



MGA-1F  
Module type F

Modules HDMI and USB work only with flat socket covers Keystone type.

Presented modules have a Keystone attachment

\* doesn't work with surface mounting wall frames

\*\* for boxes Ø 60mm, depth minimum 60mm, only as single

## Telephone socket module



MGT-K  
Module RJ12, MMC



MGT-F  
Module RJ12, FOREX

## Loudspeaker socket modules



MG-MJ  
Module mini stereo Jack



MG-RCA/R  
Module RCA, red



MG-RCA/W  
Module RCA, white

## Modules



MGS-1SC  
Fiber optic adapter, type SC



GKV-1/p/00  
Cover of module VGA



MG-VGA  
Module VGA

## Blank covers



ZOK-1/25  
Blank cover of sockets  
covers Keystone type



ZOK-1/00  
Blank cover of sockets  
covers Keystone type



# Kier

A bold, innovative shape combined with intriguing backlighting patterns is sure to be appreciated by customers. Kier represents the premium quality you can always rely on when choosing products from the Polish manufacturer OSPEL.



A full range of **modern, compact products** allows for the creation of interiors equipped with every possible convenience.

## AVAILABLE COLOURS



White – nr 00




Satin light – nr 45



Brown metallic – nr 52






## Flush mounting switches

Screw terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-20




ŁP-1W/00  
Single pole switch 1700



ŁP-2W/00  
All-or-part switch, chandelier 1701

ŁP-17W/00  
Double short-circuiting switch 1710



ŁP-9W/00  
Two-way + single pole switch 1708

ŁP-10W/00  
Double two-way switch 1709



ŁP-3W/00  
Two-way switch 1702




ŁP-4W/00  
Intermediate switch 1703



ŁP-5W/00  
Short-circuiting switch „light” 1704



ŁP-6W/00  
Short-circuiting switch „bell” 1704



ŁP-7W/00  
Venetian blind switch 1705



ŁP-7WB/00  
Venetian blind switch with mechanical lock 1750



ŁP-11W/00  
Double pole switch 1706

## Dimmers

Screw terminals  
 Current supply: 230V ~50Hz  
 Protection rating: IP-20



ŁP-8W/00  
Push-turn dimmer adapted to incandescent and halogen loading, load 40-400W 1711



ŁP-8WL2/00  
Universal dimmer load: GLS - 10-250W, CFL - 5-75W, LED - 0-100W functions: electronic switch, “time to bed” 1749

## Flush mounting switches with built-in light

Screw terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-20



ŁP-1WS/00  
Single pole switch 1700



ŁP-2WS/00  
All-or-part switch, chandelier 1701



ŁP-3WS/00  
Two-way switch 1702




ŁP-4WS/00  
Intermediate switch 1703



ŁP-5WS/00  
Short-circuiting switch „light” 1704



ŁP-6WS/00  
Short-circuiting switch „bell” 1704



ŁP-7WS/00  
Venetian blind switch 1705



ŁP-7WBS/00  
Venetian blind switch with mechanical lock 1750



ŁP-11WS/00  
Double pole switch 1706



ŁP-12WS/00  
Control switch 1707

Accessories for switches with built-in light are on page 220.

## Accessories for switches IP-44




ZU-1W  
Sealing set for switches IP-44 1738

## Wall frame



PNP-W/00  
Wall frame 1737

There is a possibility to mount switches with protection rating IP-20 as switches with IP-44, to do that must be bought accessories above.



## Flush mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-1W/00  
Single socket 1712



GP-1WP/00  
Single socket with shutters 1712



GP-1WZ/00  
Single socket with ground 1713



GP-1WZP/00  
Single socket with ground, with shutters 1713



GP-1WS/00  
Single socket with ground schuko 1716



GP-1WSP/00  
Single socket with ground schuko, with shutters 1716



GP-1WZD/22\*  
Single socket with ground DATA 1714



GP-1WZDP/22\*  
Single socket with ground DATA, with shutters 1714



GP-1WZK/22\*  
Single socket with ground DATA, with access key 1715



GPH-1WZ/00/d  
Hermetic socket with ground, IP-44 1717



GPH-1WZP/00/d  
Hermetic socket with ground, IP-44, with shutters 1717



GPH-1WS/00/d  
Hermetic socket with ground schuko, IP-44 1718




GPH-1WSP/00/d  
Hermetic socket with ground schuko, IP-44, with shutters 1718

Hermetic sockets are also offered with lids in product's colour. After right product's code write: .../00/w for products in white colour or .../01/w for products in beige colour.

\* on request

## Flush mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-2W/00  
Twin socket 1719



GP-2WZ/00  
Twin socket with ground 1720



GP-2WZP/00  
Twin socket with ground, with shutters 1720




GP-2WS/00  
Twin socket with ground schuko 1721



GP-2WSP/00  
Twin socket with ground schuko, with shutters 1721



GP-2WC/00  
Twin socket with ground, without changing phase 1722



## Telephone sockets

Screw terminals



GPT-1W/00 1730  
Single telephone socket



GPT-2WN/00 1731  
Twin telephone socket, independent



GPT-2WR/00 1731  
Twin telephone socket, parallel

## Computer sockets

Connection IDC



GPK-1W/K/00 1732  
Single computer socket, kat. 5e

GPK-1W/K6/00 1734  
Single computer socket, kat. 6



GPK-2W/K/00 1733  
Twin computer socket, kat. 5e

GPK-2W/K6/00 1735  
Twin computer socket, kat. 6



GPKT-W/K/00 1736  
Conjunct computer and telephone socket

## Antenna subscribers

Screw terminals



GPA-10WP/00\* 1723  
Through antenna RTV subscriber 10 dB

GPA-14WP/00\* 1723  
Through antenna RTV subscriber 14 dB

GPA-16WP/00\* 1723  
Through antenna RTV subscriber 16 dB

GPA-10WPZ/00\* 1723  
Through antenna RTV subscriber

GPA-WK/00 1724  
Terminal antenna RTV subscriber



GPA-1WF/00 1728  
Single, terminal antenna RTV subscriber, type F



GPA-2WF/00 1729  
Twin, terminal antenna RTV subscriber, type F



GPA-WS/00 1725  
Terminal antenna RTV-SAT subscriber



GPA-WSP/00\* 1726  
Through antenna RTV-SAT subscriber



GPA-W2S/00 1727  
Terminal antenna RTV-SAT subscriber with two outlets SAT

\* on request

## Quick and easy installation of wiring accessories



Safety shutters protect children from electric shock by preventing the insertion of metal objects into the socket apertures.




The enclosed design of the self-returning mounting claws protects the installer's fingers from accidental injury.



Side wire entry allows for a visual quality check of the terminal connections even after the socket module has been fully installed in the wall box.

### SOCKETS



Side wire entry allows for quality control of the terminal connections even after the switch module has been fully installed in the mounting box.

A two-color (silver and gold) screw designation system makes it easy to identify the power supply terminal.



The replaceable illumination module allows you to choose the color of the emitted light, ensuring a perfect match with your interior design.

### SWITCHES



Mounting claws equipped with snap-on base elements significantly simplify the installation of the switch module in the mounting box.



Upgrading the protection rating of switches to ip44 by installing an additional sealing kit.



**The Akcent series** successfully combines sharp, geometric cuts with a delicate, three-dimensional form.


# Akcent

High-quality materials ensure the long-standing popularity of this series among professionals and private users.



## AVAILABLE COLOURS

### AVAILABLE COLOURS



ŁP-1A/00 – White



ŁP-1A/01 – Beige



ŁP-1A/24 – Brown

## Flush mounting switches

Screw terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-20



ŁP-1A/00  
 Single pole switch

960



ŁP-2A/00  
 All-or-part switch, chandelier

961



ŁP-3A/00  
 Two-way switch

962

ŁP-9A/00  
 Two-way switch + single pole switch

418

ŁP-10A/00  
 Double two-way switch

419



ŁP-4A/00  
 Intermediate switch

963



ŁP-5A/00  
 Short-circuiting switch „light”

964




ŁP-6A/00  
 Short-circuiting switch „bell”

965



ŁP-7A/00  
 Venetian blind switch

190




## Flush mounting switches with built-in light

Screw terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-20



ŁP-1AS/00  
 Single pole switch 966



ŁP-2AS/00  
 All-or-part switch, chandelier 967



ŁP-9AS/00  
 Two-way + single pole switch 418

ŁP-10AS/00  
 Double two-way switch 419



ŁP-3AS/00  
 Two-way switch 968



ŁP-4AS/00  
 Intermediate switch 969



ŁP-5AS/00  
 Short-circuiting switch „light” 970



ŁP-6AS/00  
 Short-circuiting switch „bell” 971



ŁP-7AS/00  
 Venetian blind switch 191

Accessories for switches with built-in light are on page 220.

## Flush mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-1A/00  
 Single socket 972



GP-1AP/00  
 Single socket with shutters 972



GP-1AZ/00  
 Single socket with ground 973



GP-1AZP/00  
 Single socket with ground, with shutters 973



GP-1AS/00  
 Single socket with ground schuko 275



GP-1ASP/00  
 Single socket with ground schuko, with shutters 275




GPH-1AZ/00/d  
 Hermetic socket with ground, IP-44 984



GPH-1AS/00/w  
 Hermetic socket with ground schuko, IP-44 277



GPH-1ASP/00/w  
 Hermetic socket with ground schuko, IP-44, with shutters 277



## Flush mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GP-2A/00  
Twin socket 974



GP-2AZ/00  
Twin socket with ground 975



GP-2AS/00  
Twin socket with ground schuko 276



GP-2ASP/00  
Twin socket with ground schuko, with shutters 276



GP-2AC/00  
Twin socket with ground, without changing phase 420

## Computer sockets

Connection IDC



GPK-1A/K/00  
Single computer socket, 5e class, MMC 993



GPK-2A/K/00  
Twin computer socket, 5e class, MMC 994



GPKT-A/K/00  
Conjunct computer and telephone socket, MMC 995

GPK-1A/F/00  
Single computer socket, kat. 5e, FOREX 993

GPK-2A/F/00  
Twin computer socket, kat. 5e, FOREX 994

GPKT-A/F/00  
Conjunct computer and telephone socket FOREX 995

## Telephone sockets

Screw terminals



GPT-1A/00  
Single telephone socket 990



GPT-2AN/00  
Twin telephone socket, independent 991

GPT-2AR/00  
Twin telephone socket, parallel 992

## Antenna subscribers

Screw terminals



GPA-1AF/00 490  
Single, terminal antenna RTV subscriber,  
type F



GPA-2AF/00 2081  
Twin, terminal antenna RTV subscriber,  
type F



GPA-AK/00 985  
Terminal antenna RTV subscriber 2,5-3 dB



GPA-10APZ/00\* 986  
Through antenna RTV subscriber



GPA-AS/00 424  
Terminal antenna RTV-SAT subscriber  
1,5-2 dB



GPA-10AP/00\* 987  
Through antenna RTV subscriber 10 dB  
GPA-14AP/00\* 988  
Through antenna RTV subscriber 14 dB  
GPA-16AP/00\* 989  
Through antenna RTV subscriber 16 dB

## Wall frames



PNP-A/00 256  
Wall frame for switches AKCENT



PNP-AG/00 257  
Wall frame for sockets AKCENT

\* on request

**Multimedia solutions:**  
specifically designed for  
conference halls, offices,  
and hotels.



# Ospel 45

Perfect for the hospitality sector:  
Mediaports enable the effortless  
transformation of dining spaces into  
versatile conference rooms without  
compromising their everyday function.

# Ospel 45

MEDIAPORTS

AVAILABLE COLOURS

00 white

46 warm white

## Switches

Screw terminals  
Rated voltage: 250V  
Rated current: 10AX  
Protection rating: IP-20



ŁK-1/46  
Single pole switch

1800



ŁK-3/46  
Two-way switch

1801



ŁK-5/46  
Short-circuiting switch

1802

## Switches with built-in light

Screw terminals  
Rated voltage: 250V  
Rated current: 10AX  
Protection rating: IP-20



ŁK-1S/46  
Single pole switch

1800



ŁK-3S/46  
Two-way switch

1801



ŁK-5S/46  
Short-circuiting switch

1802

## Blank cover



GKZ-1/46  
Blank cover

1814

## USB Charger

Screw terminals. Rated voltage:  
– input: 100–240~ 50/60Hz 0,2A  
– output: 5VDC  
Rated current: 2,1A  
Protection rating: IP-20



GK-2USB/46  
USB Charger

1823

## Sockets

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-20



GK-1/46 \*  
Single socket

1803



GK-1P/46 \*  
Single socket with shutters

1803



GK-1Z/46  
Single socket with ground

1804



GK-1ZP/46  
Single socket with ground,  
with shutters

1804




GK-1S/46  
Single socket with ground schuko

1807




GK-1SP/46  
Single socket with ground schuko,  
with shutters

1807



GK-1ZD/22  
Single socket with ground DATA

1805



GK-1ZDP/22  
Single socket with ground DATA, with  
shutters

1805



GK-1ZK/22  
Single socket with ground DATA,  
with access key

1806

## Socket covers



GKK-1/p/46  
Socket cover Keystone type

1810

## Loudspeaker socket



GKG-1/46  
Single loudspeaker socket

1813

## Equipotential socket



GKE-1/46 \*  
Equipotential socket

1815

Modules which can be mounted in this socket cover are on page 167.

\* on request

# Ospel 45

MEDIAPORTS

## Hermetic, surface-mounted boxes

Insulation resistance: 400V  
Protection rating: IP-55



PNH45-1  
Single wall frame

1851



PNH45-2  
Twin wall frame

1852

**Surface-mounted products** with IP44 protection rating.



# Madera

The offer also includes ready-to-use hermetic sets, guaranteeing safety and a flawless appearance. This series is recommended for areas with higher humidity or in the proximity of water.

## Surface mounting switches

Screw terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-44



£NH-1N/00 1270  
 Single pole switch



£NH-2N/00 1271  
 All-or-part switch, chandelier



£NH-3N/00 1272  
 Two-way switch



£NH-4N/00 1273  
 Intermediate switch



£NH-5N/00 1274  
 Short-circuiting switch „light“



£NH-6N/00 1274  
 Short-circuiting switch „bell“



£NH-7N/00 1275  
 Venetian blind switch



£NH-11N/00 1276  
 Double pole switch

## Surface mounting switches with built-in light

Screw terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-44



£NH-1NS/00 1270  
 Single pole switch



£NH-2NS/00 1271  
 All-or-part switch, chandelier



£NH-3NS/00 1272  
 Two-way switch

## AVAILABLE COLOURS



£NH-4NS/00 1273  
 Intermediate switch



£NH-5NS/00 1274  
 Short-circuiting switch „light“



£NH-6NS/00 1274  
 Short-circuiting switch „bell“



£NH-7NS/00 1275  
 Venetian blind switch



£NH-11NS/00 1276  
 Double pole switch

## Surface mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-44

Hermetic sockets in white colour are also offered with lid in white colour. After right product's code write: .../00/w



GNH-1NZ/00/d 1277  
 Single socket with ground



GNH-1NZP/00/d 1277  
 Single socket with ground, with shutters



GNH-1NS/00/d 1279  
 Single socket with ground schuko



GNH-1NSP/00/d 1279  
 Single socket with ground schuko, with shutters



GNH-2NZ/00/d 1278  
 Twin socket with ground



GNH-2NZP/00/d 1278  
 Twin socket with ground, with shutters

# Madera

HERMETIC. SURFACE-MOUNTED SERIES



GNH-2NS/00/d 1280  
Twin socket with ground schuko



GNH-2NSP/00/d 1280  
Twin socket with ground schuko, with shutters



GNH-3NZ/00/d 1283  
Triple socket with ground



GNH-3NZP/00/d 1283  
Triple socket with ground, with shutters



GNH-3NS/00/d 1284  
Triple socket with ground schuko



GNH-3NSP/00/d 1284  
Triple socket with ground schuko, with shutters

## Sets



ZH-N1G/00/d 1285  
Single pole switch + Single socket



ZH-N12G/00/d 1287  
All-or-part switch + Single socket



ZH-N1SG/00/d 1286  
Single pole switch with built-in light + Single socket



ZH-N12SG/00/d 1288  
All-or-part switch with built-in light + Single socket



**Ideal for bathrooms**  
and laundries, as well  
as garages and  
warehouses.

# Fala

The ideal surface-mount solution  
for installations requiring electrical  
fittings with an enhanced IP rating.



## AVAILABLE COLOURS



White - nr 00



Ash / Graphite - nr 71/21

## AVAILABLE COLOURS

00 white

71 ash / graphite  
- only selected products

## Surface mounting switches

Screw terminals  
Rated voltage: 250V  
Rated current: 10AX  
Protection rating: IP-44



£NH-1H/00\*  
Single pole switch

100



£NH-2H/00\*  
All-or-part switch, chandelier

101



£NH-3H/00\*  
Two-way switch

102



£NH-4H/00  
Intermediate switch

103



£NH-5H/00\*  
Short-circuiting switch „light“

104



£NH-6H/00  
Short-circuiting switch „bell“

105



£NH-7H/00  
Venetian blind switch

106



£NH-11H/00  
Double pole switch

425

## Surface mounting switches with built-in light

Screw terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-44



£NH-1HS/00  
 Single pole switch

107



£NH-2HS/00  
 All-or-part switch, chandelier

108



£NH-3HS/00  
 Two-way switch

109



£NH-4HS/00  
 Intermediate switch

110



£NH-5HS/00  
 Short-circuiting switch „light“

111



£NH-6HS/00  
 Short-circuiting switch „bell“

112



£NH-7HS/00  
 Venetian blind switch

113



£NH-11HS/00  
 Double pole switch

426

\*Offered in ash colour

## AVAILABLE COLOURS

00 white

71 ash / graphite  
 - only selected products

## Surface mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-44



GNH-1HZ/00/d\*  
 Single socket with ground

114



GNH-1HZP/00/d  
 Single socket with ground,  
 with shutters

114



GNH-1HS/00/d  
 Single socket with ground schuko

116




GNH-1HSP/00/d  
 Single socket with ground  
 schuko, with shutters

116



GNH-2HZP/00/d\*  
 Twin socket with ground

115



GNH-2HZP/00/d  
 Twin socket with ground,  
 with shutters

115

Hermetic sockets in white colour are also offered with lid in white colour. After right product's code write: .../00/w

\*Offered in ash colour

# Fala

HERMETIC, SURFACE-MOUNTED SERIES



GNH-2HS/00/d  
Twin socket with ground schuko

117



GNH-2HSP/00/d  
Twin socket with ground schuko,  
with shutters

117



GNH-3HZ/00/d  
Triple socket with ground

460



GNH-3HSP/00/d  
Triple socket with ground, with shutters

460



GNH-3HS/00/d  
Triple socket with ground schuko

865



GNH-3HSP/00/d  
Triple socket with ground schuko,  
with shutters

865

## Sets



ZH-11G/00/d\*  
Single switch + Single socket

122



ZH-11SG/00/d  
Single pole switch with built-in light  
+ Single socket

124

Sets also available with a all-or-part switch.

\*Offered in ash colour

Our product range ensures that your interior is equipped with all the **necessary switches and power outlets.**



## Bis

Bis is a traditional surface-mounted series with a casual design. It is perfectly suited for utility and technical rooms.

## AVAILABLE COLOURS

AVAILABLE COLOURS

00 white

24 brown



ŁN-1B/00 - White



ŁN-1B/24 - Brown

## Surface mounting switches

Screwless terminals  
Rated voltage: 250V  
Rated current: 10AX  
Protection rating: IP-20



ŁN-1B/00  
Single pole switch

316



ŁN-2B/00  
All-or-part switch, chandelier

317



ŁN-3B/00  
Two-way switch

318



ŁN-4B/00  
Intermediate switch

319



ŁN-5B/00  
Short-circuiting switch „light“

320



ŁN-6B/00  
Short-circuiting switch „bell“

320



ŁN-7B/00  
Venetian blind switch

324

## Surface mounting switches with built-in light

Screwless terminals  
 Rated voltage: 250V  
 Rated current: 10AX  
 Protection rating: IP-20



£N-1BS/00  
 Single pole switch 325



£N-2BS/00  
 All-or-part switch, chandelier 326



£N-3BS/00  
 Two-way switch 327



£N-4BS/00  
 Intermediate switch 328



£N-5BS/00  
 Short-circuiting switch „light” 330



£N-6BS/00  
 Short-circuiting switch „bell” 330



£N-7BS/00  
 Venetian blind switch 333

## Surface mounting socket outlets

Screw terminals  
 Rated voltage: 250V  
 Rated current: 16A  
 Protection rating: IP-20



GN-1B/00  
 Single socket 334



GN-1BP/00  
 Single socket with shutters 334



GN-1BZ/00  
 Single socket with ground 335



GN-1BZP/00  
 Single socket with ground, with shutters 335



GN-1BS/00  
 Single socket with ground schuko 339



GN-1BSP/00  
 Single socket with ground schuko, with shutters 339

## Surface mounting socket outlets

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-20



GN-2B/00  
Twin socket 336



GN-2BP/00  
Twin socket  
with shutters 336



GN-2BZ/00  
Twin socket with ground 337



GN-2BZP/00  
Twin socket with ground,  
with shutters 337



GN-2BS/00  
Twin socket  
with ground schuko 340



GN-2BSP/00  
Twin socket  
with ground schuko,  
with shutters 340



GN-2BC/00  
Twin socket with ground,  
without changing phase 338

**Durable build**  
quality guarantees  
operational safety.



# Delfina

Our surface-mounted range is the perfect choice for environments where exposure to water and humidity is a concern.

## Surface mounting switches

Screw terminals  
Rated voltage: 250V  
Rated current: 16AX  
Protection rating: IP-44



£NH-1D/00 900  
Single pole switch



£NH-2D/00 901  
All-or-part switch, chandelier



£NH-3D/00 902  
Two-way switch



£NH-4D/00 903  
Intermediate switch



£NH-5D/00 904  
Short-circuiting switch „light”



£NH-6D/00 905  
Short-circuiting switch „bell”

## Surface mounting socket outlets

Screw terminals  
Rated voltage: 250V  
Rated current: 16A  
Protection rating: IP-44



GNH-1DZ/00/w 914  
Single socket with ground



GNH-1DS/00/w 912  
Single socket with ground schuko



GNH-2DZ/00/w 915  
Twin socket with ground



GNH-2DS/00/w 913  
Twin socket with ground schuko



£NH-1D/00 White



£NH-1D/30 Grey

## Available colours

**Plugs and socket-outlets**  
are designed for use in  
both fixed and portable  
installations.



## Industrial plugs and sockets

Designed for both industrial and domestic installations, as well as service workshops, commercial facilities, and farms. This equipment can be used both indoors and outdoors. The operating ambient temperature range for these devices is  $-25^{\circ}\text{C}$  to  $+40^{\circ}\text{C}$ . The enclosures ensure safety of use and an IP44 protection rating in accordance with the PN-EN-60309 standard.

# Industrial plugs and sockets

## Portable plugs

Standard: PN-EN 60309  
 Terminal type: Screw terminals  
 Quick-lock system: YES  
 Protection rating: IP44 Splash-proof  
 Un = 380V-415V~, 50Hz  
 Contact material: Brass  
 Earthing: YES  
 Material PA6  
 Indoor and outdoor use  
 Cable entry: Rear  
 Cable sleeve: YES  
 Clock hour position: 6h



WSP-4-16/22/30 837  
 Portable plug 400V 16A  
 Type: 16A / 4P  
 Number of poles: 4  
 Contact configuration: 3P+E  
 Wire connection capacity: max. 6 mm<sup>2</sup>  
 In = 16A



WSP-4-32/22/30 839  
 Portable plug 400V 32A  
 Type: 32A / 4P  
 Number of poles: 4  
 Contact configuration: 3P+E  
 Wire connection capacity: max. 10 mm<sup>2</sup>  
 In = 32A



WSP-5-16/22/30 840  
 Portable plug 400V 16A  
 Type: 16A / 5P  
 Number of poles: 5  
 Contact configuration: 3P+N+E  
 Wire connection capacity: max. 6 mm<sup>2</sup>  
 In = 16A



WSP-5-32/22/30 841  
 Portable plug 400V 32A  
 Type: 32A / 5P  
 Number of poles: 5  
 Contact configuration: 3P+N+E  
 Wire connection capacity: max. 10 mm<sup>2</sup>  
 In = 32A

## Portable sockets

Standard: PN-EN 60309  
 Terminal type: Screw terminals  
 Quick-lock system: YES  
 Protection rating: IP44 Splash-proof  
 Wire connection capacity: max 10 mm<sup>2</sup>  
 Un = 380V-415V~, 50Hz  
 Contact material: Brass  
 Earthing: YES  
 Material PA6  
 Indoor and outdoor use  
 Cable entry: Rear  
 Cable sleeve: YES  
 Clock hour position: 6h



GSP-4-16/22/30 842  
 Portable socket 400V 16A  
 Type: 16A / 4P  
 Number of poles: 4  
 Contact configuration: 3P+E  
 In = 16A



GSP-4-32/22/30 843  
 Portable socket 400V 32A  
 Type: 32A / 4P  
 Number of poles: 4  
 Contact configuration: 3P+E  
 In = 32A



GSP-5-16/22/30 844  
 Portable socket 400V 16A  
 Type: 16A / 5P  
 Number of poles: 5  
 Contact configuration: 3P+N+E  
 In = 16A



GSP-5-32/22/30 845  
 Portable socket 400V 32A  
 Type: 32A / 5P  
 Number of poles: 4  
 Contact configuration: 3P+N+E  
 In = 32A

# Industrial plugs and sockets

## Wall-mounted sockets

Standard: PN-EN 60309  
 Terminal type: Screw terminals  
 Quick-lock system: YES  
 Protection rating: IP44 Splash-proof  
 Wire connection capacity: max 100mm<sup>2</sup>  
 Un = 380V-415V~, 50Hz  
 Contact material: Brass  
 Earthing: YES  
 Material PA6 + PCGF  
 Indoor and outdoor use  
 Cable entry: Rear and bottom  
 Clock hour position: 6h



GSS-4-16/22/30 842  
 Wall-mounted socket 400V 16A  
 Type: 16A / 4P  
 Number of poles: 4  
 Contact configuration: 3P+E  
 In = 16A



GSS-4-32/22/30 843  
 Wall-mounted socket 400V 32A  
 Type: 32A / 4P  
 Number of poles: 4  
 Contact configuration: 3P+E  
 In = 32A



GSS-5-16/22/30 844  
 Wall-mounted socket 400V 16A  
 Type: 16A / 5P  
 Number of poles: 5  
 Contact configuration: 3P+N+E  
 In = 16A



GSS-5-32/22/30 845  
 Wall-mounted socket 400V 32A  
 Type: 32A / 5P  
 Number of poles: 5  
 Contact configuration: 3P+N+E  
 In = 32A

## Panel-mounted socket

Standard: PN-EN 60309  
 Terminal type: Screw terminals  
 Quick-lock system: YES  
 Protection rating: IP44 Splash-proof  
 Wire connection capacity: max 10 mm<sup>2</sup>  
 Un = 380V-415V~, 50Hz  
 Contact stability: Reliable contact thanks to spring-loaded system  
 Contact material: Brass  
 Earthing: YES  
 Material PA6  
 Indoor and outdoor use  
 Clock hour position: 6h



GSW-4-16/22 842  
 Panel-mounted socket 400V 16A  
 Type: 16A / 4P  
 Number of poles: 4  
 Contact configuration: 3P+E  
 In = 16A



GSW-4-32/22 843  
 Panel-mounted socket 400V 32A  
 Type: 32A / 4P  
 Number of poles: 4  
 Contact configuration: 3P+E  
 In = 32A



GSW-5-16/22 844  
 Panel-mounted socket 400V 16A  
 Type: 16A / 5P  
 Number of poles: 5  
 Contact configuration: 3P+N+E  
 In = 16A



GSW-5-32/22 845  
 Panel-mounted socket 400V 32A  
 Type: 32A / 5P  
 Number of poles: 5  
 Contact configuration: 3P+N+E  
 In = 32A



# Accessories

The Ospel range offers comprehensive solutions for electrical installations, featuring a wide selection of conduits, transformers, power cords, and essential accessories such as cable clips.

# Accessories

## Accessories for switches with built-in light



KS-1  
Capacitor for energy-saving fluorescent lamps

344



KS-2  
Bypass for LED light sources

4000



LP-1N  
Light module LTS, blue

347

LP-1P  
Light module LTS, orange

347

LP-2N  
Light module LED, blue

347

LP-2C  
Light module LED, red

347

LP-2B  
Light module LED, white

347

LP-2Z  
Light module LED, green

347

Replaceable backlight module for series: Aria, Sonata, Impresja, As, Karo, Kier.  
Not applicable to the Szafir series.  
ATTENTION: Backlight modules are not compatible with: two-way + single-pole, double two-way, double short-circuiting, and triple short-circuiting switches.

## Plugs

Rated voltage: 250V  
Rated current: 16A



WPZ/00  
Straight plug 2P+⚡/I

957



WKZ/00  
Angled plug 2P+⚡/I

959

## Hermetic boxes and junction boxes

Rated voltage: 400V



ONH-4A5  
Surface-mounted junction box, 4x4 mm², 4 outlets, 5-way, threadless grommets, IP-44

854



ONH-4B5  
Surface-mounted junction box, 4x4 mm², 4 outlets, 5-way, threaded cable glands, IP-67

855

## Electrical conduits

Operating temperature: transport, installation and usage: -5°C to +60°C  
Flammability class: minimum V-1  
Length: 25 m, 50 m

Compression strength: **320N**  
Color: grey



### Corrugated installation conduits without draw wire

RKI-16A	751
Dimensions: ID Ø 11.2mm / OD Ø 16mm	
RKI-20A	752
Dimensions: ID Ø 15,2mm / OD Ø 20mm	
RKI-25A	753
Dimensions: ID Ø 18mm / OD Ø 25mm	
RKI-32A	754
Dimensions: ID Ø 24mm / OD Ø 32mm	

### Corrugated installation conduits with draw wire

RKI-16AP	751
Dimensions: ID Ø 11.2mm / OD Ø 16mm	
RKI-20AP	752
Dimensions: ID Ø 15,2mm / OD Ø 20mm	
RKI-25AP	753
Dimensions: ID Ø 18mm / OD Ø 25mm	
RKI-32AP	754
Dimensions: ID Ø 24mm / OD Ø 32mm	

Compression strength: **750N**  
Color: dark grey



### Corrugated installation conduits without draw wire

RKI-16B	757
Dimensions: ID Ø 10mm / OD Ø 16mm	
RKI-20B	758
Dimensions: ID Ø 14mm / OD Ø 20mm	
RKI-25B	759
Dimensions: ID Ø 18mm / OD Ø 25mm	
RKI-32B	760
Dimensions: ID Ø 24mm / OD Ø 32mm	

### Corrugated installation conduits with draw wire

RKI-16BP	757
Dimensions: ID Ø 10mm / OD Ø 16mm	
RKI-20BP	758
Dimensions: ID Ø 14mm / OD Ø 20mm	
RKI-25BP	759
Dimensions: ID Ø 18mm / OD Ø 25mm	
RKI-32BP	760
Dimensions: ID Ø 24mm / OD Ø 32mm	

## Installation boxes with pockets



PP-F1X60GL-P-K  
Single installation box

659




PP-F2x60GL-P-K  
Double end-installation box with pocket, with screws, 2 x Ø60, box depth: 60 mm, pocket depth: 50 mm

660



PU.P60L-GL  
Connector for single installation boxes




# Technical

## Information


To facilitate installation work, we provide an extensive collection of wiring diagrams for switches and RTV sockets. Numerous installation and programming manuals for OSPEL products are also available.

# Wiring diagrams


## Switch wiring diagrams




Single pole switch




Single pole switch with built-in light




All-or-part switch




All-or-part switch with built-in light




Short-circuiting switch




Short-circuiting switch with built-in light




Triple switch




Triple switch with built-in light




Control switch




Double pole switch




Double pole switch with built-in light



Double short-circuiting switch




Capacitor connection method




Hotel switch


## Switch compatibility




Intermediate switch (compatibility of double two-way switches with intermediate switches)




Intermediate switch with built-in light (compatibility of double two-way switches with intermediate switches)




Double two-way switches (compatibility)




Two-way switches (compatibility)



Two-way switches with built-in light (compatibility)



Compatibility of two integrated switches (two-way + single-pole)




Compatibility of two integrated switches (two-way + single-pole)


# Wiring diagrams




Venetian blind switches for series:  
Impresja, Sonata, As, Karo, Kier, Aria




Venetian blind switch



Venetian blind switch  
with built-in light




Venetian blind switch  
with mechanical lock




Venetian blind switch  
with built-in light with  
mechanical lock

Venetian blind switches for series:  
Akcent, Fala, Madera, Bis




Venetian blind switch




Venetian blind switch  
with built-in light

Push-turn dimmer adapted to incandescent and halogen  
loading for series: Impresja, Sonata, As, Karo, Kier, Aria



Push turn dimmer




Compatibility of push-turn dimmer with two-way switch


# Wiring diagrams




## Universal dimmer (LED)




Universal dimmer




Universal dimmer - Two-way Installation (Option 1)



Universal Dimmer - Two-way Installation (Option 2)




Dimmer with 12V halogen lamps and electronic transformer (2)




Dimmer with 12V LED strips, electronic transformer (2) and AC/DC dimmable driver (3)

## Electronic movement detector




Electronic movement detector


## Compatibility of electronic movement detectors




Electronic movement detector + single pole switch




Electronic movement detector + two way switch




Electronic movement detector + all-or-part switch



Electronic movement detector + 2 two way switches



Multiple movement detectors with a single-pole switch




Electronic movement detector + control switch


# Wiring diagrams



## Temperature regulators




Temperature regulator with aerial sensor




Temperature regulator with underfloor sensor


## Sonata TOUCH




Single pole switch



All-or-part switch




Triple switch




Two-way switches

1. The light source can be connected to any switch within the system.




Double two-way switches

1. The light source can be connected to any switch within the system.




Two-way switches with intermediate function

1. The light source can be connected to any switch within the system.




Double two-way switches with function of double intermediate switch

1. The light source can be connected to any switch within the system.



Venetian blind switch



LED bypass module

### Synchronization of two-way switches

Standard two-way systems and multi-point systems with intermediate function.

Step-by-step instructions:

1. Touch and hold the touch field for approximately 5 seconds until the backlight reacts (the backlight will briefly change color to purple) and you hear a short beep.
2. Touch the touch field on the next switch (within a maximum of 30 seconds) that you wish to pair within the same circuit.
3. Synchronization completed.
4. For systems with three or more switches (intermediate switch configuration), repeat this process for each additional switch in the circuit.
5. For double two-way switches, the synchronization process described above must be performed for each lighting circuit separately.

### Cancelling synchronization – factory Reset

6. Touch and hold the touch field for approximately 10 seconds until the backlight reacts twice (the backlight will briefly change color to purple twice) and you hear two short beeps.
7. Immediately release the touch field after the second beep.
8. Synchronization cancelled.

### Bypass - przeciwzakłóceńowy

Calibration issues:


- The switch is unable to complete its calibration process (indicated by a pulsing backlight or the backlight dimming upon touching the touch field).
- The light source flickers or fails to turn off completely (remains glowing) when switched off.

In such instances, it is necessary to increase the rated current or install the KS-2 Bypass module as shown in the wiring diagram. A single bypass module is sufficient for each lighting circuit, regardless of the number of light sources within that circuit.


Compatibility: Designed to stabilize low-power LED loads and ensure proper power supply to the switch's internal electronics.

# Wiring diagrams


## Sonata TOUCH




Single pole touch switch



All-or-part switch




Triple touch switch




Touch switches in a two-way (multi-point) system


## Sonata TOUCH



Double two-way switches



Two-way touch switches with intermediate functionality



Double touch two-way switches with double intermediate function





**OSPTEL S.A.**

ul. Główna 128, Wierbka 42-436 Pilica  
tel./fax: +48 32 67 37 106-110  
fax: +48 32 75 08 499  
ospel@ospel.com.pl

**[www.ospel.com.pl](http://www.ospel.com.pl)**

